

No. MC 127526 (Sub-No. 1 TA), filed February 16, 1970. Applicant: CECIL N. BUCHOLZ, 201 Second Avenue SW., Watertown, S. Dak. 57201. Applicant's representative: D. K. Loucks, 17 Second Avenue SW., Watertown, S. Dak. 57201. Authority sought to operate as a *contract carrier*, by motor vehicle, over irregular routes, transporting: *Malt beverages, advertising matter and supplies*, from Milwaukee, Wis., and Omaha, Nebr., to Watertown, S. Dak.; and *empty containers*, from Watertown, S. Dak., to Milwaukee, Wis., and Omaha, Nebr., for 180 days. Supporting shippers: Kahnke's Watertown Beverage Co., Rural Route 2, Watertown, S. Dak. 57201; and Brewster Distributing Co., 174½ North Maple Street, Watertown, S. Dak. 57201. Send protests to: J. L. Hammond, District Supervisor, Interstate Commerce Commission, Bureau of Operations, Room 369, Federal Building, Pierre, S. Dak. 57501.

No. MC 134305 TA (Correction), filed February 2, 1970, published in the FEDERAL REGISTER issue Notice No. (21) and republished as corrected, this issue. Applicant: HARRY E. MAMM, doing business as HAMM TRUCKING, Rural Route No. 1, Erie, Ill. 61250. Applicant's representative: Albert A. Andrin, 39 South La Salle Street, Chicago, Ill. 60603. Authority sought to operate as a *common carrier*, by motor vehicle, over irregular routes, transporting: *Dry milk solids, including casein, sodium caseinate, co-precipitate and whey*; (1) from Erie, Ill., to Detroit, Mich.; Bowling Green, Rittman, and Wapakoneta, Ohio; Indianapolis, Ind.; Carthage, Kansas City, and Trenton, Mo.; Green Bay and Hager City, Wis.; Minneapolis and Rogers, Minn.; Cedar Rapids and Davenport, Iowa; (2) from Trenton, Mo., to Erie, Ill., for 180 days. NOTE: The purpose of this republication is to include the territorial description, which was inadvertently omitted in previous publication. Supporting shipper: The Erie Casein Co., Erie, Pa. Send protests to: Andrew J. Montgomery, District Supervisor, Interstate Commerce Commission, Bureau of Operations, 1086 U.S. Courthouse and Federal Office Building, 219 South Dearborn Street, Chicago, Ill. 60604.

No. MC 134334 (Sub-No. 1 TA), filed February 16, 1970. Applicant: DEAN H. PETERSEN & SON, INC., 367 Garden Street, Bennet, Nebr. 68317. Applicant's representative: Fred Coffman, Post Office Box 806, Lincoln, Nebr. 68501. Authority sought to operate as a *contract carrier*, by motor vehicle, over irregular routes, transporting: *Dairy product ingredients* used in manufacture of confections, from Sabetha, Kans., to Lincoln, Nebr., for the account of Russell Stover Candies, Inc., for 180 days. Supporting shipper: Russell Stover Candies, Inc., 1221 Baltimore Avenue, Kansas City, Mo. 64105. Send protests to: District Supervisor Johnston, Bureau of Operations, Interstate Commerce Commission, 315 Post Office Building, Lincoln, Nebr. 68508.

No. MC 134340 TA, filed February 16, 1970. Applicant: ROBERT H. PARSONS, doing business as ROBERT PAR-

SONS TRUCKING, 1500 Adams Avenue, Oshkosh, Wis. 54901. Applicant's representative: William C. Dineen, 412 Empire Building, 710 North Plankinton Avenue, Milwaukee, Wis. 43203. Authority sought to operate as a *contract carrier*, by motor vehicle, over irregular routes, transporting: *Corrugated boxes, built-up assembled box parts, corrugated logs or rolls, pallets, and rolls of pulpboard*, from the plantsite and warehouse facilities of Georgia-Pacific Corp. at Oshkosh, Wis., to points in Illinois, Iowa, Michigan, and Minnesota, for 180 days. Supporting shipper: Georgia-Pacific Corp., Post Office Box 199, Oshkosh, Wis. 54902 (Jack B. Mitchell). Send protests to: District Supervisor Lyle D. Helfer, Interstate Commerce Commission, Bureau of Operations, 135 West Wells Street, Room 807, Milwaukee, Wis. 53203.

No. MC 134342 TA, filed February 16, 1970. Applicant: JAMES PLOG, 301 East Main Street, Milledgeville, Ill. 61051. Applicant's representative: Melvin N. Routman, 306-308 Reisch Building, Springfield, Ill. 62701. Authority sought to operate as a *contract carrier*, by motor vehicle, over irregular routes, transporting: *Dry animal, livestock and poultry feeds, feed supplements and feed ingredients*, from Rock Falls, Ill., to points in Cedar, Clinton, Dubuque, Jackson, Jones, Muscatine, and Scott Counties, Iowa, for the account of W. R. Grace & Co., for 180 days. Supporting shipper: W. R. Grace & Co., Memphis, Tenn. Send protests to: Andrew J. Montgomery, District Supervisor, Interstate Commerce Commission, Bureau of Operations, 1086 U.S. Courthouse and Federal Office Building, 219 South Dearborn Street, Chicago, Ill. 60604.

By the Commission.

[SEAL]

H. NEIL GARSON,
Secretary.

[FR. Doc. 70-2266; Filed, Feb. 24, 1970;
8:47 a.m.]

[Notice 496]

MOTOR CARRIER TRANSFER PROCEEDINGS

FEBRUARY 19, 1970.

Synopses of orders entered pursuant to section 212(b) of the Interstate Commerce Act, and rules and regulations prescribed thereunder (49 CFR Part 1132), appear below:

As provided in the Commission's special rules of practice any interested person may file a petition seeking reconsideration of the following numbered proceedings within 20 days from the date of publication of this notice. Pursuant to section 17(8) of the Interstate Commerce Act, the filing of such a petition will postpone the effective date of the order in that proceeding pending its disposition. The matters relied upon by petitioners must be specified in their petitions with particularity.

No. MC-FC-71756. By order of February 13, 1970, the Motor Carrier Board approved the transfer to Martin E. Davis,

Donald R. Gardner and Billy W. Gist, a partnership, doing business as Martin E. Davis, and Donald R. Gardner, and Billy W. Gist, St. Louis, Mo., of the operating rights in certificate No. MC-2442 issued June 10, 1949, to Hugo Redhage and Erna Redhage, a partnership, doing business as Redhage Truck Line, Oermann, Mo., authorizing the transportation of general commodities, except those of unusual value, and except dangerous explosives, household goods, commodities in bulk, commodities requiring special equipment, and those injurious or contaminating to other lading, over a regular route, between Richwoods, Mo., and National Stock Yards, Ill., serving all intermediate points and certain off-route points. Thad F. Niemira, 4619 Hampton Avenue, St. Louis, Mo. 63109, attorney for applicants.

No. MC-FC-71877. By order of February 11, 1970, the Motor Carrier Board approved the transfer to Humansville Truck Line, Inc., Humansville, Mo., of certificate No. MC-52642 and certificates of registrations Nos. MC-52642 (Sub-No. 2) and MC-52642 (Sub-No. 3) issued to C. M. McNeely and Pearl McNeely, doing business as Humansville Truck Line, Humansville, Mo., covering the transportation of: General commodities between specified points in Missouri. Herman W. Huber, 101 East High Street, Jefferson City, Mo. 65101, attorney for applicants.

No. MC-FC-71893. By order of February 16, 1970, the Motor Carrier Board approved the transfer to Gerald R. Fischer and LeRoy A. Fischer, a partnership, doing business as Fischer Brothers, Box 736, Hartington, Nebr. 68739, of certificate No. MC-92018, issued February 11, 1957, to Coleridge Elevator Co., Inc., Coleridge, Nebr. 68727, authorizing the transportation of:

Agricultural implements and parts, grain, feed, hardware, and building materials, from Sioux City, Iowa, to Coleridge, Nebr., serving the intermediate and off-route points within 75 miles of Coleridge, Nebr., for delivery only; from Sioux City over U.S. Highway 20 to junction Nebraska Highway 15, thence over Nebraska Highway 15 to Coleridge, and return over the same route with no transportation for compensation except as otherwise authorized.

Emigrant movables, between Coleridge, Nebr., and points within 15 miles thereof, on the one hand, and, on the other, points in that part of Iowa on and north of U.S. Highway 6, and points in that part of South Dakota on and south of U.S. Highway 14 and east of the Missouri River.

Grain, Hay, and Livestock, between Coleridge, Nebr., and points within 15 miles thereof, on the one hand, and, on the other points in that part of Iowa on and north of U.S. Highway 30 and on and west of U.S. Highway 71, and points in that part of South Dakota on and south of U.S. Highway 14 and east of the Missouri River.

No. MC-FC-71902. By order of February 16, 1970, the Motor Carrier Board

approved the transfer to Groups Unlimited, Inc., New York, N.Y., of the license in No. MC-12426 issued December 8, 1959, to Scenic Pleasure Tours, Inc., New York, N.Y., authorizing the holder to engage as a broker at New York, N.Y., Atlantic City, N.J., Philadelphia, Pa., and Baltimore, Md., in the arrangement of transportation for passengers and their baggage, in round-trip all-expense tours, by motor vehicle or by a combination of motor vehicle and other means of transportation, beginning and ending at New York, N.Y., and extending between points in the United States, except Alaska and Hawaii. Sidney J. Leshin, 501 Madison Avenue, New York, N.Y. 10022, attorney for applicants.

No. MC-FC-71908. By order of February 13, 1970, the Motor Carrier Board approved the transfer to Wayne E. Schroeder, 513 Ann Street, Manning, Iowa 51455, of the operating rights in certificate No. MC-6864 issued April 26, 1949, to Chris Schmidt, 423 10th Street,

Manning, Iowa 51455, authorizing the transportation of livestock and agricultural commodities, between Manning, Iowa, and Omaha, Nebr., serving intermediate and off-route points within 15 miles of Manning, Iowa; and mill feeds, building materials, farm machinery and parts, and farm hardware, from Omaha, Nebr., to Manning, Iowa, serving intermediate and off-route points within 15 miles of Manning, Iowa.

[SEAL]

H. NEIL GARSON,
Secretary.[F.R. Doc. 70-2264; Filed, Feb. 24, 1970;
8:47 a.m.]

[Ex Parte No. 252 (Sub. No. 1)]

**INCENTIVE PER DIEM CHARGES,
1968**

FEBRUARY 20, 1970.

The order of December 12, 1969, served December 22, 1969, intended that persons, including respondents, who desired to

participate actively in the proceeding would notify the Secretary on or before January 23, 1970, to have their names placed on the service list to receive copies of pleadings filed with the Commission.

It has come to the attention of the Commission that a number of respondent carriers did not notify the Secretary that they desired to have their names placed on the service list as active participants for the receipt of verified statements and pleadings. To avoid a multiplicity of calls requesting to be placed on the service list, all respondent carriers are hereby notified again that if they desire to have their names placed on the service list, they should notify the Office of the Secretary in writing on or before March 2, 1970. Thereafter, a supplemental service list will be issued.

[SEAL]

H. NEIL GARSON,
Secretary.[F.R. Doc. 70-2333; Filed, Feb. 24, 1970;
8:48 a.m.]**CUMULATIVE LIST OF PARTS AFFECTED—FEBRUARY**

The following numerical guide is a list of parts of each title of the Code of Federal Regulations affected by documents published to date during February.

1 CFR	Page	5 CFR	Page	7 CFR—Continued	Page
Appendix A	3552	213	2383,	PROPOSED RULES—Continued	
		2643, 2644, 2765, 2859, 3153, 3279		915	3173
3 CFR		305	3065, 3217	1001	2527
PROCLAMATIONS:		752	3217	1002	2527
1677 (see PLO 4762)	2402	754	3217	1003	2527
2929 (see Proc. 3964)	3645	771	3217	1004	2527
3140 (see Proc. 3964)	3645			1005	2527
3822 (modified by Proc. 3964)	3645	7 CFR		1006	2527, 2878
3958	2571	5	3158	1007	2527
3959	2641	52	3651	1011	2527
3960	2815	301	2577, 2859	1012	2527, 2878
3961	3019	318	2503	1013	2527, 2878
3962	3061	319	2503, 3021	1015	2527
3963	3063	354	2859	1016	2527
3964	3645	401	3279	1030	2527
3965	3649	413	3107	1032	2527
EXECUTIVE ORDERS:		601	2817, 3217	1033	2527
11211 (amended by EO 11506)	2501	722	2721	1034	2527, 2729
11248 (amended by EO 11510)	3105	724	2504-2506	1035	2527
11282 (superseded by EO 11507)	2576	729	2860	1036	2527
11288 (superseded by EO 11507)	2576	811	2383	1040	2527
11353 (revoked by EO 11509)	2857	857	2507	1041	2527, 2730
11368 (see EO 11506)	2501	907	2578, 2860, 3158, 3218	1043	2527
11418 (revoked by EO 11509)	2857	908	2861, 3159	1044	2527
11506	2501	910	2383,	1046	2527
11507	2573	913	2721, 2765, 3021, 3065, 3280, 3652	1049	2527
11508	2855	947	2722, 3021, 3653	1050	2527
11509	2857	966	2766	1060	2527
11510	3105	980	3159	1061	2527
PRESIDENTIAL DOCUMENTS OTHER THAN PROCLAMATIONS AND EXECUTIVE ORDERS:		989	3022, 3160	1062	2527
Regulation of February 11, 1970	2951	1421	3653	1063	2527
			2766, 3107	1064	2527
		PROPOSED RULES:		1065	2527
		52	2668, 2787	1068	2527
		724	2526, 3293	1069	2527
		729	2994	1070	2527
		907	2526	1071	2527
		911	3173	1073	2527
				1075	2527

7 CFR—Continued

Page

PROPOSED RULES—Continued

1076	2572
1078	2527
1079	2527
1090	2527
1094	2527
1096	2527
1097	2527
1098	2527, 2669, 3174
1099	2527, 3174
1101	2527
1102	2527
1103	2572
1104	2527
1106	2527
1108	2527
1120	2527
1121	2527, 3293
1124	2527
1125	2527
1126	2527, 3293
1127	2527
1128	2572
1129	2527
1130	2527
1131	2527, 3174
1132	2527
1133	2527
1134	2527
1136	2527
1137	2527
1138	2527

8 CFR

211	3065
212	3065
214	3066

PROPOSED RULES:

103	3172
223a	3172
238	3120, 3233
299	3172

9 CFR

56	3654
74	3022, 3023
76	2507,
	2508, 2644, 2722, 2767, 2817, 2861,
	2953, 3066, 3218, 3654
161	3023

PROPOSED RULES:

2	2729
318	2527

10 CFR

3	2862
14	2723

12 CFR

204	2768
207	3280
217	2768, 2953
220	3280
226	2865
265	2383
329	2768
510	2509
526	2723, 3219
542	2509
543	2509
545	2511, 3024
555	3024, 3107
556	2514
562	2514

12 CFR—Continued

Page

563	3027, 3107
567	2515
569	3027
571	2515
582	2515
591	2725
610	3153

13 CFR

121	2385
PROPOSED RULES:	
107	3032
113	2596, 3041
121	2597

14 CFR

13	2578
21	2818, 3154
37	3154
39	2517,
	2726, 2868, 3108, 3153, 3220, 3281,
	3282
47	2578
61	2818
71	2517,
	2580-2583, 2645, 2646, 2726, 2769,
	2819, 2869, 2953, 3029, 3109, 3110,
	3155, 3156, 3220, 3221, 3282, 3659
73	2769
75	2583, 2584, 2726, 2819, 3659
91	2578, 2818
95	3221
97	2390, 2647, 2954, 3223, 3283
121	2818, 3154
127	3154
135	3154
145	3154
241	2819

PROPOSED RULES:

21	2412
23	3175
25	2412, 3175
27	3175
29	3175
39	2594, 2996
71	2595,
	2670, 2791-2793, 2889, 2890, 2996,
	2997, 3119, 3175, 3176, 3235-3237
73	2595, 3297
75	2596
171	2528
207	2730
211	3300
299	3032
302	3300
399	3300

16 CFR

13	2385-2387,
	2517-2522, 2769-2773, 3156, 3157
15	2655, 2656, 3067
500	3110
501	3110

PROPOSED RULES:

89	3077
118	2673
250	2998

17 CFR

200	3659
240	3660
PROPOSED RULES:	
230	2672

18 CFR

Page

PROPOSED RULES:

2	3240
101	2413
141	2832, 3074
157	3076
201	2413
250	2730

19 CFR

8	3232
10	2822

PROPOSED RULES:

9	2410
---	------

20 CFR

PROPOSED RULES:

405	2593
-----	------

21 CFR

1	2869
3	2656, 2657, 2774, 3029
5	2584
120	2585, 2727, 3161
121	2727, 2822, 2823, 3161, 3162
135e	3162
135g	3162
146b	2657
147	2657, 2870, 2993
148m	3279
164	2658
191	2659

PROPOSED RULES:

3	2411
120	3233, 3234
130	3073
138	2995
141b	2670
146	3073
146b	2670
191	3119
320	2874

22 CFR

123	3029
125	3029
207	3232

23 CFR

PROPOSED RULES:

255	3176
-----	------

24 CFR

200	2823
Ch. VI	2827
1914	3292
1915	3292

26 CFR

1	2774
13	3030, 3067

29 CFR

8	2387
201	2556
202	2557
203	2561
205	2563
402	2990
403	2990
404	2990
405	2990
406	2990
408	2990

29 CFR—Continued

	Page
409	2990
541	2389, 3220
690	3068
727	2774
1500	2822
1601	3163

PROPOSED RULES:

462	2994
-----	------

30 CFR

55	3660
56	3665
57	3670

31 CFR

316	2827
-----	------

32 CFR

54	3164
65	2870
101	2990
102	2871
115	2775
210	3068
536	2659
564	3111
1715	2873

33 CFR

117	3678
205	3069
207	2660, 2727

PROPOSED RULES:

117	3234
-----	------

35 CFR

253	3232
-----	------

36 CFR

221	3283
261	3165

PROPOSED RULES:

7	2787
---	------

37 CFR

1	2828
3	2828

38 CFR

2	3166
3	2827
17	2389, 3166

39 CFR

PROPOSED RULES:

261	2410
262	2410

41 CFR

1-1	3070, 3283, 3284
1-12	3113
3-1	2992
4-1	3679
4-2	3680
4-3	3681
4-4	3682
4-12	3682, 3683
4-16	3683
5A-2	2399
5A-72	2400
5A-73	2400
5B-3	2585
9-5	2586
14-1	2523
60-2	2586
101-11	3219
101-30	3071

42 CFR

73	2400
----	------

PROPOSED RULES:

71	3119
73	2411
81	2411

43 CFR

1810	3072
1820	3072
1860	3072
2010	3072
2020	3072
2030	3072
2120	3072
2200	3072
2210	3072
2220	3072
2230	3072
2240	3072
2250	3072
2310	3072
2320	3072
2330	3072
4110	2591

PUBLIC LAND ORDERS:

4755 (corrected)	2828
4762	2402
4763	2776

PROPOSED RULES:

23	2994
1840	3173

45 CFR

233	3072
249	3072
1009	3284
1061	2402
1067	3284, 3288

PROPOSED RULES:

85	2791
----	------

46 CFR

2	3706
24	3707
30	3707
31	3709
32	3709
35	3709
38	3709
39	3709
40	3710
70	3710
90	3710
98	3711
110	3712
146	3712
151	3714
175	3713
502	2523
504	3114

47 CFR

2	3169
15	2405, 2660
63	2776
64	2776
73	2590, 2828
81	3169
83	3170
87	2829, 3170
97	3117

PROPOSED RULES:

25	2671
73	2831, 2998, 3120, 3179
74	2672

49 CFR

7	3289
71	2667
371	2409
393	3167
1023	2524
1033	2868
1043	2829
1048	2727, 2992, 3290
1084	2829

PROPOSED RULES:

172	3298
173	3298
174	3298
177	3298
179	2794
192	3237
236	2412
371	3177, 3297
393	3177
Ch. X	2890
1048	2995

50 CFR

28	3170
32	2592
33	2592, 2992, 3171, 3291, 3292, 3684
279	2407

PROPOSED RULES:

280	2526
-----	------

FEDERAL REGISTER

VOLUME 35 • NUMBER 38

Wednesday, February 25, 1970 • Washington, D.C.

PART II

DEPARTMENT OF TRANSPORTATION

Coast Guard

•

Certain Bulk
Dangerous Cargoes
on Unmanned Tank Barges



Title 46—SHIPPING

Chapter I—Coast Guard, Department of Transportation

[CGFR 70-10]

CERTAIN BULK DANGEROUS CARGOES ON UNMANNED TANK BARGES

A notice of proposed rule making was published in the FEDERAL REGISTER of February 7, 1969 (34 F.R. 1831) and in the Merchant Marine Council Public Hearing Agenda dated March 24, 1969 (CG-249). The proposed amendments were identified as Items PH 1-69 to PH 9-69, inclusive. Item PH 10-69 was published in the FEDERAL REGISTER of February 15, 1969 (34 F.R. 2254). The Merchant Marine Council held a public hearing on March 24, 1969 in Washington, D.C. on these ten items in accordance with the terms of the notices. Interested persons were given the opportunity to submit written comments and to make oral comments regarding all the proposed amendments at the public hearing. At the conclusion of the public hearing the Council at an executive session held on March 24 and 25, 1969 duly considered all the proposed amendments and the comments submitted.

This is the third of a series of documents which concerns the amendments considered by the Merchant Marine Council at the public hearing held on March 24, 1969. The first document concerned the proposals designated as Items PH 5-69, PH 9a-69, and that part of Item 4a-69 which involved amendments to Title 33, Code of Federal Regulations. This document was published in the FEDERAL REGISTER of October 29, 1969 (34 F.R. 17478). The second document concerned the proposals designated as Items PH 2-69, PH 3-69, PH 4b and 4c-69, PH 6a and 6b-69, PH 8-69, PH 9b-69, PH 10-69 and that part of PH 4a-69 which involved amendments to Title 46, Code of Federal Regulations. This document was also published in the FEDERAL REGISTER of October 29, 1969 (34 F.R. 17479). This third document concerns the proposals designated as Item PH 1-69. This third document creates a new Subchapter O to Title 46, Code of Federal Regulations which regulates certain bulk dangerous cargoes when carried on unmanned tank barges. In addition, this document makes changes to Subchapters A, C, D, H, I, J, N, and T necessitated by the establishment of Subchapter O. The only remaining item, of the Public Hearing Agenda dated March 24, 1969 is Item PH 7-69 which will appear in a subsequent document.

The regulations promulgated by this document in Part 151, Subchapter O constitutes the first phase of a program to develop regulations for water transportation of all bulk dangerous cargoes

having hazards other than, or in addition to, the conventional flammability and combustibility of petroleum products. The scope of complete program includes all physical forms of such cargoes (solid, liquid, liquefied gas) transported in ships, barges, and portable tanks. However, the present Part 151 is limited to liquids and liquefied gases carried in unmanned barges and include only cargo carrying requirements. Certification as tank barges or cargo barges will continue to be in accordance with the procedures of Subchapter D or Suchapter I. As an interim measure pending development of additional parts to Subchapter O, Part 151 provides that manned barges carrying cargoes regulated by this subchapter will be considered by the Coast Guard on an individual basis and may be required to meet the cargo containment and handling requirements specified for unmanned barges. The additional parts to Subchapter O to complete the program are still being developed by the joint industry and Coast Guard Task Group under the Chemical Transportation Advisory Panel to the Merchant Marine Council of the Coast Guard. These additional regulations will be considered at public hearings in the future.

As a result of its study of the regulations proposed in Item PH 1-69 and the many comments received from the public with respect thereto, the Merchant Marine Council has recommended to the Commandant, U.S. Coast Guard a number of changes in the regulations as originally proposed. The significant changes recommended by the Council are as follows:

1. The proposed method of dealing with cargo compatibility has been changed to make it less restrictive by placing responsibility for cargo compatibility on the shipper and/or owner of the barge. This change avoids the necessity of including lengthy endorsements on the Certificate of Inspection. This change has been effected by altering the cargo separation column and the footnotes in Table 151.05, by deleting §§ 151.05-1(f), 151.13-5(a)(2), by changing §§ 151.13-5(b), 151.13-10(a), and by adding a new § 151.45-4(d)(11).

2. The hull type requirement was reduced from Type II to Type III for acetonitrile, *n*-butyl acrylate, isobutyl acrylate, ethyl acrylate, ethylenediamine, methyl acrylate and methyl methacrylate. This reduction is reflected by changes for these products in Table 151.05.

3. Table 151.01-10(d) was changed to emphasize that all products regulated by Subchapter D (Tank Vessels) are flammable or combustible as defined in Subchapter D.

4. The following products were added to Table 151.01-10(d)—Cargoes to be regulated by Subchapter D: Asphalt blending stocks (roofers flux, straight run residue), cumene, distillates

(straight run, flashed feed stocks), dodecanol, gas oil (cracked), gasolines (straight run, polymer), gasoline blending stocks (alkylates reformates), heptanol, hexanol, ethoxylated dodecanol, ethoxylated pentadecanol, ethoxylated tridecanol, ethoxylated tetradecanol, linear alcohol (12-15 carbon), nonanol, octanol, oils (clarified, road, transformer), pentadecanol, tetradecanol, undecanol, 1-pentene, 1-heptene, 1-octene, 1-decene, 1-undecene, 1-tridecene, 1-tetradecene, and 1-hexene.

5. The word "minimum" was inserted in the first sentence of § 151.01-1(a) to make it clear that Part 151 sets forth only the minimum requirements for unmanned tank barges.

6. In § 151.15-3, a new paragraph (c) has been added and the former paragraph (c) has been made (d). The new paragraph permits cargoes with a specific gravity greater than that for which the scantlings of the tank were designed to be carried provided the maximum cargo weight (tons) in a specific tank does not exceed the maximum cargo weight (tons) endorsed on the Certificate of Inspection, and provided the scantlings are sufficient to prevent rupture under the full head of the higher density cargo.

7. In § 151.50-22, a new paragraph (b) has been added, and the former paragraph (b) has been redesignated as (c). The new paragraph (b) permits the use of compressed air to discharge hydrochloric acid from gravity type cargo tanks if the tanks are of cylindrical shape with dished heads and the air pressure does not exceed the design pressure or 10 pounds per square inch gage.

8. In § 151.50-34(a) the listing of prohibited materials for the construction of equipment coming into contact with vinyl chloride has been changed by adding magnesium, mercury, and silver, and by deleting zinc and lead.

Accordingly, after due consideration of all the relevant matter including the comments of the interested persons and the recommendations of the Merchant Marine Council, the Commandant, U.S. Coast Guard has approved the regulations and the amendments to existing regulations set forth below.

SUBCHAPTER A—PROCEDURES APPLICABLE TO THE PUBLIC

PART 2—VESSEL INSPECTIONS

Subpart 2.01—Inspecting and Certificating of Vessels

§ 2.01-7 [Amended]

1. In § 2.01-7, Table 2.01-7(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

be considered individually by the Com-mandant and may be required to comply with the requirements of Subchapter O of this chapter, as applicable, as well as the requirements of this subchapter.

§ 30.01-5 [Amended]

4. In § 30.01-5(d), Table 30.01-5(d) is amended by adding an eighth column, by adding two footnotes at the end of the Table (footnotes 10 and 11), and by re-vising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 30.01-5(d)

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹				Vessels subject to the provisions of Subchapter O—Certain Bulk Dan-gerous Cargoes ¹⁰	
Method of propulsion	Vessels inspected and certificated un-der Subchapter I—Cargo and Mis-cellaneous Vessels ²	Vessels subject to the provisions of Subchapter O—Certain Bulk Dan-gerous Cargoes ¹⁰	Column 5	Column 8	
Column 1	Column 1	Column 1	Column 5	Column 8	
Steam	***	***	***	***	None.
Motor	***	***	***	***	None.
Sail	***	***	***	***	None.
Nonself-propelled.	***	Those vessels carrying dangerous car-goes when required by 46 CFR Part 146.	***	***	All tank barges carrying certain flammable and combustible liquids and liquefied gases in bulk.
	***	All seagoing barges except those cov-ered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	***	All tank barges carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.
¹¹ For manned tank barges see § 151.01-10(e) of this chapter.

5. Part 30 is amended by adding a new subpart, Subpart 30.25, to read as follows:

Subpart 30.25—Commodities Regulated

§ 30.25-1 Commodities regulated by Subchapter D.

The commodities listed in Table 30.25-1 shall be regulated by Subchap-ter D.

TABLE 30.25-1
Commodities regulated by Subchapter D (If flammable or combustible, see §§ 30.10-15, 30.10-22, and 30.10-39)

Acetone.
Amyl acetate.
n-Decyl alcohol.
Decaldehyde.
1-Decene.

SUBCHAPTER D—TANK VESSELS
PART 30—GENERAL PROVISIONS
Subpart 30.01—Administration

3. Section 30.01-5 is amended by adding paragraph (g) to read as follows:

§ 30.01-5 Application of regulations—TB/ALL.

(g) Manned barges carrying any of the cargoes listed in Table 30.25-5 will

TABLE 2.01-7(e)
Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations¹

Method of propulsion	Vessels inspected and certificated un-der Subchapter I—Cargo and Mis-cellaneous Vessels ²	Vessels subject to the provisions of Subchapter O—Certain Bulk Dan-gerous Cargoes ¹⁰
Column 1	Column 5	Column 8
Steam	***	None.
Motor	***	None.
Sail	***	None.
Nonself-propelled.	***	All tank barges carrying certain flammable and combustible liquids and liquefied gases in bulk.
	***	All seagoing barges except those cov-ered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.
¹¹ For manned tank barges see § 151.01-10(e) of this chapter.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b) (1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655 (b) (1); 49 CFR 1.4 (a) (2))

SUBCHAPTER C—UNINSPECTED VESSELS
PART 24—GENERAL PROVISIONS
Subpart 24.05—Application

§ 24.05-1 [Amended]

2. In § 24.05-1(a), Table 24.05-1(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 24.05-1(a)

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹				Vessels subject to the provisions of Subchapter O—Certain Bulk Dan-gerous Cargoes ¹⁰	
Method of propulsion	Vessels inspected and certificated un-der Subchapter I—Cargo and Mis-cellaneous Vessels ²	Vessels subject to the provisions of Subchapter O—Certain Bulk Dan-gerous Cargoes ¹⁰	Column 5	Column 8	
Column 1	Column 5	Column 1	Column 5	Column 8	
Steam	***	***	***	***	None.
Motor	***	***	***	***	None.
Sail	***	***	***	***	None.
Nonself-propelled.	***	Those vessels carrying dangerous car-goes when required by 46 CFR Part 146.	***	***	All tank barges carrying certain flammable and combustible liquids and liquefied gases in bulk.
	***	All seagoing barges except those cov-ered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	***	All tank barges carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.
¹¹ For manned tank barges see § 151.01-10(e) of this chapter.

TABLE 30.25-1—Continued

Dextrose solution.
 Diacetone alcohol.
 Dicyclopentadiene.
 Diethylbenzene.
 Diethylene glycol.
 Diethylene glycol monoethyl ether.
 Diethylene glycol monomethyl ether.
 Diisobutyl carbinol.
 Diisobutylene.
 Dioctyl phthalate.
 Dipropylene glycol.
 Distillates:
 Straight run.
 Flashed feed stocks.
 Dodecanol.
 Dodecene.
 1-Dodecene.
 Ethane.
 Ethoxylated dodecanol.
 Ethoxylated pentadecanol.
 Ethoxylated tetradecanol.
 Ethoxylated tridecanol.
 Ethoxy triglycol.
 Ethyl acetate.
 Ethyl alcohol.
 Ethyl benzene.
 Ethyl butanol.
 2-Ethyl hexanol.
 Ethyl hexyl tallate.
 Ethylene.
 Ethylene glycol.
 Ethylene glycol monobutyl ether.
 Ethylene glycol monoethyl ether.
 Ethylene glycol monoethyl ether acetate.
 Ethylene glycol monomethyl ether.
 Gas oil:
 Cracked.
 Gasoline blending stocks:
 Alkylates.
 Reformates.
 Gasolines:
 Automotive (containing not over 4.23 grams lead per gallon).
 Aviation (containing not over 4.86 grams lead per gallon).
 Casinghead (natural).
 Polymer.
 Straight run.
 Glycerine.
 Heptane.
 Heptanol.
 Hexane.
 Hexanol.
 1-Hexene.
 Hexylene glycol.
 Isobutyl acetate.
 Isobutyl alcohol.
 Isodecyl alcohol.
 Isodecaldehyde.
 Isohexane.
 Isooctyl alcohol.
 Isooctylaldehyde.
 Isopentane.
 Isopropyl acetate.
 Isopropyl alcohol.
 Jet fuels:
 JP-1 (kerosene).
 JP-3.
 JP-4.
 JP-5 (kerosene, heavy).
 Kerosene.
 Latex, liquid synthetic.
 Linear alcohols (12-15 carbon).
 Methane.
 Methyl alcohol.
 Methyl amyl acetate.
 Methyl amyl alcohol.
 Methyl ethyl ketone.
 Methyl isobutyl ketone.
 Methyl isobutyl carbinol.
 Mineral spirits.
 Molasses, all.
 Naphtha:
 Coal tar.
 Solvent.
 Stoddard solvent.
 VM&P (75 percent naphtha).
 Naphthalene, molten.
 Nonanol.

TABLE 30.25-1—Continued

Nonene.
 1-Nonene.
 Nonyl phenol.
 Octanol.
 1-Octene.
 Oils:
 Clarified.
 Coal tar.
 Crude oil.
 Diesel oil.
 Fuel oil:
 No. 1 (kerosene).
 No. 1-D.
 No. 2.
 No. 2-D.
 No. 4.
 No. 5.
 No. 6.
 Road.
 Transformer.
 Edible oils, including:
 Castor.
 Cotton seed.
 Fish.
 Olive.
 Peanut.
 Soya bean.
 Vegetable.
 Miscellaneous oils, including:
 Absorption.
 Coal tar.
 Lubricating.
 Mineral seal.
 Mineral.
 Motor.
 Neatsfoot.
 Penetrating.
 Range.
 Resin.
 Rosin.
 Sperm.
 Spindle.
 Spray.
 Tall.
 Tanner's.
 Turbine.
 Pentadecanol.
 n-Pentane.
 1-Pentene.
 Petrolatum.
 Petroleum naphtha.
 Polybutene.
 Polypropylene glycol methyl ether.
 Propylene.
 Propylene butylene polymer.
 Propylene tetramer.
 Propane.
 Propionaldehyde.
 n-Propyl acetate.
 n-Propyl alcohol.
 Propylene glycol.
 Sorbitol.
 Tallow.
 Tetra decanol.
 1-Tetradecene.
 Tetrahydronaphthalene.
 Toluene.
 Tridecanol.
 1-Tridecene.
 Triethyl benzene.
 Triethylene glycol.
 Turpentine.
 Undecanol.
 1-Undecene.
 Valeraldehyde.
 Vinyl toluene.
 Waxes:
 Carnauba.
 Paraffin.
 m-Xylene.
 o-Xylene.
 p-Xylene.

§ 30.25-5 Commodities regulated by Subchapter O of this chapter.

The commodities listed in Table 30.25-5 shall be regulated by the provisions of Subchapter O of this chapter.

TABLE 30.25-5

Commodities regulated by Subchapter O of this chapter.

Acetaldehyde.
 Acetic acid.
 Acetic anhydride.
 Acetone cyanohydrin.
 Acetonitrile.
 Acrylonitrile.
 Adiponitrile.
 Allyl alcohol.
 Allyl chloride.
 Aminoethylethanolamine.
 Ammonia, anhydrous.
 Ammonium hydroxide (not to exceed 28 percent NH_3).
 Aniline.
 Benzene.
 Butadiene, inhibited.
 Butyl acrylate (n-).
 Butyl acrylate (iso).
 Butyraldehyde (n-).
 Butyraldehyde (iso).
 Camphor oil.
 Carbolic oil.
 Carbon bisulfide.
 Carbon tetrachloride.
 Caustic potash solution.
 Caustic soda solution.
 Chlorine.
 Chlorobenzene.
 Chloroform.
 Chlorohydrins, crude.
 Chlorosulfonic acid.
 Cresols.
 Crotonaldehyde.
 Dichlorodifluoromethane.
 Dichloropropane.
 Dichloropropene.
 Diethanolamine.
 Diethylenetriamine.
 Diisopropanolamine.
 Dimethylamine.
 Epichlorohydrin.
 Ethyl acrylate.
 Ethyl chloride.
 Ethylene cyanohydrin.
 Ethylenediamine.
 Ethylene dichloride.
 Ethyleneimine.
 Ethylene oxide.
 Ethyl ether.
 2-Ethyl-3-Propylacrolein.
 Formaldehyde solution.
 Formic acid.
 Furfural.
 Hydrochloric acid.
 Hydrofluoric acid.
 Hydrogen chloride.
 Hydrogen fluoride.
 Isoprene.
 Methyl acrylate.
 Methyl bromide.
 Methyl chloride.
 Methyl methacrylate.
 Monochlorodifluoromethane.
 Monoethanolamine.
 Monoisopropanolamine.
 Morpholine.
 Motor fuel antiknock compounds containing tetraethyl lead or tetramethyl lead.
 Oleum.
 Phenol.
 Phosphoric acid.
 Phosphorus.
 Propionic acid.
 Propylene oxide.
 Styrene.
 Sulfur (liquid).
 Sulfuric acid.
 Sulfuric acid, spent.
 Triethanolamine.
 Triethylenetetramine.
 Vinyl acetate.
 Vinyl chloride.
 Vinylidene chloride, inhibited.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b) (1), 30 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b) (1); 49 CFR 1.4(a) (2))

PART 31—INSPECTION AND CERTIFICATION

Subpart 31.01—General

6. Section 31.01-1 is amended by revising paragraphs (a) and (c) to read as follows:

§ 31.01-1 Inspections required—TB/ALL.

(a) Every tank vessel subject to the regulations in this subchapter shall be inspected biennially, or annually, or oftener, if necessary, by the Coast Guard to see that the hull, boilers, machinery, equipment, apparatus for storage, and appliances of the vessel comply with the marine inspection laws, and the regulations in this subchapter, and, when applicable, subchapters E, F, J, O, and Q of this chapter.

(c) For inspection and tests of tanks containing certain dangerous cargoes in bulk, see Part 98 and Subchapter O of this chapter.

Subpart 31.05—Certificates of Inspection

7. Section 31.05-1(a) is revised as follows:

§ 31.05-1 Issuance of certificate of inspection—TB/ALL.

(a) When a tank vessel is found to comply with law and the regulations in this subchapter, and applicable provisions of Subchapters E, F, J, O, and Q of this chapter, a certificate of inspection shall be issued to it, or to its owners, by the Officer in Charge, Marine Inspection.

Subpart 31.15—Manning of Tank Vessels

8. Section 31.15-5 is revised to read as follows:

§ 31.15-5 Tank barges—B/ALL.

(a) Tank barges subject to the provisions of this subchapter need not be manned unless in the judgment of the Officer in Charge, Marine Inspection, such manning is necessary for the protection of life and property and for the safe operation of the vessel. However, towing vessels, while towing barges which are not required to be manned, shall carry in the regular complement of the towing vessel and shall have on board at all times while towing, at least one licensed officer or certificated tankerman.

(b) Where the bulk liquid cargo to be transported is covered by the requirements of § 35.01-55 of this subchapter, the person in charge of the towing vessel or barge shall be provided with, and have on board, the information card required by § 35.01-55(c) of this subchapter.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

PART 32—SPECIAL EQUIPMENT, MACHINERY, AND HULL REQUIREMENTS

Subpart 32.55—Ventilation and Venting

9. Section 32.55-25(a) (1) is revised to read as follows:

§ 32.55-25 Venting of cargo tanks of tank barges constructed on or after July 1, 1951—B/ALL.

(a) *Venting required.* (1) On all tank barges, subject to the provisions of this subchapter the construction or conversion of which is started on or after July 1, 1951, each cargo tank shall be equipped with a vent. The diameter of a vent shall be not less than 2½ inches.

Subpart 32.60—Hull Requirements for Tank Vessels Constructed on or After July 1, 1951

10. Section 32.60-35 is revised to read as follows:

§ 32.60-35 Tank vessels carrying Grade A liquid cargo—TB/ALL.

(a) Grade A liquids having a Reid vapor pressure in excess of 25 pounds per square inch shall be transported in cargo tanks which are independent of the hull.

(b) Barges carrying Grade A liquids having a Reid vapor pressure in excess of 25 pounds per square inch shall be of a Type III barge hull as defined in § 32.63-5(b)(3).

Subpart 32.63—Hull and Cargo Tank Requirements for Tank Barges Constructed or Converted on or After July 1, 1964, and Carrying Certain Dangerous Bulk Cargoes

11. Section 32.63-1 is revised to read as follows:

§ 32.63-1 Application—B/ALL.

(a) The requirements of this subpart shall apply to all tank barges, the construction or conversion of which is started on or after July 1, 1964, and carrying those cargoes listed in Table 30.25-1 which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (Part 32).

(2) Liquefied flammable gases (Part 38 of this subchapter).

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

PART 35—OPERATIONS

Subpart 35.01—Special Operating Requirements

12. Section 35.01-45(a) is revised to read as follows:

§ 35.01-45 Open hopper type barges—B/ALL.

(a) With the exception of those open hopper type barges constructed or modified in conformance with the require-

ments of Subpart 32.63 of this subchapter, the special operating conditions in this section apply to all other open hopper type barges carrying those cargoes listed in Table 30.25-1, of this chapter, which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (Part 32 of this subchapter).

(2) Liquefied flammable gases (Part 38 of this subchapter).

13. Section 35.01-50(a) is revised to read as follows:

§ 35.01-50 Special operating requirements for tank barges carrying certain dangerous bulk cargoes—B/ALL.

(a) The requirements of this section shall apply to all tank barges carrying those cargoes listed on Table 30.25-1, of this chapter, which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (Part 32 of this subchapter).

(2) Liquefied flammable gases (Part 38 of this subchapter).

§ 35.01-55 [Revoked]

14. Subpart 35.01 is amended by revoking § 35.01-55.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

PART 38—LIQUEFIED FLAMMABLE GASES

Subpart 38.05—Design and Installation

15. Section 38.05-1(f) is revised to read as follows:

§ 38.05-1 Design and construction of vessels—general—TB/ALL.

(f) Barges utilized for the carriage of liquefied gases shall be of Type II barge hull as defined in § 32.63-5(b)(2) of this subchapter. The Commandant may, based on the properties of the liquefied gas to be carried, require a Type I barge hull, as defined in § 32.63-5(b)(1) of this subchapter, to ensure the hull is consistent with the degree and nature of the hazard of the liquefied gas to be carried.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

PART 39—FLAMMABLE OR COMBUSTIBLE LIQUIDS HAVING LETHAL CHARACTERISTICS

Subpart 39.01—General

16. Section 39.01-1(a) is revised to read as follows:

§ 39.01-1 Scope of regulations—TB/ALL.

(a) The regulations in this part contain requirements for the transportation

of flammable or combustible liquids having lethal characteristics and defined as Class "B" or "C" poisons in §§ 146.25-10 and 146.25-15 of this chapter. The regulations covering the transportation in portable tanks of flammable or combustible liquids having lethal characteristics and defined as Class "B" or "C" poisons are contained in Part 146 of this chapter. The regulations covering the transportation in unmanned tank barges of the liquids listed in Table 30.25-5, of this subchapter, are contained in Subchapter O of this chapter.

Subpart 39.20—Venting and Ventilation

17. Section 39.20-1 is amended by revising the heading and adding paragraph (d) to read as follows:

§ 39.20-1 Venting—TB/ALL.

(d) Manned barges shall meet the requirements of this section.

§ 39.20-2 [Revoked]

18. Subpart 39.20 is amended by revoking § 39.20-2.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b) (1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b) (1); 49 CFR 1.4(a) (2))

PART 40—SPECIAL CONSTRUCTION, ARRANGEMENT, AND OTHER PROVISIONS FOR CARRYING CERTAIN FLAMMABLE OR COMBUSTIBLE DANGEROUS CARGOES IN BULK

Subpart 40.01—Application

19. Section 40.01-1 is revised to read as follows:

§ 40.01-1 General—T/ALL.

The provisions of this part shall apply to all tank vessels and manned barges which carry in bulk any of the dangerous cargoes specifically noted in this part. The provisions of Subchapter O of this chapter shall apply to any unmanned tank barge which carries in bulk any of the cargoes listed in Table 30.25-5 of this subchapter.

Subpart 40.05—Ethylene Oxide

20. Section 40.05-20(a) is revised to read as follows:

§ 40.05-20 Installation of cargo tanks—TB/ALL.

(a) Cargo tanks shall be located below deck in holds or enclosed spaces with the domes or trunks extended above the weather deck and terminating in the open. Provisions shall be made to main-

tain the watertightness of the deck by means of watertight seals around such domes or trunks. The holds or enclosed spaces, in which the ethylene oxide tanks are located, shall not be used for any other purpose. The weathertightness of the weatherdeck may not be required to be fully maintained on tankships operating on sufficiently protected waters.

Subpart 40.10—Propylene Oxide

21. Section 40.10-1 is amended by revising the heading and paragraph (b) to read as follows:

§ 40.10-1 General—T/ALL.

(b) Propylene oxide may be carried in tankships in accordance with the provisions of this subpart.

22. Section 40.10-20 is amended by revising the heading and paragraph (a) to read as follows:

§ 40.10-20 Installation of cargo tanks—T/ALL.

(a) Cargo tanks shall be located below deck in holds or enclosed spaces with the domes or trunks extended above the

weather deck and terminating in the open. Provisions shall be made to maintain the watertightness of the deck by means of watertight seals around such domes or trunks. The holds or enclosed spaces, in which the propylene oxide tanks are located, shall not be used for any other purpose. The weathertightness of the weather deck may not be required to be fully maintained on tankships operating on sufficiently protected waters.

(R.S. 4405, as amended, 4462, as amended, 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b) (1); 49 CFR 1.4(a) (2))

SUBCHAPTER H—PASSENGER VESSELS

PART 70—GENERAL PROVISIONS

Subpart 70.05—Application

§ 70.05-1 [Amended]

23. In § 70.05-1(a), Table 70.05-1(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 70.05-1(a)

Method of propulsion	Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹		
	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ²	Vessels subject to the provisions of Subchapter O—Certain Bulk Dangerous Cargoes ¹⁰	
Column 1	Column 5	Column 8	
Steam.....	***	***	None.
Motor.....	***	***	None.
Sail.....	***	***	None.
Nonself-propelled.	***	***	None.
	Those vessels carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.
	All seagoing barges except those covered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.

¹¹ For manned tank barges see § 151.01-10(e) of this chapter.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b) (1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b) (1); 49 CFR 1.4(a) (2))

SUBCHAPTER I—CARGO AND MISCELLANEOUS VESSELS

PART 90—GENERAL PROVISIONS

Subpart 90.05—Application

§ 90.05-1 [Amended]

24. In § 90.05-1(a), Table 90.05-1(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 90.05-1(a)

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹				
Method of propulsion	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ²		Vessels subject to the provisions of Subchapter O—Certain Bulk Dangerous Cargoes ¹⁰	
Column 1	Column 5		Column 8	
Steam.....	***	***	None.	
Motor.....	***	***	None.	
Sail.....	***	***	None.	
Nonsself-propelled.	***	***	None.	
	***	Those vessels carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.
	***	All seagoing barges except those covered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.
¹¹ For manned tank barges see § 151.01-10(e) of this chapter.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b) (1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b) (1); 49 CFR 1.4(a) (2))

PART 98—SPECIAL CONSTRUCTION, ARRANGEMENT, AND PROVISIONS FOR CERTAIN DANGEROUS CARGOES IN BULK

Subpart 98.01—Application

25. Section 98.01-1 is amended by revising paragraph (a) and adding paragraphs (c), (d), and (e) to read as follows:

§ 98.01-1 General.

(a) The provisions of this part shall apply to all self-propelled cargo vessels which carry in bulk any of the dangerous cargoes specifically noted in this part.

(c) The regulations for barges carrying any of the bulk chemical cargoes listed in Subparts 98.01 through 98.25 are found in Subchapter O of this chapter.

(d) The word "vessel" as used in Subparts 98.01 through 98.25 refers to a self-propelled cargo vessel.

(e) Manned barges carrying any of the cargoes listed in Table 151.01-10(b) of this chapter will be considered individually by the Commandant and may be required to meet the applicable requirements of Subchapter O of this chapter, as well as the requirements of this subchapter.

Subpart 98.03—Barges Carrying Dangerous Cargoes

26. Part 98 is amended by revoking Subpart 98.03.

Subpart 98.05—Elemental Phosphorus in Water in Bulk

27. Section 98.05-1 is revised to read as follows:

§ 98.05-1 General.

(a) Elemental phosphorus, white or yellow, in water may be carried in bulk in self-propelled cargo vessels in accordance with the provisions of this subpart.

(b) Any self-propelled vessel carrying elemental phosphorus in water in bulk shall be inspected and certificated in accordance with the provisions of this subchapter or Subchapter D of this chapter, as applicable.

§ 98.05-50 [Amended]

28. Section 98.05-50 is amended by revoking paragraphs (h) and (i) and redesignating paragraph (j) as paragraph (h).

Subpart 98.10—Sulfuric Acid in Bulk

29. Section 98.10-1 is revised to read as follows:

§ 98.10-1 General.

(a) Sulfuric acid or spent sulfuric acid may be carried in bulk in self-propelled cargo vessels in accordance with the provisions of this subpart.

(b) Any self-propelled vessel carrying sulfuric acid or spent sulfuric acid in bulk shall be inspected and certificated in accordance with the applicable provisions of this subchapter or Subchapter D of this chapter.

30. Section 98.10-15(c) is revised to read as follows:

§ 98.10-15 Pressure-vessel type cargo tanks.

(c) Tanks designed, inspected, and tested as required by Department of Transportation Specification 103A, 103A-W, 103B, or 103B-W will be accepted as pressure-vessel type cargo tanks, provided the maximum pressure to which the tanks may be subjected does not exceed 30 pounds per square inch: *And provided*, That prior to installing such tanks on a self-propelled cargo vessel, the owner shall furnish the Commandant with a copy of the inspection report certifying that the tanks and appurtenances comply with Department of Transportation specifications.

Subpart 98.15—Hydrochloric Acid in Bulk

31. Section 98.15-1 is revised to read as follows:

§ 98.15-1 General.

(a) Hydrochloric acid may be carried in bulk in self-propelled cargo vessels in accordance with the provisions of this subpart.

(b) Any self-propelled vessel carrying hydrochloric acid in bulk shall be inspected and certificated in accordance with the applicable provisions of this subchapter or Subchapter D of this chapter.

32. Section 98.15-15(c) is revised to read as follows:

§ 98.15-15 Pressure-vessel type cargo tanks.

(c) Tanks designed, inspected, and tested as required by Department of Transportation Specification 103B or 103B-W will be accepted as pressure-vessel type cargo tanks. However, the maximum pressure to which the tanks may be subject shall not exceed 30 pounds per square inch. Prior to installing such tanks on a self-propelled cargo vessel, the owner shall furnish the Commandant with a copy of the inspection report certifying that the tanks and appurtenances comply with Department of Transportation specifications.

Subpart 98.18—Phosphoric Acid in Bulk

33. Section 98.18-1 is amended by revising paragraphs (b) and (c) to read as follows:

§ 98.18-1 General.

(b) Phosphoric acid may be carried in bulk in self-propelled cargo vessels in accordance with the provisions of this subpart.

(c) Any self-propelled cargo vessel carrying phosphoric acid in bulk shall be inspected and certificated in accordance with the applicable provisions of this subchapter or Subchapter D of this chapter.

Subpart 98.20—Liquid Chlorine in Bulk

34. Part 98 is amended by revoking Subpart 98.20.

Subpart 98.25—Anhydrous Ammonia in Bulk

35. Section 98.25-1 is revised to read as follows:

§ 98.25-1 General.

(a) Anhydrous ammonia may be carried in bulk in self-propelled cargo vessels in accordance with the provisions of this subpart.

(b) Any self-propelled cargo vessel carrying anhydrous ammonia in bulk shall be inspected and certificated in accordance with the applicable provisions of this subchapter or Subchapter D of this chapter.

§ 98.25-20 [Amended]

36. Section 98.25-20 is amended by deleting the words "barge or" from the first sentences of paragraphs (a) and (b).

§ 98.25-25 [Revoked]

37. Subpart 98.25 is amended by revoking § 98.25-25.

§ 98.25-40 [Amended]

38. Section 98.25-40(b) is amended by deleting the third sentence.

§ 98.25-50 [Amended]

39. Section 98.25-50 is amended by revoking paragraphs (e), (e)(1), and (e)(2).

40. Section 98.25-70 is amended by revoking paragraph (b), redesignating paragraphs (c), (d), (e), (f), and (g) respectively as paragraphs (b), (c), (d), (e), and (f) and revising the newly designated paragraphs (b) and (c) to read as follows:

§ 98.25-70 Venting.

(b) The capacity of branch vents or vent headers shall depend upon the number of cargo tanks connected to such branch or header as provided in Table 98.25-70(b).

TABLE 98.25-70(b)—CAPACITY OF BRANCH VENTS OR VENT HOLDERS

Number of cargo tanks:	Percent of total valve discharge
1 or 2	100
3	90
4	80
5	70
6 or more	60

(c) In addition to the requirement specified in paragraph (b) of this section, the size of the branch vents or vent headers shall be such that the back pressure in relief valve discharge lines shall not be more than 10 percent of the safety relief valve setting.

§ 98.25-85 [Amended]

41. Section 98.25-85 is amended by deleting the words "barge or" in the second sentence.

42. Section 98.25-90 is revised to read as follows:

§ 98.25-90 Special operating requirements.

(a) Repairs involving welding or burning shall not be undertaken on the cargo tanks or piping while anhydrous ammonia in either the liquid or vapor state is present in the system.

(b) During the time anhydrous ammonia is laden in the tanks the vessel shall be under constant surveillance.

(c) Authorization from the Commandant (MHM) shall be obtained to transport lading other than anhydrous ammonia in the cargo tanks.

(d) Sufficient hose stations shall be installed with adequate water supply so that if leakage of anhydrous ammonia occurs the vapors may be removed by use of a stream of water.

(e) (1) At least two units of approved self-contained breathing apparatus, one stowed forward of the cargo tanks and one stowed aft of the cargo tanks, shall be carried on board the vessel at all times.

(2) All approved self-contained breathing apparatus, masks and respiratory protective devices shall be of types suitable for starting and operating at the temperatures encountered, and shall be maintained in good operating condition.

(3) Personnel involved in the filling or discharge operations shall be adequately trained in the use of the equipment.

(4) For all self-propelled cargo vessels, during filling or discharge operations every person on the vessel shall carry on his person or have close at hand at all times a canister mask approved for ammonia; or each person shall carry on his person a respiratory protective device which will protect the wearer against ammonia vapors and provide respiratory protection for emergency escape from a contaminated area which would result from cargo leakage. This respiratory protective equipment shall be of such size and weight that the person wearing it will not be restricted in movement or in the wearing of lifesaving device.

(f) While fast to a dock, a vessel during transfer of bulk cargo shall display a red flag by day or a red light by night, which signal shall be so placed that it will be visible on all sides. When at anchor, a vessel during transfer of bulk cargo shall display a red flag by day, which signal shall be so placed that it will be visible on all sides.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

SUBCHAPTER J—ELECTRICAL ENGINEERING

PART 110—GENERAL PROVISIONS

Subpart 110.05—Application

§ 110.05-1 [Amended]

43. In § 110.05-1(a), Table 110.05-1(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 110.05-1(a)

Method of propulsion	Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹		
	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ^{2,4}	Vessels subject to the provisions of Subchapter O—Certain Bulk Dangerous Cargoes ¹⁰	
Column 1	Column 5	Column 8	
Steam	***	***	None.
Motor	***	***	None.
Sail	***	***	None.
Nonself-propelled.	***	***	None.
	Those vessels carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.
	All seagoing barges except those covered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.

² For manned tank barges see § 151.01-10(e) of this chapter.

(R.S. 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

SUBCHAPTER N—DANGEROUS CARGOES

PART 146—TRANSPORTATION OR STORAGE OF EXPLOSIVES OR OTHER DANGEROUS ARTICLES OR SUBSTANCES, AND COMBUSTIBLE LIQUIDS ON BOARD VESSELS

Subpart 146.02—General Regulations

44. Section 146.02-2 is amended by revising paragraph (i) and by adding paragraph (j) to read as follows:

§ 146.02-2 Application to vessels.

(i) In addition to complying with the requirements of this part, foreign vessels of novel design or construction or whose operation involves potentially unusual risks shall be subject to inspection to the extent necessary to safeguard life and property in U.S. ports. For details concerning inspection, see §§ 2.01-13, 30.01-5, 70.05-3, 90.05-1, and 151.01-10 of this chapter.

(j) Unmanned tank barges carrying in bulk any of the cargoes enumerated in Table 151.01-10(b) of this chapter shall be subject to the provisions of Subchapter O of this chapter. The regulations of this part shall not apply to any barge subject to the provisions of Subchapter O of this chapter and carrying any cargo listed in Table 151.01-10(b) of this chapter, except such vessel shall be subject to the provisions of R.S. 4472, as amended (46 U.S.C. 170), with respect to explosives prohibited to be transported, stored, or stowed on board any vessel.

Subpart 146.10—Barges

45. Section 146.10-50 is amended by making the following changes in the table:

a. The introductory text is revised to read as follows:

§ 146.10-50 Stowage of explosives or other dangerous articles or substances on board barges.

There is indicated in this table the explosives or other dangerous articles or substances, separated according to their classification, that are permitted or re-

stricted in their transportation and stowage on board the various class barges. Unless otherwise stated in the table, a permitted stowage applies to substances when in containers only.

b. For the substance "Corrosive liquids" delete in columns AA, AB, AC, BA and BB the words, "also bulk in tanks" and add the numeral "9" (as a footnote indicator) after the word, "Yes".

c. For the substance "Corrosive liquids" delete in columns AD and BC the words, "except bulk in tanks" and add the numeral "9" (as a footnote indicator) after the word "No".

d. To the footnotes add footnote 9 to read as follows:

* Transportation of certain hazardous cargoes in bulk is governed by the rules and regulations contained in Subchapter O of this chapter.

Subpart 146.21—Detailed Regulations Governing Inflammable Liquids

46. Subpart 146.21 is amended by adding § 146.21-80 to read as follows:

§ 146.21-80 Certain inflammable liquids in bulk.

Vessels transporting in bulk inflammable liquids shall comply with the applicable provisions of Subchapters D or O of this chapter.

Subpart 146.22—Detailed Regulations Governing Inflammable Solids and Oxidizing Materials

47. Section 146.22-35 is revised to read as follows:

§ 146.22-35 Elemental phosphorus in water in bulk.

(a) Elemental phosphorus, white or yellow, in water may be carried in bulk only in inspected and certificated cargo barges, tank barges, or cargo vessels. For applicable requirements, see Subchapters I and O of this Chapter.

§ 146.22-100 [Amended]

48. In § 146.22-100, Table E is amended by deleting for the article, "phosphorus, white or yellow in water" the note in column 1 reading, "Note: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this chapter".

Subpart 146.23—Detailed Regulations Governing Corrosive Liquids

49. Section 146.23-35 is revised to read as follows:

§ 146.23-35 Certain corrosive liquids in bulk.

(a) Vessels transporting corrosive liquids in bulk shall comply with applicable provisions of Subchapters D, I, or O of this chapter.

§ 146.23-50 [Revoked]

50. Subpart 146.23 is amended by revoking § 146.23-50.

§ 146.23-100 [Amended]

51. In § 146.23-100, Table F is amended by making the following changes:

a. For the article, "Hydrochloric (Muriatic) Acid" delete the note in column 1 reading:

NOTE: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this subchapter.

b. For the article, "Sulfuric Acid (oil of vitriol)" delete the note in column 1 reading:

NOTE: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this chapter.

Subpart 146.24—Detailed Regulations Governing Compressed Gases

52. Section 146.24-80 is revised to read as follows:

§ 146.24-80 Compressed gases in bulk.

(a) Vessels transporting compressed gases in bulk shall comply with the applicable provisions of Subchapters D, I, or O of this chapter.

§ 146.24-85 [Revoked]

53. Subpart 146.24 is amended by revoking § 146.24-85.

§ 146.24-100 [Amended]

54. In § 146.24-100 Table G is amended by making the following changes:

a. For the article, "Ammonia, anhydrous", delete the note in column 1 reading:

NOTE: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this chapter.

b. For the article, "Chlorine", delete the note in column 1 reading:

NOTE: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this chapter.

Subpart 146.25—Detailed Regulations Governing Poisonous Articles

55. Subpart 146.25 is amended by adding § 146.25-70 to read as follows:

§ 146.25-70 Poisonous articles in bulk.

(a) Vessels transporting certain poisons in bulk shall comply with the appli-

cable provisions of Subchapters D or O of this chapter.

Subpart 146.26—Detailed Regulations Governing Combustible Liquids

56. Section 146.26-5 is amended by adding paragraph (d) to read as follows:

§ 146.26-5 Application to vessels.

(d) Vessels transporting combustible liquids in bulk shall comply with applicable provisions of Subchapters D or O of this chapter.

Subpart 146.27—Detailed Regulations Governing Hazardous Articles

57. Section 146.27-50 is revised to read as follows:

§ 146.27-50 Certain hazardous articles in bulk.

(a) Vessels transporting certain hazardous substances in bulk shall comply with the applicable provisions of Subchapters D, I, or O of this chapter.

§ 146.27-100 [Amended]

58. In § 146.27-100, Table K is amended by deleting for the article, "Phosphoric Acid", the note in column 1 reading:

NOTE: For bulk shipments, see Subchapter I (Cargo and Miscellaneous Vessels) of this chapter.

(R.S. 4405, as amended, 4462, as amended, 4472, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 170, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

SUBCHAPTER T—SMALL PASSENGER VESSELS (UNDER 100 GROSS TONS)

PART 175—GENERAL PROVISIONS

Subpart 175.05—Application

§ 175.05-1 [Amended]

59. In § 175.05-1, Table 175.05-1(a) is amended by adding an eighth column, by adding two footnotes at the end of the table (footnotes 10 and 11), and by revising the entries in the fifth column for "non-self-propelled" vessels to read as follows:

TABLE 175.05-1(a)

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹			
Method of propulsion	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ²		Vessels subject to the provisions of Subchapter O—Certain Bulk Dangerous Cargoes ¹⁰
Column 1	Column 5		Column 8.
Steam.....	***	***	None.
Motor.....	***	***	None.
Sail.....	***	***	None.
Nonself-propelled:	***	***	None.
	***	***	None.
	Those vessels carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.
	All seagoing barges except those covered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 146.	***	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹⁰ Bulk dangerous cargoes are cargoes specified in Tables 30.25-5 and 151.01-10(b) of this chapter.

¹¹ For manned tank barges see § 151.01-10(c) of this chapter.

(R.S. 4405, as amended, 4462, as amended, sec. 3, 70 Stat. 152, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 375, 416, 390b, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2))

60. Chapter I is amended by adding Subchapter O and Part 151 to read as follows:

SUBCHAPTER O—CERTAIN BULK DANGEROUS CARGOES

PART 151—UNMANNED BARGES

- Subpart 151.01—General**
- Sec.
151.01-1 Purpose of regulations.
151.01-3 Assignment of functions.
151.01-5 Authority for regulations.
151.01-10 Application of vessel inspection regulations.
151.01-15 Dangerous cargoes not specifically named.
151.01-20 Use of minimum requirements.
151.01-25 Existing barges.
151.01-30 Effective date.

- Subpart 151.02—Equivalents**
- 151.02-1 Conditions under which equivalents may be used.
151.02-5 Design of unmanned barges.

- Subpart 151.03—Definitions**
- 151.03-1 Definitions of terms.
151.03-3 Angle of downflooding.
151.03-5 Approved.
151.03-7 Barge.
151.03-9 Cargo.
151.03-11 Coastwise.
151.03-13 Cofferdam.
151.03-15 Commandant.
151.03-17 Compatible.
151.03-19 Environment.
151.03-21 Filling density.
151.03-23 Flame arrestor.
151.03-25 Flame screen.
151.03-27 Gas free.
151.03-29 Great Lakes.
151.03-31 Headquarters.
151.03-33 Lakes, bays, and sounds.
151.03-35 Limiting draft.
151.03-37 Maximum allowable working pressure.
151.03-39 Ocean.
151.03-41 Officer in Charge, Marine Inspection.
151.03-43 Pressure.
151.03-45 Rivers.
151.03-47 Service.
151.03-49 Sounding tube.
151.03-51 Tank barge.
151.03-53 Tankerman.
151.03-55 Vessel.

- Subpart 151.04—Inspection and Certification**
- 151.04-1 Certificate of Inspection.
151.04-2 Inspection required.
151.04-3 Initial inspection.
151.04-5 Inspection for certification.

- Subpart 151.05—Summary of Minimum Requirements for Specific Cargoes**
- 151.05-1 Explanation of column headings in Table 151.05.

- Subpart 151.10—Barge Hull Construction Requirements**
- 151.10-1 Barge hull classifications.
151.10-5 Intact stability.
151.10-10 Subdivision and damage stability.
151.10-15 Stability and subdivision calculations.
151.10-20 Hull construction.

- Subpart 151.13—Cargo Segregation**
- 151.13-1 General.
151.13-5 Cargo segregation—tanks.
151.13-10 Cargo segregation—piping.

Subpart 151.15—Tanks

- 151.15-1 Tank types.
151.15-3 Construction.
151.15-5 Venting.
151.15-6 Venting piping.
151.15-10 Cargo gaging devices.

Subpart 151.20—Cargo Transfer

- 151.20-1 Piping—general.
151.20-5 Cargo system valving requirements.
151.20-10 Cargo system instrumentation.
151.20-15 Cargo hose if carried on the barge.
151.20-20 Cargo transfer methods.

Subpart 151.25—Environmental Control

- 151.25-1 Cargo tank.
151.25-2 Cargo handling space.

Subpart 151.30—Portable Fire Extinguishers

- 151.30-1 Type.

Subpart 151.40—Temperature or Pressure Control Installations

- 151.40-1 Definitions.
151.40-2 Materials.
151.40-5 Construction.
151.40-10 Operational requirements.
151.40-11 Refrigeration systems.

Subpart 151.45—Operations

- 151.45-1 General.
151.45-2 Special operating requirements.
151.45-3 Manning.
151.45-4 Cargo handling.
151.45-5 Open hopper barges.
151.45-6 Maximum amount of cargo.
151.45-7 Shipping papers.
151.45-8 Illness, alcohol, drugs.
151.45-9 Signals.

Subpart 151.50—Special Requirements for Certain Cargoes

- 151.50-1 General.
151.50-5 Cargoes having toxic properties.
151.50-6 Motor fuel antiknock compounds.
151.50-10 Alkylene oxides.
151.50-12 Ethylene oxide.
151.50-13 Propylene oxide.
151.50-20 Inorganic acids.
151.50-21 Sulfuric acid.
151.50-22 Hydrochloric acid.
151.50-23 Phosphoric acid.
151.50-24 Hydrofluoric acid.
151.50-30 Compressed gases.
151.50-31 Chlorine.
151.50-32 Anhydrous ammonia.
151.50-33 Anhydrous hydrogen chloride.
151.50-34 Vinyl chloride.
151.50-40 Additional requirements for carbon bisulfide and ethyl ether.
151.50-41 Carbon bisulfide.
151.50-42 Ethyl ether.
151.50-50 Elemental phosphorus in water.
151.50-55 Liquid sulfur.
151.50-60 Ethylenimine.
151.50-65 Hydrogen fluoride.

Subpart 151.55—Special Requirements for Materials of Construction

- 151.55-1 General.

AUTHORITY: The provisions of this Part 151 issued under R.S. 4472, as amended, 4417a, as amended, 4405, as amended, 4462, as amended, sec. 6(b)(1), 80 Stat. 937; 46 U.S.C. 170, 391a, 375, 416, 49 U.S.C. 1655(b)(1); 49 CFR 1.4(a)(2).

Subpart 151.01—General

§ 151.01-1 Purpose of regulations.

(a) The purpose of the regulations in this part is to set forth uniform minimum requirements for unmanned tank barges, whether being navigated or not, used for the transportation of those

liquids or liquefied gases in bulk which have dangerous characteristics within the definitions listed in § 146.03-8 of this chapter, or which have flammability or combustibility characteristics within the scope of Title 46, United States Code, section 391(a), and within the definitions in §§ 30.10-15, 30.10-22, and 30.10-39 of this chapter.

(b) A dangerous cargo within the meaning of the regulations in this subchapter is any cargo meeting any one of the following classifications:

Explosives.	Oxidizing materials.
Flammable liquids.	Corrosive liquids.
Combustible liquids.	Compressed gases.
Liquefied flammable gases.	Poisons.
Flammable solids.	Hazardous articles.

(c) The classifications of dangerous cargoes are defined in other parts of this chapter. The definitions applicable to this subchapter are found in the following sections:

Explosives	146.20-1, 146.20-9, 146.20-11
Flammable liquids	30.10-22
Combustible liquids	30.10-15
Liquefied flammable gases	30.10-39
Flammable solids	146.22-1
Oxidizing material	146.22-1
Corrosive liquids	146.23-1
Compressed gases	146.24-1
Poisons	146.25-1
Hazardous articles	146.27-1

(d) Other subchapters of these regulations referenced in the text of this subchapter are as follows:

- Subchapter D—Parts 30-40, Tank Vessels.
Subchapter E—Parts 42-46, Load Lines.
Subchapter F—Parts 50-63, Marine Engineering.
Subchapter I—Parts 90-98, Cargo and Miscellaneous Vessels.
Subchapter J—Parts 110-113, Electrical Engineering.
Subchapter N—Parts 146-149, Dangerous Cargoes.
Subchapter Q—Parts 160-164, Specifications.

§ 151.01-3 Assignment of functions.

(a) By subsection 6(b)(1) of the Department of Transportation Act (49 U.S.C. 1655(b)(1)) the Coast Guard was transferred to the Department of Transportation and there was transferred to and vested in the Secretary of Transportation all functions, powers, and duties, relating to the Coast Guard, of the Secretary of the Treasury and of other officers and offices of the Department of the Treasury. Effective April 1, 1967, the Secretary of Transportation by a rule designated 49 CFR 1.4(a)(2) authorized the Commandant, U.S. Coast Guard, to exercise the functions, powers, and duties vested in the Secretary by subsection 6(b)(1) relating generally to functions, powers, and duties of the Coast Guard except as specifically restricted to certain designated subjects as described in 49 CFR Part 1.

(b) By Order No. 2, the National Transportation Safety Board, pursuant to the authority set forth in subsection 5(m) of the Department of Transportation Act (49 U.S.C. 1654(m)), with the approval of the Secretary of Transportation, made the following delegation to

"* * * the Commandant of the Coast Guard, all the functions, powers, and duties of the National Transportation Safety Board under subsection 5(b) of such Act regarding matters arising in the administration of functions and responsibilities assigned to the Commandant except: (1) The review to determine cause or probable cause and to report the facts and circumstances after the actions of a Marine Board of Investigation, appointed by the Commandant pursuant to Part 136, Subpart 136.09 of this chapter, have been completed; and, (2) the authority to review decisions of the Commandant on appeals from orders of hearing examiners revoking licenses, certificates, documents or registers under the procedures of R.S. 4450, as amended (46 U.S.C. 239), the Act of July 15, 1954 (46 U.S.C. 239a, b) or under section 4, Great Lakes Pilotage Act (46 U.S.C. 216b)."

§ 151.01-5 Authority for regulations.

(a) The authority to prescribe regulations generally is set forth in 46 U.S.C. 375 and 416, as well as in certain other provisions of that title. Under the provisions of 46 U.S.C. 372, the Commandant, U.S. Coast Guard is required to superintend the administration of the vessel inspection laws and to produce a correct and uniform administration of the inspection laws, rules, and regulations.

(b) The regulations regarding vessels, carrying bulk dangerous cargoes are issued under 46 U.S.C. 170, 391a, 392, 395, 435, and 481. Vessels of 150 gross tons or over which engage in foreign or coastwise voyages by sea or voyages on the Great Lakes are also subject to 46 U.S.C., 85a or 88a, and the regulations issued thereunder in Subchapter E of this chapter.

§ 151.01-10 Application of vessel inspection regulations.

(a) The regulations in this part are requirements which may be in addition to, supplement, or modify requirements in other subchapters in this chapter. When a specific requirement in another part or section in another subchapter in this chapter is in conflict with or contrary to requirement or intent expressed in this part, the regulations in this part shall take precedence.

(b) Every unmanned tank barge which carries or is intended to carry in bulk any liquid or liquefied gas listed in Table 151.01-10(b) and has flammability or combustibility characteristics as indicated by a fire protection requirement in Table 151.05 shall be inspected and certificated under the provisions in Subchapter D (Tank Vessels) of this chapter and the regulations in this part.

TABLE 151.01-10(b)—CARGOES REGULATED BY SUBCHAPTER O

Acetaldehyde.
Acetic acid.
Acetic anhydride.
Acetone cyanohydrin.
Acetonitrile.
Acrylonitrile.
Adiponitrile.
Allyl alcohol.

Allyl chloride.
Aminoethylethanolamine.
Ammonia, Anhydrous.
Ammonium hydroxide (not to exceed 28 percent NH_3).
Aniline.
Benzene.
Butadiene, inhibited.
Butyl acrylate (n-).
Butyl acrylate (iso).
Butyraldehyde (n-).
Butyraldehyde (iso).
Camphor oil.
Carbolic oil.
Carbon bisulfide.
Carbon tetrachloride.
Caustic potash solution.
Caustic soda solution.
Chlorine.
Chlorobenzene.
Chloroform.
Chlorohydrins (crude).
Chlorosulfonic acid.
Cresols.
Crotonaldehyde.
Dichlorodifluoromethane.
Dichloropropane.
Dichloropropene.
Diethanolamine.
Diethylenetriamine.
Diisopropanolamine.
Dimethylamine.
Epichlorohydrin.
Ethyl acrylate.
Ethyl chloride.
Ethylene cyanohydrin.
Ethylenediamine.
Ethylene dichloride.
Ethyleneimine.
Ethylene oxide.
Ethyl ether.
2-Ethyl-3-propylacrolein.
Formaldehyde solution.
Formic acid.
Furfural.
Hydrochloric acid.
Hydrofluoric acid.
Hydrogen chloride.
Hydrogen fluoride.
Isoprene.
Methyl acrylate.
Methyl bromide.
Methyl chloride.
Methyl methacrylate.
Monochlorodifluoromethane.
Monoethanolamine.
Monoisopropanolamine.
Morpholine.
Motor fuel antiknock compounds containing lead alkyls.
Oleum.
Phenol.
Phosphoric acid.
Phosphorus.
Propionic acid.
Propylene oxide.
Styrene.
Sulfur (liquid).
Sulfuric acid.
Sulfuric acid, spent.
Triethanolamine.
Triethylenetetramine.
Vinyl acetate.
Vinyl chloride.
Vinylidene chloride, inhibited.

(c) Every unmanned tank barge prior to the carriage in bulk of any liquid or liquefied gas listed in Table 151.01-10(b) which does not have the flammability or combustibility characteristics as indicated by the fire protection requirement in Table 151.05 shall be inspected and certificated under the applicable provisions of Subchapter D or Subchapter I of this chapter, at the option of the barge owner, in addition to the regulations in this part. However, unless the barge

owner notifies the Officer in Charge, Marine Inspection of his option to have the barge inspected and certificated under Subchapter I at the time he submits the application for inspection (Form CG-3752), the unmanned tank barge shall be inspected and certificated under the provisions of Subchapter D of this chapter and the regulations in this part.

(d) The provisions of Subchapter D of this chapter shall apply to all unmanned tank barges which carry in bulk any of the liquids or liquefied gases listed in Table 151.01-10(d). The provisions of this part shall not apply to such barges unless it is also desired to carry one or more of the liquids or liquefied gases listed in Table 151.01-10(b).

TABLE 151.01-10(d)—CARGOES TO BE REGULATED BY SUBCHAPTER D

If flammable or combustible (see § 151.01-1 (c))

Acetone.
Amyl acetate.
n-Amyl alcohol.
Asphalt.
Asphalt blending stocks:
Roofers flux.
Straight run residue.
Butane.
n-Butyl acetate.
sec-Butyl acetate.
n-Butyl alcohol.
sec-Butyl alcohol.
tert-Butyl alcohol.
Butylene.
Corn syrup.
Cyclohexane.
Cumene.
p-Cymene.
n-Decyl alcohol.
Decaldehyde.
1-Decene.
Dextrose solution.
Diacetone alcohol.
Dicyclopentadiene.
Diethylbenzene.
Diethylene glycol.
Diethylene glycol monoethyl ether.
Diethylene glycol monomethyl ether.
Diisobutyl carbinol.
Diisobutylene.
Diethyl phthalate.
Dipropylene glycol.
Distillates:
Straight run.
Flashed feed stocks.
Dodecanol.
Dodecene.
1-Dodecene.
Ethane.
Ethoxy triglycol.
Ethoxylated dodecanol.
Ethoxylated pentadecanol.
Ethoxylated tetradecanol.
Ethoxylated tridecanol.
Ethyl acetate.
Ethyl alcohol.
Ethyl benzene.
Ethyl butanol.
2-Ethyl hexanol.
Ethyl hexyl tallate.
Ethylene.
Ethylene glycol.
Ethylene glycol monobutyl ether.
Ethylene glycol monoethyl ether.
Ethylene glycol monoethyl ether acetate.
Ethylene glycol monomethyl ether.
Gas oil:
Cracked.
Gasolines:
Automotive (containing not over 4.23 grams lead per gallon).
Aviation (containing not over 4.86 grams lead per gallon).

Casinghead (natural).
 Polymer.
 Straight run.
 Gasoline blending stocks:
 Alkylates.
 Reformates.
 Glycerine.
 Heptane.
 Heptanol.
 1-Heptene.
 Hexane.
 Hexanol.
 1-Hexene.
 Hexylene glycol.
 Isobutyl acetate.
 Isobutyl alcohol.
 Isodecyl alcohol.
 Isodecylaldehyde.
 Isohexane.
 Isooctyl alcohol.
 Isooctylaldehyde.
 Isopentane.
 Isopropyl acetate.
 Isopropyl alcohol.
 Jet fuels:
 JP-1 (kerosene).
 JP-3.
 JP-4.
 JP-5 (kerosene, heavy).
 Kerosene.
 Latex, liquid synthetic.
 Linear alcohols.
 (12-15 carbon).
 Methane.
 Methyl alcohol.
 Methyl amyl acetate.
 Methyl amyl alcohol.
 Methyl ethyl ketone.
 Methyl isobutyl ketone.
 Methyl isobutyl carbinol.
 Mineral spirits.
 Molasses, all.
 Naphtha:
 Coal tar.

Solvent.
 Stoddard solvent.
 VM&P (75 percent Naphtha).
 Naphthalene, molten.
 Nonanol.
 Nonene.
 1-Nonene.
 Nonylphenol.
 Octanol.
 1-Octene.
 Oils:
 Clarified.
 Crude.
 Diesel.
 Edible oils, including:
 Castor.
 Cotton seed.
 Fish.
 Olive.
 Peanut.
 Soya bean.
 Vegetable.
 Fuel oils:
 No. 1 (kerosene).
 No. 1-D.
 No. 2.
 No. 2-D.
 No. 4.
 No. 5.
 No. 6.
 Miscellaneous oils, including:
 Absorption.
 Coat tar.
 Lubricating.
 Mineral seal.
 Mineral.
 Motor.
 Neatsfoot.
 Penetrating.
 Range.
 Resin.
 Rosin.
 Sperm.

Spindle.
 Spray.
 Tall.
 Tanner's.
 Turbine.
 Road.
 Transformer.
 Pentadecanol.
 n-Pentane.
 1-Pentene.
 Petrolatum.
 Petroleum naphtha.
 Polybutene.
 Polypropylene glycol methyl ether.
 Propylene.
 Propylene butylene polymer.
 Propylene tetramer.
 Propane.
 Propionaldehyde.
 n-Propyl acetate.
 n-Propyl alcohol.
 Propylene glycol.
 Sorbitol.
 Tallow.
 Tetradecanol.
 1-Tetradecene.
 Tetrahydronaphthalene.
 Toluene.
 Tridecanol.
 1-Tridecene.
 Triethyl benzene.
 Triethylene glycol.
 Turpentine.
 Undecanol.
 1-Undecene.
 Valeraldehyde.
 Vinyl toluene.
 Waxes:
 Carnauba.
 Paraffin.
 m-Xylene.
 o-Xylene.
 p-Xylene.

TABLE 151.01-10(f)

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations¹

Method of propulsion	Size or other limitations ¹	Vessels inspected and certificated under Subchapter D—Tank Vessels ²	Vessels inspected and certificated under either Subchapter H—Passenger Vessels ^{2, 3, 4, 5} or Subchapter T—Small Passenger Vessels ^{2, 4}	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ^{2, 6}	Vessels subject to provisions of Subchapter C—Uninspected Vessels ^{2, 3, 6, 7, 8}	Vessels subject to provisions of Subchapter U—Oceanographic Vessels ^{2, 3, 6, 7, 9}	Vessels subject to the provisions of Subchapter O—Certain bulk dangerous cargoes. ¹⁰
Column 1	Column 2	Column 3	Column 4	Column 5	Column 6	Column 7	Column 8
Steam.....	Vessels not over 65 feet in length.	All vessels carrying combustible or flammable liquid cargo in bulk.	All vessels carrying more than 6 passengers. ⁷	All tugboats and towboats.	All vessels except those covered by columns 3, 4, 5, and 7.	None.....	None.
	Vessels over 65 feet in length.	All vessels carrying combustible or flammable liquid cargo in bulk. ⁵	1. All vessels carrying more than 12 passengers on an international voyage, except yachts. 2. All vessels of not over 15 gross tons which carry more than 6 passengers. ⁷ 3. All other vessels carrying passengers, ⁷ except: a. Yachts. b. Documented cargo or tank vessels issued a permit to carry not more than 16 persons in addition to the crew. c. Towing and fishing vessels, in other than ocean and coastwise service, may carry persons on the legitimate business of the vessel, in addition to crew, but not to exceed one for each net ton of the vessel.	All vessels except those covered by columns 3 and 4.	None.....	All vessels engaged in oceanographic research.	None.

See footnotes at end of document.

TABLE 151.01-10(f)—Continued

Classes of vessels (including motorboats) examined or inspected under various Coast Guard regulations ¹							
Method of propulsion	Size or other limitations ¹	Vessels inspected and certificated under Subchapter D—Tank Vessels ²	Vessels inspected and certificated under either Subchapter H—Passenger Vessels ^{2,3,4,5} or Subchapter T—Small Passenger Vessels ^{2,4}	Vessels inspected and certificated under Subchapter I—Cargo and Miscellaneous Vessels ^{2,4}	Vessels subject to provisions of Subchapter C—Uninspected Vessels ^{2,3,6,7,8}	Vessels subject to provisions of Subchapter U—Oceanographic Vessels ^{2,3,6,7,9}	Vessels subject to the provisions of Subchapter O—Certain bulk dangerous cargoes, ¹⁰
Column 1	Column 2	Column 3	Column 4	Column 5	Column 6	Column 7	Column 8
Motor.....	Vessels not over 15 gross tons.	All vessels carrying combustible or flammable liquid cargo in bulk.	All vessels carrying more than 6 passengers.	Those vessels carrying dangerous cargoes when required by 46 CFR Part 98 or 146.	All vessels except those covered by columns 3, 4, 5, and 7.	None.....	None.
	Vessels over 15 gross tons except seagoing motor vessels of 300 gross tons and over.	All vessels carrying combustible or flammable liquid cargo in bulk. ³	1. All vessels carrying more than 12 passengers on an international voyage, except yachts. 2. All vessels not over 65 feet in length which carry more than 6 passengers. ⁷ 3. All other vessels of over 65 feet in length carrying passengers for hire except documented cargo or tank vessels issued a permit to carry not more than 16 persons in addition to the crew.	All vessels carrying freight for hire except those covered by columns 3 and 4.	All vessels except those covered by columns 3, 4, 5, and 7.	None.....	None.
	Seagoing motor vessels of 300 gross tons and over.	All vessels carrying combustible or flammable liquid cargo in bulk. ³	1. All vessels carrying more than 12 passengers on an international voyage, except yachts. 2. All other vessels carrying passengers, ⁷ except: a. Yachts. b. Documented cargo or tank vessels issued a permit to carry not more than 16 persons in addition to the crew.	All vessels except those covered by columns 3 and 4, and those engaged in the fishing, oystering, clamming, crabbing, or any other branch of the fishery, kelp, or sponge industry.	All vessels except those covered by columns 3, 4, 5, and 7.	All vessels engaged in oceanographic research.	None.
Sail.....	Vessels not over 700 gross tons.	All vessels carrying combustible or flammable liquid cargo in bulk.	All vessels carrying more than 6 passengers. ⁷	Those vessels carrying dangerous cargoes when required by 46 CFR Part 98 or 146.	None.....	None.....	None.
	Vessels over 700 gross tons.	All vessels carrying combustible or flammable liquid cargo in bulk.	All vessels carrying passengers for hire.	Those vessels carrying dangerous cargoes when required by 46 CFR Part 98 or 146.	None.....	None.....	None.
Non-self-propelled.	Vessels less than 100 gross tons.	All vessels carrying combustible or liquid cargo in bulk.	All vessels carrying more than 6 passengers. ⁷	Those vessels carrying dangerous cargoes when required by 46 CFR Part 98 or 146.	All barges carrying passengers except those covered by column 4.	None.....	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.
	Vessels 100 gross tons or over.	All vessels carrying combustible or flammable liquid cargo in bulk.	All vessels carrying passengers for hire.	All seagoing barges except those covered by columns 3 and 4; and those inland barges carrying dangerous cargoes when required by 46 CFR Part 98 or 146.	All barges carrying passengers except those covered by columns 4 and 7.	All seagoing barges engaged in oceanographic research.	All tank barges ¹¹ carrying certain flammable and combustible liquids and liquefied gases in bulk.

¹ Where length is used in this table it means the length measured from end to end over the deck, excluding sheer. This expression means a straight line measurement of the overall length from the foremost part of the vessel to the aftermost part of the vessel, measured parallel to the centerline.

² Subchapters E (Load Lines), F (Marine Engineering), J (Electrical Engineering), and N (Dangerous Cargoes) of this chapter may also be applicable under certain conditions. The provisions of 46 U.S.C. 170 and Subchapter N (Dangerous Cargoes) of this chapter apply whenever explosives or dangerous articles or substances are on board vessels (including motorboats), except when specifically exempted by law.

³ Public nautical schoolships, other than vessels of the Navy and Coast Guard, shall meet the requirements of Part 167 of Subchapter R (Nautical Schools) of this chapter. Civilian nautical schoolships, as defined by 46 U.S.C. 1331, shall meet the requirements of Subchapter II (Passenger Vessels) and Part 168 of Subchapter R (Nautical Schools) of this chapter.

⁴ Subchapter H (Passenger Vessels) of this chapter covers only those vessels of 100 gross tons or more. Subchapter T (Small Passenger Vessels) of this chapter covers only those vessels of less than 100 gross tons.

⁵ Vessels covered by Subchapter H (Passenger Vessels) or I (Cargo and Miscellaneous Vessels) of this chapter, where the principal purpose or use of the vessel is not for the carriage of liquid cargo, may be granted a permit to carry a limited amount of flammable or combustible liquid cargo in bulk. The portion of the vessel used for the carriage of the flammable or combustible liquid cargo shall meet the require-

ments of Subchapter D (Tank Vessels) in addition to the requirements of Subchapter H (Passenger Vessels) or I (Cargo and Miscellaneous Vessels) of this chapter.

⁶ Any vessel on an international voyage is subject to the requirements of the International Convention for Safety of Life at Sea, 1960.

⁷ The meaning of the term "passenger" is as defined in the Act of May 10, 1956 (Sec. 1, 70 Stat. 151; 46 U.S.C. 390). On oceanographic vessels scientific personnel on board shall not be deemed to be passengers nor seamen, but for calculations of lifesaving equipment, etc., shall be counted as persons.

⁸ Boilers and machinery are subject to examination on vessels over 40 feet in length.

⁹ Under 46 U.S.C. 441 an "oceanographic research vessel" is a vessel " * * * being employed exclusively in instruction in oceanography or limnology, or both, or exclusively in oceanographic research, * * * " Under 46 U.S.C. 443, "an oceanographic research vessel shall not be deemed to be engaged in trade or commerce." If or when an oceanographic vessel engages in trade or commerce, such vessel cannot operate under its certificate of inspection as an oceanographic vessel, but shall be inspected and certificated for the service in which engaged, and the scientific personnel aboard then become persons employed in the business of the vessel.

¹⁰ Bulk dangerous cargoes are cargoes specified in Table 151.01-10(b) of § 30.25-5 of this chapter.

¹¹ For manned tank barges see § 151.01-10(e).

(e) Manned barges which carry or intend to carry in bulk the cargoes specified in Table 151.01-10(b) will be considered individually by the Commandant and may be required to meet the requirements of this subchapter and of Subchapter D (Tank Vessels) or I (Cargo and Miscellaneous Vessels) of this chapter as applicable.

(f) This subchapter shall be applicable to all unmanned barges indicated in column 8 of Table 151.01-10(f).

§ 151.01-15 Dangerous cargoes not specifically named.

(a) Any liquid or liquefied gas, which meets the definitions referred to in § 151.01-1 and is not named in Table 151.01-10(b) or Table 151.01-10(d) shall not be transported in bulk in a manned or unmanned tank barge without the prior specific approval of the Commandant.

(b) Mixtures or blends of two or more cargoes, one or more of which appears in Table 151.01-10(b), will be treated as though they were new products and specific approval of the Commandant must be obtained prior to undertaking their transportation.

(c) Mixtures or blends of two or more cargoes appearing in Table 151.01-10(d) may be treated as though that mixture were included on the list and may be transported under the provisions of Subchapter D (Tank Vessels) of this chapter.

§ 151.01-20 Use of minimum requirements.

(a) The minimum requirements governing transportation of any liquid or liquefied gas listed in Table 151.01-10(b) are set forth in this part when such substances are carried in bulk in unmanned tank barges.

(b) Before any liquid or liquefied gas listed in Table 151.01-10(b) may be carried in an unmanned tank barge, the certificate of inspection issued to such barge shall be appropriately endorsed to show approval to transport such cargo.

§ 151.01-25 Existing Barges.

(a) Except as provided in paragraph (c) of this section, barges certified for, or used within the previous 2 years prior to the effective date of this regulation, or barges equivalent to such barges, for the transportation of any cargo regulated by this subchapter which do not meet the specific requirements herein, may be continued in service subject to the following conditions:

(1) Venting, gaging, and all operating requirements shall be met within a 1-year period subsequent to the effective date.

(2) All other requirements shall be met within a 2-year period subsequent to the effective date.

(b) If an existing barge, which has been designed to carry or has regularly been carrying one or more of the cargoes regulated by this subchapter, is found to be so arranged or outfitted that conversion to bring it into compliance with any or all of the requirements of this subchapter is impractical or impossible, the Commandant, upon application, may

review the plans of the barge to determine if it is suitable and safe for the cargoes to be transported.

(c) Except for operating requirements, barges constructed and certificated for the transportation of any cargo for which specific regulations existed, in Parts 36, 38, 39, 40, and 98 of this chapter at the time of their construction or conversion, may continue and will be certificated to operate without the requirement that they comply with the provisions of Subchapter O of this subchapter.

§ 151.01-30 Effective date.

(a) The regulations in this subchapter are effective on and after June 1, 1970. However, amendments, revisions, or additions shall become effective ninety (90) days after the date of publication in the FEDERAL REGISTER unless the Commandant shall fix a different time.

(b) The regulations in this subchapter are not retroactive in effect unless specifically made so at the time the regulations are issued. Changes in specification requirements of articles of equipment, or materials used in construction of tank barges, shall not apply to such items which have been passed as satisfactory until replacement shall become necessary, unless a specific finding is made that such equipment or materials used is unsafe or hazardous and has to be removed from tank barges.

Subpart 151.02—Equivalents

§ 151.02-1 Conditions under which equivalents may be used.

(a) Where in this part it is provided that a particular fitting, material, appliance, apparatus, or equipment, or type thereof, shall be fitted or carried in a vessel, or that any particular provision shall be made or arrangement including cargo segregation shall be adopted, the Commandant may accept in substitution therefore any other fitting, material, apparatus or equipment, or type thereof, or any other provision or arrangement. However, the Commandant shall be satisfied by suitable evidence that the fitting, material, appliance, apparatus, or equipment, or the type thereof, or the provision or arrangement shall be at least as effective as that specified in this part.

(b) In any case where it is shown to the satisfaction of the Commandant that the use of any particular equipment, apparatus, or arrangement not specifically required by law is unreasonable or impracticable, the Commandant may permit the use of alternate equipment, apparatus, or arrangement to such an extent and upon such conditions as will insure, to his satisfaction, a degree of safety consistent with the minimum standards set forth in this part.

§ 151.02-5 Design of unmanned barges.

(a) In order not to inhibit design and application, the Commandant may approve vessels of novel design, both new and for conversion, after it is shown to his satisfaction that such a vessel is at least as safe as any vessel which meets the standards required by this part.

Subpart 151.03—Definitions

§ 151.03-1 Definitions of terms.

Certain terms used in the regulations in this subchapter are defined in this subpart.

§ 151.03-3 Angle of downflooding.

The angle of heel of the vessel at which any opening in the hull not provided with a water tight closure would be immersed.

§ 151.03-5 Approved.

This term means approved by the Commandant unless otherwise stated.

§ 151.03-7 Barge.

This term means any non-self-propelled vessel designed to carry cargo.

§ 151.03-9 Cargo.

This term means any liquid, gas or solid having one or more of the dangerous properties defined in this subchapter.

§ 151.03-11 Coastwise.

This designation refers to all vessels normally navigating the waters of any ocean or the Gulf of Mexico 20 nautical miles or less offshore.

§ 151.03-13 Cofferdam.

This term means a void or empty space separating two or more compartments for the purpose of isolation or to prevent the contents of one compartment from entering another in the event of the failure of the walls of one to retain their tightness.

§ 151.03-15 Commandant.

This term means Commandant of the U.S. Coast Guard.

§ 151.03-17 Compatible.

Compatible means that a cargo will not react in an unsafe manner with other cargo or materials used in construction of the barge. The prime considerations are the chemical, physical, or thermal properties of the reaction including heat, pressure, toxicity, stability, and explosive nature of the reaction and its end products.

§ 151.03-19 Environment.

This term refers to the atmosphere within a cargo tank and the spaces adjacent to the tank or spaces in which cargo is handled.

§ 151.03-21 Filling density.

The ratio, expressed as a percentage, of the weight of cargo that may be loaded into a tank compared to the weight of water that the tank will hold at 60° F. The weight of a gallon of water at 60° F. in air shall be 8.32828 pounds.

§ 151.03-23 Flame arrestor.

Any device or assembly of cellular, tubular, pressure or other type used for preventing the passage of flames into enclosed spaces.

§ 151.03-25 Flame screen.

A fitted single screen of corrosion-resistant wire of at least 30 by 30 mesh, or two fitted screens, both of corrosion-resistant wire, of at least 20 by 20 mesh

spaced not less than one-half inch or more than 1½ inches apart.

§ 151.03-27 Gas free.

Free from dangerous concentrations of flammable or toxic gases.

§ 151.03-29 Great Lakes.

A designation for all vessels in Great Lakes service.

§ 151.03-31 Headquarters.

The Office of the Commandant, U.S. Coast Guard, Washington, D.C. 20591.

§ 151.03-33 Lakes, bays, and sounds.

A designation for all vessels navigating the waters of any of the lakes, bays, or sounds other than the waters of the Great Lakes.

§ 151.03-35 Limiting draft.

Maximum allowable draft to which a barge may be loaded. Limiting draft is a function of hull type and cargo specific gravity. A barge may be assigned different limiting drafts for different hull types or within one hull type for different specific gravities.

§ 151.03-37 Maximum allowable working pressure.

The maximum allowable working pressure shall be as defined in section 8 of the ASME Boiler and Pressure Vessel Code.

§ 151.03-39 Ocean.

A designation for all vessels normally navigating the waters of any ocean or the Gulf of Mexico more than 20 nautical miles offshore.

§ 151.03-41 Officer in Charge, Marine Inspection.

Any person from the civilian or military branch of the Coast Guard designated as such by the Commandant and who, under the superintendence and direction of the Coast Guard District Commander, is in charge of an inspection zone for the performance of duties with respect to the enforcement and administration of title 52 R.S., acts amendatory thereof or supplemental thereto, and rules and regulations thereunder.

§ 151.03-43 Pressure.

Terminology used in this part are: pounds per square inch gage (p.s.i.g.) or pounds per square inch absolute (p.s.i.a.). 14.7 p.s.i.a. is equal to 0 p.s.i.g. P.s.i.g. is normally used in reference to design or operating requirements.

§ 151.03-45 Rivers.

A designation for all vessels whose navigation is restricted to rivers and/or canals, exclusively.

§ 151.03-47 Service.

The waters upon which a vessel may be operated as endorsed upon the certificate of inspection.

§ 151.03-49 Sounding tube.

This is an unperforated tube fitted to an ullage hole, secured so as to be vapor tight to the underside of the tank top,

open at the bottom, and extending to within 18 inches or less of the bottom of the tank.

§ 151.03-51 Tank barge.

A non-self-propelled vessel especially constructed or converted to carry bulk liquid cargo in tanks.

§ 151.03-53 Tankerman.

A person holding a certificate issued by the Coast Guard attesting to his competency in handling flammable or combustible liquid cargo in bulk or is any person holding a valid license as master, mate, pilot, or engineer.

§ 151.03-55 Vessel.

The word "vessel" as used in this subchapter applies to those classes indicated in column 8 of Table 151.01-10(f).

Subpart 151.04—Inspection and Certification

§ 151.04-1 Certificate of inspection.

(a) A certificate of inspection is required for every unmanned tank barge subject to the requirements in this subchapter. A certificate of inspection shall be issued to the barge or to its owners by the Officer in Charge, Marine Inspection, if the barge is found to comply with applicable inspection laws and the regulations in this chapter.

(b) The certificate of inspection shall be endorsed with respect to the waters over which the barge may be operated.

(c) The certificate shall be endorsed describing the cargoes by name as given in Table 151.01-10(b) or as specifically approved by the Commandant. No other dangerous cargo as defined in 151.01-1 shall be carried. Certificates shall specify maximum cargo weight (short tons), maximum density (pounds per gallon), and any operating limitations and a limiting draft.

§ 151.04-2 Inspection required.

(a) Every unmanned tank barge subject to the regulations in this subchapter shall be inspected biennially. More frequent inspections may be required, if necessary, by the Officer in Charge, Marine Inspection, to see that the hull, equipment and appliances of the vessel comply with the marine inspection laws, and the regulations of this subchapter and other subchapters where applicable.

§ 151.04-3 Initial inspection.

(a) The initial inspection which may consist of a series of inspections during the construction of an unmanned barge shall include a complete inspection of the structure, auxiliary machinery, and equipment. The inspection shall be such as to insure that the arrangement, materials, and scantlings of the hull structure, tanks and pressure vessels and their appurtenances comply with applicable regulations of this chapter and with the requirements of this part.

§ 151.04-5 Inspection for certification.

(a) An inspection for certification is a prerequisite of the reissuance of a Certificate of Inspection as provided for in applicable regulations of this chapter.

(b) Unless otherwise specified by special requirements, cargo tanks shall be internally examined according to the following:

(1) Where the cargo tank is of the gravity type and the structural framing is on the internal tank surface, the tank shall be inspected internally at the time of inspection for certification.

(2) Where the cargo tank is of the gravity type and the structural framing is on the external tank surface accessible for examination from voids, cofferdams, double bottoms, and other similar spaces, tanks shall be inspected internally at 4-year intervals.

(3) Where the cargo tank is of the pressure-vessel type, it shall be examined internally at 8-year intervals.

(4) Internal inspection may be required at more frequent intervals as deemed necessary by the Officer in Charge, Marine Inspection.

(c) Cargo tanks shall be visually inspected externally at the time of the vessel's inspection for certification. In the case of single skin construction, underwater portions of the tanks need not be examined unless deemed necessary by the Officer in Charge, Marine Inspection.

(1) For tanks where external examination of the tank proper is not possible due to insulation, the Officer in Charge, Marine Inspection, may require a sufficient portion of the insulation to be removed to determine the soundness of the tank. As an alternative to removing the insulation for external examination, the Officer in Charge, Marine Inspection, may accept, upon request, an internal examination.

(2) In addition to visual inspection, the Officer in Charge, Marine Inspection, may require the tank to be tested by such nondestructive means as he considers necessary to determine the condition of the tank.

(d) Quick closing valves shall be tested by operating the emergency shutoff system from each operating point at the time of each vessel's inspection for certification.

(e) Excess flow valves shall be inspected at the time of inspection for certification. The Officer in Charge, Marine Inspection, shall satisfy himself that the valve is in working condition by visual inspection, and if this is impossible, by one of the following means:

(1) Removing the valve and bench testing ashore; the valve shall close at or below its rated closing flow.

(2) By any other means acceptable to the Officer in Charge, Marine Inspection, which will demonstrate that the valve is operable.

(f) Pressure vacuum relief valves shall be examined to determine that the operating mechanism is free and capable of activation.

(g) Safety relief valves shall be tested by bench testing or other suitable means. The valves shall relieve and reset within the design tolerances of the set pressure, or it shall be removed and reset prior to being returned to service. This test shall be conducted at the time of the inspection for certification.

(h) Cargo hose stored on board the vessel which is used in transferring cargoes listed in Table 151.01-10(b) shall be inspected every 2 years. This inspection shall consist of a visual examination and a hydrostatic test of $1\frac{1}{2}$ times the maximum pressure to which the hose will be subjected in service. The date of the most recent inspection and the test pressure shall be stenciled or otherwise marked on the hose.

(i) Cargo piping shall be inspected and tested at the same time as the cargo tanks.

Subpart 151.05—Summary of Minimum Requirements for Specific Cargoes

§ 151.05-1 Explanation of column headings in Table 151.05.

(a) *Cargo identification/name.* This column identifies commodities by name as listed in Table 151.01-10(b).

(b) *Cargo identification/pressure.* This column identifies cargo in terms of pressure within the tank. Terms used are:

(1) *Pressurized.* Cargo carried at a pressure in excess of 10 pounds per square inch gage as measured at the top of the tank (i.e., exclusive of static head).

(2) *Atmospheric pressure.* Cargo carried at not more than 10 pounds per square inch gage, exclusive of static head.

(c) *Cargo identification/temperature.* This column identifies the cargo by the temperature of the cargo during transit.

(1) *Ambient temperature.* Cargo which is carried at naturally occurring temperatures.

(2) *Low temperature.* Cargo carried below ambient temperatures when the product temperature is below 0°F.

(3) *Elevated temperature.* Cargo carried above ambient temperatures.

(d) *Hull type.* This column refers to the flotation features of the barge. Terms used are explained and defined in Subpart 151.10 of this part.

(e) *Cargo segregation/tanks.* This column refers to the separation of the cargo from its surroundings. Terms are explained in § 151.13-5 and in footnotes to Table 151.05 of this part.

(n) *Fire protection.* This column specifies whether portable fire extinguishers are required on barges carrying the cargo named. Requirements for cargoes requiring extinguishers are given in Subpart 151.30 of this part.

(o) *Special requirements.* This column refers to requirements which apply to specific cargoes and which cannot be stated in generalized terms. Where applicable, detailed requirements are given in Subparts 151.50 and 151.55 of this part.

(g) *Tanks/type.* This column refers to the design requirements for cargo tanks and their placement within the hull of the vessel. Terms are explained in § 151.15-1.

(h) *Tanks/venting.* This column refers to arrangements for preventing excess pressure or vacuum within the cargo tank. Terms used are explained and defined in § 151.15-5.

(i) *Tanks/gaging devices.* This column refers to arrangements provided for determining the amount of cargo present in cargo tanks. Terms used are explained and defined in § 151.15-10.

(j) *Cargo transfer/piping.* This column refers to the classification of piping in accordance with Subchapter F of this chapter as discussed in § 151.20-1.

(k) *Cargo transfer/control.* This column refers to the valving requirements for the cargo piping system. These requirements are defined in § 151.20-5.

(l) *Environmental control/cargo tanks.* This column refers to control of

the composition of the environment within cargo tanks. Definitions and detailed requirements are given in § 151.25-1.

(m) *Environmental control/cargo handling space.* This column refers to control of the environment in the cargo handling spaces. Definitions and detailed requirements are found in § 151.25-2.

(n) *Fire protection.* This column specifies whether portable fire extinguishers are required on barges carrying the cargo named. Requirements for cargoes requiring extinguishers are given in Subpart 151.30 of this part.

(o) *Special requirements.* This column refers to requirements which apply to specific cargoes and which cannot be stated in generalized terms. Where applicable, detailed requirements are given in Subparts 151.50 and 151.55 of this part.

(p) *Electrical installations/hazard group and class.* This column refers to the hazardous material group and class ratings of § 111.60-40, of this chapter. These group and class ratings are to be used in the selection of electrical equipment for use within the hazardous areas as permitted by Subpart 111.70 of this chapter. All the cargoes listed in Table 151.05 are classified and group ratings are, and will continue to be, indicated when available.

(q) *Temperature control installations.* This column refers to systems which are used to control the temperature of the cargo. Definitions and requirements which applicable if such systems are used are given in Subpart 151.40 of this part.

(r) *Tank inspection period.* This column refers to the maximum period in years between internal cargo tank inspections. Applicable requirements are given in § 151.04-5.

TABLE 151.05—SUMMARY OF MINIMUM REQUIREMENTS

Cargo identification			Hull type	Cargo segregation	Tanks			Cargo transfer		Environmental control		Fire protection required	Special requirements (Section)	Electrical hazard group-class	Temp. control install.	Tank internal inspection period—years
Name	Pressure	Temp.			Type	Vent	Gaging device	Piping class	Control	Cargo tanks	Cargo handling space					
Acetaldehyde	Press.	Amb.	II	INA 2li	Ind. Pressure	SR	Restr.	II	P-1	Inerted	Vent F	Yes	151.55-1(b)	I-C	NA	G
Acetic acid	Atmos.	Amb.	III	II 2li	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(g)	I	NA	G
Acetic anhydride	Atmos.	Amb.	III	II 2li	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	151.55-1(g)	I	NA	G
Acetone cyanohydrin	Atmos.	Amb.	I	III 2li	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I	NA	G
Acetonitrile	Atmos.	Amb.	III	II 2li	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I-D	NA	G
Acrylonitrile	Atmos.	Amb.	II	III 2li	Integral Gravity	PV	Closed	II	G-1	NR	Vent F	Yes	151.55-1(e)	I-D	NA	G
Adiponitrile	Atmos.	Amb.	II	III 2li	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	No	I	NA	G
Allyl alcohol	Atmos.	Amb.	I	III 2li	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I	NA	G
Allyl chloride	Atmos.	Amb.	I	III 2li	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I-D	NA	G
For requirements see these sections:			151.10	151.13-5	151.15-1	151.15-5	151.15-10	151.20-1	151.20-5	151.25-1	151.25-2	151.30		111.60-40 (Subchapter J)	151.40	151.04-5

See footnotes at end of document.

RULES AND REGULATIONS

3721

TABLE 151.05—SUMMARY OF MINIMUM REQUIREMENTS—Continued

Cargo identification			Hull type	Cargo segregation	Tanks			Cargo transfer		Environmental control		Fire protection required	Special requirements (Section)	Electrical hazard group-class	Temp. control install.	Tank internal inspect. period—years
Name	Pressure	Temp.			Tank	Type	Vent	Gaging device	Piping class	Control	Cargo tanks					
Aminoethyl-ethanolamine	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(b)	I	NA	G
Ammonia, anhydrous	Press.	Amb.	II	1NA 2II	Ind. Pressure	SR 250 p.s.i.	Restr.	II	P-2	NR	Vent F	No	151.50-30 151.50-32	I-D	NA	8
Ammonia, anhydrous	Atmos.	Low	II	1NA 2II	Ind. Gravity	PV	Restr.	II-L	G-2	NR	Vent F	No	151.50-30 151.50-32	I-D	151.40-1(b)(1)	8
Ammonium hydroxide, not to exceed 28% NH ₃	Atmos.	Amb.	III	II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	No	No	I-③	NA	G
Aniline	Atmos.	Amb.	I	III 2II	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I-D	NA	G
Benzene	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	No	I-D	NA	G
Butadiene, inhibited	Press.	Amb.	II	1NA 2II	Ind. Pressure	SR	Restr.	II	P-2	NR	Vent F	Yes	No	I-B	NA	8
N-butyl acrylate	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent N	Yes	No	I	NA	G
Isobutyl acrylate	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent N	Yes	No	I	NA	G
Butyraldehyde, (N)	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	151.55-1(h)	I	NA	G
Isobutyraldehyde	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	151.55-1(h)	I	NA	G
Camphor oil (light)	Atmos.	Amb.	II	III 2II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	No	I	NA	G
Carbolic oil	Atmos.	Amb.	I	III 2II	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I	NA	G
Carbon bisulfide	Atmos.	Amb.	II	1NA 2II	Ind. Gravity	PV	Restr.	II	G-1	Inert	Vent F	Yes	151.50-40 151.50-41	151.50-41(g)	NA	G
Carbon tetrachloride	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent N	No	No		NA	G
Caustic potash solution	Atmos.	Amb. Elev.	III	II	Integral Gravity	Open	Open	II	G-1	NR	NR	No	151.55-1(b)		NA	G
Caustic soda solution	Atmos.	Amb. Elev.	III	II	Integral Gravity	Open	Open	II	G-1	NR	NR	No	151.55-1(b)		NA	G
Chlorine	Press.	Amb.	I	1NA 2II	Ind. Pressure	SR 300 p.s.i.	Indirect	I	P-2	NR	Vent F	No	151.50-30 151.50-31		NA	2
Chlorobenzene	Atmos.	Amb.	III	II	Integral Gravity	PV	Open	II	G-1	NR	Vent N	Yes	No	I	NA	G
Chloroform	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent F	No	No		NA	G
Chlorohydrins (crude)	Atmos.	Amb.	I	III 2II	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I	NA	G
Chlorosulfonic acid	Atmos.	Amb.	III	III 2II	Integral Gravity	PV	Open	II	G-1	NR	Vent N	No	151.50-20 151.50-21	I	NA	G
Cresols	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	No	I-D	NA	G
Crotonaldehyde	Atmos.	Amb.	II	III 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	151.55-1(h)	I	NA	G
Dichlorodifluoromethane	Press.	Amb.	III	1NA 2I	Ind. Pressure	SR	Restr.	II	P-1	NR	NR	No	No		NA	8
Dichloropropane	Atmos.	Amb.	III	II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I	NA	G
Dichloropropene	Atmos.	Amb.	II	III 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I-D	NA	G
Diethanolamine	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(c)	I	NA	G
Diethyleneetriamine	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(c)	I	NA	G
Diisopropylamine	Atmos.	Amb.	III	II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(c)	I	NA	G
For requirements see these sections:																
	151.10	151.13-5		151.15-1	151.15-5	151.15-10	151.20-1	151.20-5	151.25-1	151.25-2	151.30		111.60-40 (Subchapter J)		151.40	151.04-5

See footnotes at end of document.

TABLE 151.05—SUMMARY OF MINIMUM REQUIREMENTS—Continued

Cargo Identification			Hull type	Cargo segregation	Tanks			Cargo transfer		Environmental control		Fire protection required	Special requirements (Section)	Electrical hazard group-class	Temp. control install.	Tank internal i spec. period—years
Name	Pressure	Temp.			Tank	Type	Vent	Gaging device	Piping class	Control	Cargo tanks	Cargo handling space				
Dimethylamine	Press.	Amb.	II	1NA 2II	Ind. Pressure	SR	Restr.	II	P-2	NR	Vent F	Yes	151.55-1(e)	I-D	NA	8
Epichlorohydrin	Atmos.	Amb.	I	1II 2II	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I	NA	G
Ethyl acrylate	Atmos.	Amb.	III	1I 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I	NA	G
Ethyl chloride	Press.	Amb.	II	1NA 2II	Ind. Pressure	SR	Restr.	II	P-2	NR	Vent F	Yes	No	I	NA	8
Ethyl Ether	Atmos.	Amb.	II	1NA 2II	Ind. Gravity	PV	Closed	II	G-1	Inert	Vent F	Yes	151.50-40 151.50-42	I-C	NA	G
2-Ethyl, 3-Propyl Acrolein	Atmos.	Amb.	III	1I 2I	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I	NA	G
Ethylene cyanohydrin	Atmos.	Amb.	III	1I 2II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	No	I	NA	G
Ethylene diamine	Atmos.	Amb.	III	1I 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	151.55-1(c)	I	NA	G
Ethylene dichloride	Atmos.	Amb.	III	1II 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I	NA	G
Ethyleneimine	Atmos.	Amb.	I	1NA 2II	Ind. Pressure	SR	Closed	II	G-1	Inert	Vent F	Yes	151.50-60	I	151.40-1 (b) (2)	G
Ethylene oxide	Press.	Amb.	I	1NA 2II	Ind. Pressure	SR	Restr.	II	P-2	Inert	Vent F	Yes	151.50-10 151.50-12	I-B	151.40-1 (c) (2)	4
Formaldehyde solution 37-50%	Atmos.	Amb.	III	1II 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	No	151.55-1(h)	I	NA	G
Formic acid	Atmos.	Amb.	III	1II 2I	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	151.55-1(i)	I	NA	G
Furfural	Atmos.	Amb.	III	1II 2I	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	151.55-1(h)	I	NA	G
Hydrochloric acid	Atmos.	Amb.	III	1NA 2II	Ind. Gravity	Open	Open	II	G-1	NR	Vent F	No	151.50-20 151.50-22		NA	4
Hydrofluoric acid (3)	Atmos.	Amb.	I	1NA 2II	Ind. Gravity	PV	Closed	II	G-1	NR	Vent F	No	151.50-24		NA	G
Hydrogen chloride (3)	Press.	Amb. or Low	I	1NA 2II	Ind. Pressure	SR	Closed	I or I-L	P-2	NR	Vent F	No	151.50-33 151.55-1(e)		151.40-1 (b) (2)	2
Hydrogen fluoride (3)	Press.	Amb.	I	1NA 2II	Ind. Pressure	SR	Closed	I	P-2	NR	Vent F	No	151.50-65		151.40-1 (b) (2)	G
Isoprene	Atmos.	Amb.	III	1I 2II	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	No	I-C	NA	G
Methyl acrylate	Atmos.	Amb.	III	1I 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I	NA	G
Methyl bromide	Press.	Amb.	I	1NA 2II	Ind. Pressure	SR	Closed	I	P-2	NR	Vent F	Yes	151.50-5	I-D	NA	2
Methyl chloride	Press.	Amb.	II	1NA 2II	Ind. Pressure	SR	Restr.	II	P-2	NR	Vent F	Yes	151.55-1(c)	I-D	NA	8
Methyl methacrylate	Atmos.	Amb.	III	1I 2II	Integral Gravity	PV	Restr.	II	G-1	NR	Vent F	Yes	No	I-D	NA	G
Monochlorodifluoromethane	Press.	Amb.	III	1NA 2I	Ind. Pressure	SR	Restr.	I	P-1	NR	NR	No	No	I	NA	8
Monoethanolamine	Atmos.	Amb.	III	1I 2I	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(c)		NA	G
Monoisopropanolamine	Atmos.	Amb.	III	1I 2I	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(c)	I	NA	G
Morpholine	Atmos.	Amb.	III	1I 2II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	155.55-1(c)	I	NA	G
Motorfuel antiknock compounds	Atmos.	Amb.	I	1II 2II	Ind. Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-6	I	NA	151.50-6 4
Oilium	Atmos.	Amb.	III	1II 2II	Integral Gravity	Open	Open	II	G-1	NR	Vent N	No	151.50-20 151.50-21	I	NA	
Phenol	Atmos.	Amb.	I	1II 2I	Integral Gravity	PV	Closed	I	G-1	NR	Vent F	Yes	151.50-5	I-D	NA	2
For requirements see these sections:			151.10	151.13-5	151.15-1	151.15-5	151.15-10	151.20-1	151.20-5	151.25-1	151.25-2	151.30		111.60-40 (Subchapter J)	151.40	151.04-5

See footnotes at end of document.

TABLE 151.05—SUMMARY OF MINIMUM REQUIREMENTS—Continued

Cargo identification			Hull type	Cargo segregation	Tanks			Cargo transfer		Environmental control		Fire protection required	Special requirements (Section)	Electrical hazard group-class	Temp. control install.	Tank internal inspect. period—years
Name	Pressure	Temp.			Tank	Type	Vent	Gaging device	Piping class	Control	Cargo tanks					
Phosphorus, elemental	Atmos.	Elev.	I	1ii 2ii	Integral Gravity	PV	Closed	I	G-1	Water Pad	Vent F	Yes	151.50-50		NA	8-4
Phosphoric acid	Atmos.	Amb.	III	1ii 2i	Integral Gravity	Open	Open	II	G-1	NR	Vent N	No	151.50-20 151.50-23	I	NA	4
Propionic acid	Atmos.	Amb.	III	1i 2ii	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(g)	I	NA	G
Propylene oxide	Press.	Amb.	II	1NA 2ii	Ind. Pressure	SR	Restr.	II	P-1	Inerted	Vent F	Yes	151.50-10 151.50-13	I-B	NA	4
Styrene monomer	Atmos.	Amb.	III	1i 2ii	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	No	I-D	NA	G
Sulfur (liquid)	Atmos.	Elev.	III	1i 2ii	Integral Gravity	Open	Open	II	G-1	Vent N	Vent N	Yes	151.50-55	I-C	151.40-1 (f) (1)	G
Sulfuric acid	Atmos.	Amb.	III	1ii 2ii	Integral Gravity	Open	Open	II	G-1	NR	Vent N	No	151.50-20 151.50-21	I	NA	4
Sulfuric acid spent	Atmos.	Amb.	III	1ii 2ii	Integral Gravity	Open	Open	II	G-1	NR	Vent N	No	151.50-20 151.50-21	I	NA	4
Triethanolamine	Atmos.	Amb.	III	1i 2i	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(b)	I	NA	G
Triethylene tetramine	Atmos.	Amb.	III	1i 2i	Integral Gravity	Open	Open	II	G-1	NR	Vent N	Yes	151.55-1(b)	I	NA	G
Vinyl acetate	Atmos.	Amb.	III	1i 2ii	Integral Gravity	PV	Open	II	G-1	NR	Vent F	Yes	No	I-D	NA	G
Vinyl chloride	Press.	Amb.	II	1NA 2ii	Ind. Pressure	SR	Restr.	II	P-2	NR	Vent F	Yes	151.50-30 151.50-34	I-D	NA	8
Vinyl chloride	Atmos.	Low	II	1NA 2ii	Ind. Gravity	PV	Restr.	II-L	G-2	NR	Vent F	Yes	151.50-30 151.50-34	I-D	151.40-1 (b) (1)	8
Vinylidene chloride inhibited	Atmos.	Amb.	II	1NA 2ii	Ind. Gravity	PV	Closed	II	P-2	Padded	Vent F	Yes	151.55-1(f)	I	NA	G
For requirements see these sections:			151.10	151.13-5	151.15-1	151.15-5	151.15-10	151.20-1	151.20-5	151.25-1	151.25-2	151.30		111.60-40 (Subchapter J)	151.40	151.04-5

FOOTNOTES AND TERMS USED IN TABLE 151.05

Footnotes:

① Group D required as indicated in Subpart 111.60, Subchapter J of this chapter.

② May be necessary under certain climatic conditions in order to maintain temperature.

③ Special requirements not completed as of this date.

Terms and symbols:

Segregation—Tank—

Line 1—Segregation of cargo from surrounding waters:

1=Skin of vessel (single skin) only required. Cargo tank wall can be vessel's hull.

1i=Double skin required. Cargo tank wall cannot be vessel's hull.

Line 2—Segregation of cargo space from machinery spaces and other spaces which have or could have a source of ignition:

1=Single bulkhead only required. Tank wall can be sole separating medium.

Subpart 151.10—Barge Hull Construction Requirements

§ 151.10-1 Barge hull classifications.

(a) Each barge constructed or converted in conformance with this subpart shall be assigned a hull type number.

(1) Effective dates for certain requirements:

(i) Barges constructed or converted between July 1, 1964, and June 1, 1970, in accordance with the construction requirements of § 32.63 of this chapter and § 98.03 of this chapter are considered to comply with the basic provisions of this subpart and shall retain the hull type classification for the service for which

they were originally approved. Changes in product endorsement shall not be considered a change in service, except when a change to a product of higher specific gravity necessitates a reevaluation of the intact and damage stability requirements of §§ 151.10-5 and 151.10-10.

(b) For this purpose the barge hull types shall be defined as follows:

(1) *Type I barge hull.* Barge hulls classed as Type I are those designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. These barges are required to meet standards of intact stability, § 151.10-5; a modified two-compartment standard of

subdivision and damage stability, § 151.10-10; and hull structural requirements, including an assumed grounding condition.

(2) *Type I-S (special) barge hulls.* Type I-S (special) barge hulls are those constructed or converted for the carriage of chlorine in bulk prior to July 1, 1964, and modified to higher stability standards prior to July 1, 1968, but not meeting the requirements for full Type I classification.

(3) *Type II barge hull.* Barge hulls classed as Type II are those designed to carry products which require significant preventive measures to preclude the uncontrolled release of the cargo. These

1i=Double bulkhead required. Cofferdam, empty tank, pump-room, tank with Grade E Liquid (if compatible with cargo) is satisfactory.

Internal tank inspection—

G—Indicates cargo is subject to general provisions of § 151.04-5(b).

Specific numbers in this column are changes from the general provisions.

Abbreviations used:

Tank type: Ind=Independent.

Vent: PV=Pressure vacuum valve.

SR=Safety relief.

Gaging device: Restr.=Restricted.

General usage: NR=No requirements.

NA=Not applicable.

barges are required to meet standards of intact stability, § 151.10-5; a modified one-compartment standard of subdivision and damage stability, § 151.10-10; and hull structural requirements including an assumed grounding condition.

(4) *Type III barge hull.* Barge hulls classed as Type III are those designed to carry products of sufficient hazard to require a moderate degree of control. These barges are required to meet standards of intact stability, § 151.10-5; and hull structural requirements.

§ 151.10-5 Intact stability.

(a) *Transverse stability.* (1) All barges shall have at least the following amounts of transverse stability up to the angle of maximum righting arm or angle of downflooding, whichever is less:

River service—5-foot degrees.

Lakes, bays, and sounds (Great Lakes—summer)—10-foot degrees.

Ocean service (Great Lakes—winter)—15-foot degrees.

(2) As an alternate to determination of stability requirements under the foregoing requirements, the minimum required metacentric height (GM) in feet at any particular draft may be determined by the following formula:

$$GM = \frac{kB}{je}$$

where:

$k = 0.3$ for river service

$= 0.4$ for lakes, bays, and sounds service (Great Lakes—summer)

$= 0.5$ for ocean service (Great Lakes—winter)

$B = \text{beam (ft.)}$

$je = \text{effective freeboard (} f + fa \text{) in feet. This is freeboard to the deck at side (} f \text{) plus a freeboard augmentation (} fa \text{) for those barges with a watertight (structural) trunk. Where draft (} d \text{) is less than } je \text{, it shall be used in lieu of } je \text{. The freeboard augmentation (} fa \text{) may be calculated by the following formula:}$

$$fa = (1.25) \left(\frac{l}{L} \right) \left(\frac{2b}{B} - 1 \right) (h)$$

where:

$l = \text{trunk length (ft.)}$

$L = \text{overall length (ft.)}$

$b = \text{trunk breadth (ft.)}$

$h = \text{trunk height at side (ft.)}$

(b) *Longitudinal stability.* (1) The minimum required longitudinal metacentric height (GMI) in feet at any particular draft shall be determined by the following formula:

$$GMI = \frac{0.02L^2}{d}$$

where:

$L = \text{overall length (ft.)}$

$d = \text{draft (ft.)}$

§ 151.10-10 Subdivision and damage stability.

(a) *Types I and II barge hulls.* (1) Types I and II hopper barge hulls shall be constructed with a complete watertight (rainshield) deck, or if of the "open-hopper" type with such construction that positive buoyancy and stability will be maintained when the barge is fully loaded and the hopper space is flooded to the level of the main deck.

Credit may be given for the buoyancy, if any, of the immersed portion of cargo tanks when an effective arrangement for securing the tanks is provided.

(2) (i) Type I barge hulls shall retain positive buoyancy and stability after holing the bottom or side shell plating anywhere including the intersection of a transverse and a longitudinal watertight bulkhead.

(ii) Type I box barge hulls, specifically designed for operation in an integrated tow, shall retain positive buoyancy and stability after holing the bottom shell plating except in way of a transverse watertight bulkhead, or after holing the side shell plating in way of a transverse watertight bulkhead.

(3) Type II barge hulls shall retain positive buoyancy and stability after holing the bottom or side shell plating anywhere except in way of a transverse watertight bulkhead.

(b) *Extent of damage.* (1) *Transverse bulkheads.* When the spacing of any two transverse bulkheads is less than 6 feet, only one of these bulkheads shall be regarded as forming a part of the subdivision of the vessel when determining extent of flooding.

(2) *Longitudinal wing bulkheads.* Longitudinal wing bulkheads less than 30 inches inboard of the side shell plating shall be considered as ineffective when determining extent of flooding caused by side damage.

(3) *Inner bottom.* Inner bottoms with a depth of less than 15 inches shall be considered ineffective when determining the extent of flooding caused by bottom damage.

(c) *Limits of heel, trim, and freeboard.* (1) *Hopper barges.* The limits of submergence in heel and trim is the deck edge, except that in way of coamings at least 36 inches in height, the limit of submergence may be extended to the intersection of the coaming and deck edge, but in no case should the limit of submergence in heel exceed that specified for an integral trunked tank barge with identical dimensions as specified in subparagraph (2) (i) of this paragraph.

(2) *Integral tank barges.* No part of the actual cargo tank top may be under water.

(i) *Limits of heel:* The limit of submergence in heel is the deck edge, except that for trunked barges an additional submergence at the deck edge may be permitted. This additional submergence is equal to the freeboard augmentation (fa) calculated in § 151.10-5(a) (2).

(ii) *Limits of trim:* The limit of submergence in trim is the deck edge, except that for trunked barges the limit is the intersection of the trunk and deck at the forward and after ends of the trunk. If there is simultaneous heel and trim, the above restriction would apply at the centerline, and an additional submergence on the low side may be permitted by subdivision (i) of this subparagraph.

(iii) Where barges are fitted with a "step-down" in hull depth on either or both ends to permit the barge of greater hull depth to "headlog" or match-up

with adjacent barges of shallower hull depth, the actual deck edge and tank top in such stepped-down area may be submerged provided that all cargo tank openings are located on the higher deck level.

§ 151.10-15 Stability and subdivision calculations.

(a) *General.* The requirements of §§ 151.10-5 and 151.10-10 shall be determined by direct calculations which take into consideration the proportions and design characteristics of the barge and the arrangement and configuration of the damaged compartments. When it is desired to operate a barge in two or more type categories or at different limiting drafts calculations shall be submitted for each condition.

(b) *Free surface.* (1) In preparing calculations, the barge shall be assumed to be in the most severe service condition as regards stability, having due regard to free surface effects of liquids, particularly under conditions of partial filling with high density cargoes.

(2) Calculations shall consider the effect of both transverse and longitudinal free surface.

(3) When calculations are submitted, a maximum specific gravity and capacity shall be established for each tank. This specific gravity may be greater than that for which the scantlings of the tank are designed, provided that there is compliance with the provisions of § 151.15-3(c).

(c) *Certificate endorsement.* The following information shall be submitted, and upon approval of calculations shall form part of the endorsement on the Certificate of Inspection:

(1) Limiting draft for each hull type service for which approval is requested.

(2) Maximum density (lb./gal.) and maximum cargo weight (tons) for each tank for which approval is requested. These weights will normally reflect uniform loading except that for trim purposes the individual tank cargo weight may exceed the uniform loading tank cargo weight, corresponding to the barge fresh water deadweight at the limiting draft, by 5 percent. Where a greater degree of nonuniform loading is desired, longitudinal strength calculations shall be submitted.

§ 151.10-20 Hull construction.

(a) *Construction features.* (1) Each barge hull shall be constructed with a suitable bow form (length, shape, and height of headlog) to protect against diving at the maximum speed at which the barge is designed to be towed. In any integrated tow, only the lead barge need comply with this requirement.

(2) All "open hopper" type barges shall be provided with coamings around the hopper space and a 36-inch minimum height plowshare breakwater on the forward rake. The plowshare breakwater may be omitted, if it is demonstrated to the satisfaction of the Commandant that sufficient protection is achieved without it. Coamings shall have a minimum height of 36 inches forward and may be graduated to a minimum height of 24 inches at midlength and 18

inches thereafter. All hopper barges constructed with a weathertight rain shield over the hopper space are exempt from these requirements, except that they shall be provided with an 18-inch minimum coaming all around the hopper.

(3) All "open hopper" type barges modified for the carriage of chlorine in bulk shall be provided with 36-inch minimum height coamings around the hopper.

(4) All barges in ocean or coastwise service shall be provided with a structural deck and hatches in accordance with the applicable provisions of Subchapter E of this chapter and the scantling requirements of the American Bureau of Shipping.

(b) *Hull structural requirements.* (1) All Types I, II, and III barges shall comply with the basic structural requirements of the American Bureau of Shipping for barges of the ordinary types and the applicable supplementary requirements of this section.

(2) Types I and II barges in inland service: A grounding condition shall be assumed where the forward rake bulkhead rests upon a pinnacle at the water surface. The maximum hull and tank bending moment and tank saddle reactions (if applicable) shall be determined. The hull bending stress shall not exceed the applicable limits of subdivision (i), (ii), or (iii) of this subparagraph. The maximum tank bending moment and saddle reaction shall be used in the tank design calculations required by § 151.15-2(b)(3).

(i) Independent tanks supported by only two saddles do not contribute to the strength and stiffness of the barge hull. In such case, the hull stress shall not exceed either 50 percent of the minimum ultimate tensile strength of the material or 70 percent of the yield strength when specified, whichever is greater.

(ii) Independent tanks supported by three or more saddles contribute to the strength and stiffness of the hull. In such case, the hull stress shall not exceed the percentage stress values prescribed in § 151.10-20(b)(2)(i), multiplied by the quantity $(1.5 - SWT)$, where SWT

UTS

is the stress calculated without including the effect of the tanks, and UTS is the minimum ultimate tensile strength of the material. The value SWT , however, shall in no case be more than 75 percent of UTS .

(iii) Integral tanks may be considered as contributing to the strength and stiffness of the barge hull. The hull stresses for integral tank barges shall not exceed the percentage stress values prescribed in subdivision (i) of this subparagraph.

(3) Types I and II barges in ocean service:

(i) Independent tank barges with tanks supported by three or more saddles shall be subject to a $0.6L^{0.9}$ trochoidal wave hogging analysis to determine the maximum hull and tank bending moments and tank saddle reactions.

(ii) All independent tank barges, regardless of the number of saddle supports shall be subject to a still water

bending analysis to determine the hull bending moment. For those barges with independent tanks supported by three or more saddles, this analysis shall consider tank-hull interaction so as to determine tank bending moments and saddle reactions.

(iii) The still water tank bending moments and saddle reactions shall be superimposed upon those obtained by simultaneous application of the following dynamic loadings:

(a) Rolling 30° each side (120° full cycle) in 10 seconds.

(b) Pitching 6° half amplitude (24° full cycle) in 7 seconds.

(c) Heaving $L/80$ half amplitude ($L/20$ full cycle) in 8 seconds.

(iv) The hull structure and saddle support system shall be analyzed, using the maximum hull bending moments and saddle reactions obtained from the foregoing. Bending stress shall not exceed 60 percent of the yield strength or 42 percent of the minimum tensile strength of the material, whichever is less. Critical buckling strength shall be at least 75 percent greater than calculated buckling stresses. The maximum tank bending moments and saddle reactions shall be used in the tank design calculations required by § 151.15-3(b)(8).

Subpart 151.13—Cargo Segregation

§ 151.13-1 General.

(a) This subpart prescribes the requirements for cargo segregation for cargo tanks, cargo piping, and cargo vents. These requirements are based on considerations of cargo reactivity, stability, and contamination of the surroundings and other cargoes.

§ 151.13-5 Cargo segregation—tanks.

(a) The configurations listed in this paragraph refer to the separation of the cargo from its surroundings and list the various degrees of segregation required. Subparagraphs (1), (2), and (3) of this paragraph explain the symbols used in lines 1 and 2, in order, under the tank segregation column of Table 151.05.

(1) Segregation of cargo from surrounding waters (Line 1 of Table 151.05).

i = Skin of vessel (single skin) only required. Cargo tank wall can be vessel's hull.

ii = Double skin required. Cargo tank wall cannot be vessel's hull.

NA = Nonapplicable for this case. Independent tanks already have such segregation built in through design.

(2) Segregation of cargo space from machinery spaces and other spaces which have or could have a source of ignition (Line 2 of Table 151.05).

i = Single bulkhead only required. Tank wall can be sole separating medium.

ii = Double bulkhead required. Cofferdam, empty tank, pumproom, tank with Grade E Liquid (if compatible with cargo) is satisfactory.

(b) Cargoes which when mixed with each other react in a hazardous manner must be separated from each other by a

cofferdam, empty tank, or a mutually compatible cargo.

(c) If a cofferdam is required for segregation purposes and a secondary barrier is required for low temperature protection by § 151.15-3(d)(4), the void space between the primary and secondary barriers shall not be acceptable in lieu of the required cofferdam.

§ 151.13-10 Cargo segregation-piping.

(a) Tanks containing cargoes which when mixed with each other react in a hazardous manner must have separate pipeline and tank vent systems.

Subpart 151.15—Tanks

§ 151.15-1 Tank types.

This section lists the definitions of the various tank types required for cargo containment by Table 151.05.

(a) *Integral.* A cargo containment envelope which forms a part of the vessel's hull in which it is built, and may be stressed in the same manner and by the same loads which stress the contiguous hull structure. An integral tank is essential to the structural completeness of its vessel's hull.

(b) *Independent.* A cargo containment envelope which is not a contiguous part of the hull structure. An independent tank is built and installed so as to eliminate, whenever possible (or, in any event, to minimize) its stressing as a result of stressing or motion of the adjacent hull structure. In general, therefore, motion of parts of the tank relative to the adjacent hull structure is possible. An independent tank is not essential to the structural completeness of its carrying vessel's hull.

(c) *Gravity.* Tanks having a design pressure (as described in Part 54 of this chapter) not greater than 10 pounds per square inch gage and of prismatic shape or other geometry where stress analysis is neither readily nor completely determinate. (Integral tanks are of the gravity type.)

(d) *Pressure.* Independent tanks whose design pressure (as described in Part 54 of this chapter) is above 10 pounds per square inch gage and fabricated in accordance with Part 54, of this chapter. Independent gravity tanks which are of normal pressure vessel configuration (i.e., bodies of revolution, in which the stresses are readily determinate) shall be classed as pressure vessel type tanks even though their maximum allowable working pressure is less than 10 pounds per square inch gage. Pressure vessel tanks shall be of Classes I, I-L, II, II-L, or III, as defined in Subchapter F of this chapter.

§ 151.15-3 Construction.

This section lists the requirements for construction of the types of cargo tanks defined in § 151.15-1.

(a) *Gravity type tanks:* Gravity type cargo tanks vented at a pressure of 4 pounds per square inch gage or less shall be constructed and tested as required by standards established by the American Bureau of Shipping or other recognized classification society. Gravity type tanks vented at a pressure exceeding 4 but not

exceeding 10 pounds per square inch gage will be given special consideration by the Commandant.

(b) Pressure vessel type tanks: Pressure vessel type tanks shall be designed and tested in accordance with the requirements of Part 54 of this chapter.

(1) Uninsulated cargo tanks, where the cargo is transported, at or near ambient temperatures, shall be designed for a pressure not less than the vapor pressure of the cargo at 115° F. The design shall also be based on the minimum internal pressure (maximum vacuum), plus the maximum external static head to which the tank may be subjected.

(2) When cargo tanks, in which the cargo is transported at or near ambient temperature, are insulated with an insulation material of a thickness to provide a thermal conductance of not more than 0.075 B.t.u. per square foot per degree Fahrenheit differential in temperature per hour, the tanks shall be designed for a pressure of not less than the vapor pressure of the cargo at 105° F. The insulation shall also meet the requirements of paragraph (f) of this section.

(3) Cargo tanks in which the temperature is maintained below the normal atmospheric temperature by refrigeration or other acceptable means shall be designed for a pressure of not less than 110 percent of the vapor pressure corresponding to the temperature of the liquid at which the system is maintained, or the pressure corresponding to the greatest dynamic and static loads expected to be encountered in service. For mechanically stressed relieved cargo tanks, additional factors relating design pressure and maximum allowable pressure shall be as specified by the Commandant. The material of the tank shall meet the material requirements specified in Part 54 of this chapter for the service temperature, and this temperature shall be permanently marked on the tank as prescribed in § 54.10-20 of this chapter.

(4) The maximum allowable temperature of the cargo is defined as the boiling temperature of the liquid at a pressure equal to the setting of the relief valve.

(5) The service temperature is the minimum temperature of a product at which it may be contained, loaded and/or transported. However, the service temperature shall in no case be taken higher than given by the following formula.

$$t_s = t_w - 0.25 (t_w - t_b)$$

where:

t_s = Service temperature.

t_w = Boiling temperature of gas at normal working pressure of container but not higher than +32° F.

t_b = Boiling temperature of gas at atmospheric pressure.

Under normal circumstances, only temperatures due to refrigerated service will be considered in determining the service temperature. Refrigerated service for purposes of this paragraph is defined as service where the temperature is controlled in the process rather than being caused by atmospheric conditions.

(6) Heat transmission studies, where required, shall assume the minimum ambient temperatures of 0° F. still air and

32° F. still water, and maximum ambient temperatures of 115° F. still air and 90° F. still water.

(7) Where applicable, the design of the cargo tanks shall investigate the thermal stresses induced in the tanks at the service temperature.

(8) Calculations showing the stress level in the tanks under dynamic loading conditions for ocean service barges (see § 151.10-20(b)(4)) and grounding conditions for inland service barges (see § 151.10-20(b)(2)) shall be submitted to the Commandant for approval. These calculations shall take into account the local stresses due to the interaction between the barge hull and the tanks.

(c) High density cargo: Cargoes with a specific gravity greater than that for which the scantlings of the tank are designed may be carried provided that:

(1) The maximum cargo weight (tons) in a specific tank does not exceed the maximum cargo weight (tons) endorsed on the certificate of inspection.

(2) The scantlings of the tank are sufficient to prevent rupture under a full head of the higher density cargo. Scantlings meeting ordinary bulkhead requirements for the full head will satisfy this requirement.

(d) Arrangements:

(1) Collision protection. (i) Tanks containing cargoes which are required to be carried in Type I hulls by Table 151.05 shall be located a minimum of 4 feet inboard from the side shell and box end of the vessel. Tanks containing cargoes which are required to be carried in Type II hulls by Table 151.05 shall be located a minimum of 3 feet inboard from the side shell and box end of the vessel.

(ii) All independent cargo tanks installed on Type I or Type II barge hulls shall be protected with suitable collision chocks or collision straps. A longitudinal collision load of one and one half times the combined weight of the tank and the cargo shall be assumed. All other independent cargo tanks shall be provided with suitable collision chocks or collision straps assuming a longitudinal collision load equal to the combined weight of the tank and the cargo. The design bearing stress shall not exceed 2 times the yield strength or 1.5 times the minimum ultimate strength, whichever is less.

(iii) Tanks containing cargoes, which are required to be carried in Type I or Type II hulls by Table 151.05, shall be located a minimum of 25 feet from the head log at the bow. Box barges and trail barges need not comply with this requirement.

(2) Inspection clearances. The distance between tanks or between a tank and the vessel's structure shall be such as to provide adequate access for inspection and maintenance of all tank surfaces and hull structure; but shall not normally be less than 15 inches except in way of web frames or similar major structural members where the minimum clearance shall be equal to the flange or faceplate width.

(3) Access openings. Each tank shall be provided with at least a 15" x 18" diameter manhole, fitted with a cover located above the maximum liquid level

as close as possible to the top of the tank. Where access trunks are fitted to tanks, the diameter of the trunks shall be at least 30 inches.

(4) Low temperature protection. (i) When low temperature cargoes are to be carried in gravity type tanks at a temperature lower than that for which the hull steel is adequate, a secondary barrier designed to contain leaked cargo temporarily shall be provided. The design of the cargo containment system shall be such that under normal service conditions, or upon failure of the primary tank, the hull structure shall not be cooled down to a temperature which is unsafe for the materials involved. The secondary barrier and structural components of the hull which may be exposed to low temperatures shall meet the material requirements (i.e., chemistry and physical properties) specified in Part 54 of this chapter for the service temperature involved. Heat transmission studies and tests may be required to demonstrate that the structural material temperatures in the hull are acceptable.

(ii) The design shall take into consideration the thermal stresses induced in the cargo tank at the service temperature during loading.

(iii) Where necessary, devices for spray loading or other methods of pre-cooling or cooling during loading shall be included in the design.

(iv) Pressure-vessel type tanks shall be radiographed in accordance with the requirements of Part 54 of this chapter. For gravity type tanks, all weld intersections or crossings in joints of primary tank shells shall be radiographed for a distance of 10 thicknesses from the intersection. All other welding in the primary tank and in the secondary barrier, shall be spot radiographed in accordance with the requirements specified in Part 54 of this chapter for Class II-L pressure vessels.

(v) For nonpressure vessel type containment systems, access shall be arranged to permit inspection one side each of the primary tank and secondary barrier, under normal shipyard conditions. Containment systems which, because of their peculiar design, cannot be visually inspected to this degree, may be specially considered provided an equivalent degree of safety is attained.

(e) Installation of cargo tanks:

(1) Cargo tanks shall be supported on foundations of steel or other suitable material and securely anchored in place to prevent the tanks from shifting when subjected to external forces. Each tank shall be supported so as to prevent the concentration of excessive loads on the supporting portions of the shell or head.

(2) Foundations, and stays where required, shall be designed for support and constraint of the weight of the full tank, and the dynamic loads imposed thereon. Thermal movement shall also be considered.

(3) Foundations and stays shall be suitable for the temperatures they will experience at design conditions.

(4) Cargo tanks may be installed "on deck," "under deck," or with the tanks protruding through the deck. All tanks

shall be installed with the manhole openings located in the open above the weather deck. Provided an equivalent degree of safety is attained, the Commandant may approve cargo tanks installed with manhole openings located below the weather deck. Where a portion of the tank extends above the weather deck, provision shall be made to maintain the weathertightness of the deck, except that the weathertightness of the upper deck need not be maintained on:

(i) Vessels operating on restricted routes which are sufficiently protected; or,

(ii) Open hopper type barges of acceptable design.

(5) No welding shall be performed on tanks which require and have been stress relieved unless authorized by the Commandant.

(f) Materials:

(1) Materials used in the construction of cargo tanks shall be suitable for the intended application and shall be in accordance with the applicable requirements of Part 54 of this chapter. For cargoes carried at low temperatures, the tank supports and foundations, and portions of the hull which may be exposed to low temperature, shall also meet the applicable requirements of that part.

(2) When required, cargo tanks shall be lined with rubber or other material acceptable to the Commandant. The interior surfaces of the cargo tanks shall be made smooth, welds chipped or ground smooth, and the surfaces thoroughly cleaned before the lining is applied. The lining material shall be resistive to attack by the cargo, not less elastic than the metal of the tank proper, and non-porous when tested after application. It shall be of substantially uniform thickness. The lining shall be directly bonded to the tank plating, or attached by other satisfactory means acceptable to the Commandant.

(g) Insulation:

(1) Insulation, when provided, shall be compatible with the cargo and the tank materials.

(2) Insulation in a location exposed to possible high temperature or source of ignition shall be one of the following:

(i) Incombustible, complying with the requirements of Subpart 164.009 of Part 164 of this chapter; or

(ii) Fire retardant, having a flame spread rating of 50 or less as determined by ASTM Specification E-84 (Tunnel Test); or,

(iii) Nonburning or "self-extinguishing" as determined by ASTM Specification D-1692, "Flammability of Plastics" and covered by a steel jacket having a minimum thickness of 18 gage (0.0428 inches) (U.S. Standard Gage) or an equivalent means of protection acceptable to the Commandant.

(3) Insulation in a location protected against high temperature or source of ignition need satisfy no requirement for combustibility.

(4) Insulation shall be impervious to water vapor, or have a vapor-proof coating of a fire-retardant material acceptable to the Commandant. Unless the vapor barrier is inherently weather

resistant, tanks exposed to the weather shall be fitted with a removable sheet metal jacket of not less than 18 gage over the vapor-proof coating and flashed around all openings so as to be weathertight. Insulation which is not exposed to the weather when installed on tanks carrying cargoes above ambient temperatures need not be impervious to water vapor nor be covered with a vapor-proof coating.

(5) Insulation shall be adequately protected in areas of possible mechanical damage.

(h) Fire exposure protection: Tanks which are provided with fire exposure protection of one of the following categories may be allowed a reduction in the size of relief valves.

(1) Approved incombustible insulation meeting the requirements of Subpart 164.007 of Part 164 of this chapter which is secured to the tank with steel bands.

(2) Located in a hold or protected by a self-supporting steel jacket or cover (such as a hopper cover) of at least 10 gage (0.1345) for insulation.

(i) Tanks not protected against fire exposure as described in this paragraph shall not be permitted a reduction in size of relief valves.

§ 151.15-5 Venting.

This section contains definitions and requirements for the various methods of venting specified in Table 151.05. In addition to the requirement that all vents must penetrate into tanks at the top of the vapor space, the following methods of venting and the applicable restrictions are listed:

(a) *Open venting.* A venting system which offers no restriction (except pipe losses and flame screen, where used) to the movement of liquid or vapor to or from the cargo tank (via the vent) under normal operating conditions. The total cross-sectional area of the vents shall not be less than the total cross-sectional area of the filling pipe or pipes. Ullage openings may be counted as part of the required cross-sectional area: *Provided*, That each cargo tank has at least one permanent vent. The minimum size of a cargo tank vent shall be not less than 2½ inches. The outlet end of the vent shall terminate in a gooseneck bend and shall be located at a reasonable height above the weather deck, clear of all obstructions. No shut-off valve or frangible disk shall be fitted in the vent lines except that a float check valve may be installed so as to exclude the entry of water into the tank (i.e., to prevent downflooding). An open venting system may be fitted with a flame screen.

(b) *Pressure-vacuum venting.* A normally closed venting system fitted with a device to automatically limit the pressure or vacuum in the tank to design limits. Pressure-vacuum relief valves shall comply with the requirements of Subpart 162.017 of this chapter. The required capacity of the venting system shall be in accordance with Part 54 of this chapter.

(c) *Safety relief venting.* A closed venting system fitted with a device to

automatically limit the pressure in the tank to below its maximum allowable working pressure. The maximum safety relief valve setting shall not exceed the maximum allowable working pressure of the tank. For cargoes carried at ambient temperatures, the minimum safety relief valve setting shall correspond to the saturated vapor pressure of the cargo at 105° F. if carried in an insulated tank, or 115° F. if carried in an uninsulated tank. For cargoes carried below ambient temperature, the safety relief valve setting shall be selected to provide a suitable margin between normal operating pressure of the tank and the opening pressure of the valve but in no case shall it exceed the maximum allowable working pressure of the tank. The safety relief valves shall be of a type approved under subparts 162.001 or 162.018 of Subchapter Q of this chapter. The required capacity of the safety relief valves shall be in accordance with the requirements of Part 54 of this chapter.

(d) *Rupture disks.* (1) When required by the nature of the cargo, rupture disks may be installed in lieu of or in addition to other pressure limiting devices in accordance with the requirements of § 54.15-13 of this chapter.

(2) When a pressure-vacuum relief valve or safety relief valve normally protected by a rupture disk or breaking pin device is exposed to the cargo due to breakage of the disk, the valve shall be reinspected before being returned to service.

§ 151.15-6 Venting piping.

(a) The back pressure in the relief valve discharge lines shall be taken into account when determining the flow capacity of the relief valve to be used. The back pressure in the discharge line shall be limited to 10 percent of the valve operating pressure or a compensating-type valve shall be used. Suitable provision shall be made for draining condensate which may accumulate in the vent piping.

§ 151.15-10 Cargo gaging devices.

This section contains definitions and requirements for types of gaging devices specified in Table 151.05.

(a) *Open gaging:* A gaging method which uses an opening in the cargo tank and which may expose the gage user to the cargo and its vapors. Examples of this type are gage hatch, ullage hole.

(b) *Restricted:* A gaging device which penetrates the cargo tank and which, in operation, causes or permits the release to the atmosphere of small quantities of cargo vapor or liquid. The amount of cargo released is controlled by the small diameter of the tank penetration opening and by a locally operated valve or similar closure device in that opening. When not in use, this type gaging device is closed to maintain the complete integrity of cargo containment. Examples of this type are rotary tube, fixed tube, slip tube, sounding tube. (See §§ 151.03-43 and 151.15-10(g).)

(c) *Closed:* A gaging device which penetrates the cargo tank, but which is part of a closed system maintaining the

complete integrity of cargo containment. This device is designed and installed so as not to release cargo liquid or vapor in any amount to the atmosphere. Examples of this type are automatic float, continuous tape (magnetic coupled), sight glass (protected), electronic probe, magnetic, differential pressure cell.

(d) Isolated or indirect: A gaging method or device which is isolated from the tank (no penetration of the tank shell) and which may employ an indirect measurement to obtain the desired quantity. Examples of this type are weighing of cargo, sonic depth gage (without penetration of tank shell), pipe flow meter.

(e) All gaging devices and related fixtures which form a part of the cargo containment barrier shall be of suitable material and shall be designed for the pressure and temperature of the cargo in accordance with the requirements of Subchapter F of this chapter.

(f) Use of restricted gaging devices:

(1) When required in Table 151.05, cargoes carried under pressure shall have restricted gaging devices designed so that the maximum bleed valve opening is not larger than 0.055" diameter, unless provided with an excess flow valve. Sounding tubes are prohibited for use with cargoes having a vapor pressure in excess of 14.7 p.s.i.a. at 115° F., if carried in an uninsulated tank, or at 105° F., if carried in an insulated tank.

(2) When utilizing a sounding tube, the cargo tank vent system shall be designed to prevent the discharge of cargo through the sounding tube due to pressure build up in the cargo tank vapor space. (See § 151.03-43) When cargoes carried at atmospheric pressure are required to have a restricted gaging device, open gages may be provided in addition to restricted gages for this type of cargo. However, open gages may not be used while cargo transfer operations are actually being performed.

(g) Fixed tube gages are not acceptable as primary means of gaging. They may be used as a check on the calibration of other gaging devices.

(h) For pressure-vessel type tanks, each automatic float, continuous reading tape or similar type gage not mounted directly on the tank or dome shall be fitted with a shutoff device located as close to the tank as practicable. When an automatic float gaging device, which gages the entire height of the tank, is used, a fixed tube gage set in the range of 85 percent to 90 percent of the water capacity of the tank shall be provided in addition as a means of checking the accuracy of the automatic float gage, or other alternate means acceptable to the Commandant may be used.

(i) Gage glasses of the columnar type are prohibited.

(j) Flat sight glasses may be used in the design of automatic float continuous reading tape gages. However such glasses shall be made of high strength material, suitable for the operating temperatures, of not less than one-half inch in thickness and adequately protected by a metal cover.

Subpart 151.20—Cargo Transfer

§ 151.20-1 Piping—general.

(a) Cargo piping systems shall be arranged and fabricated in accordance with this section and Subchapter F. The class of piping system required for a specific cargo shall be as listed in Table 151.05 as a minimum; however, a higher class may be required when the actual service temperature or pressure so dictates. See Table 56.04-2 of this chapter.

(b) Piping system components shall be suitable for use with the cargoes for which the barge is certificated, and shall be of materials listed in Subchapter F of this chapter, or such other material as the Commandant may specifically approve. All piping materials shall be tested in accordance with the requirements of Subchapter F of this chapter. The valve seat material, packing, gaskets, and all other material which comes into contact with the cargo shall be resistant to the chemical action of the cargoes for which the barge is certificated.

(c) Cargo piping systems, when subject to corrosive attack of the cargo, and when serving cargo tanks which are required by this subchapter to be lined or coated, shall be constructed of, lined or coated with corrosion-resistant material. Vent systems shall be similarly constructed, lined, or coated up to and including the vent control device.

(d) All piping systems components shall have a pressure rating at operating temperature (according to the applicable American National Standards Institute, Inc., pressure/temperature relations) not less than the maximum pressure to which the system may be subjected. Piping which is not protected by a relief valve, or which can be isolated from its relief valve, shall be designed for the greatest of:

(1) The cargo vapor pressure at 115° F.

(2) The maximum allowable working pressure of the cargo tank.

(3) The pressure of the associated pump or compressor relief valve.

(4) The total discharge head of the associated pump or compressor where a discharge relief valve is not used.

The escape from cargo piping system relief valves shall be run to venting system or to a suitable recovery system. Provisions shall be made for pressure relief of all piping, valves, fittings, etc., in which excessive pressure build-up may occur because of an increase in product temperature.

(e) Provisions shall be made by the use of offsets, loops, bends, expansion joints, etc., to protect the piping and tank from excessive stress due to thermal movement and/or movements of the tank and hull structure. Expansion joints shall be held to a minimum and where used shall be subject to individual approval by the Commandant.

(f) Low temperature piping shall be isolated from the hull structure. Where necessary, arrangements to provide for the protection of the hull structure from

leaks in low temperature systems in way of pumps, flanges, etc., shall be provided.

(g) Connections to tanks shall be protected against mechanical damage and tampering. Underdeck cargo piping shall not be installed between the outboard side of cargo containment spaces and the skin of the barge, unless provision is made to maintain the minimum inspection and collision protection clearances (where required) between the piping and the skin. Cargo piping which is external to tanks, and is installed below the weather deck shall be joined by welding, except for flanged connections to shutoff valves and expansion joints.

(h) Piping shall enter independent cargo tanks above the weatherdeck, either through or as close to the tank dome as possible.

(i) Horizontal runs of cargo piping on integral tank barges may be run above or below the weatherdeck. When run below the weatherdeck, the following are applicable:

(1) Horizontal runs located entirely within integral cargo tanks shall be fitted with a stop valve, located inside the tank that is being serviced and operable from the weatherdeck. There shall be cargo compatibility in the event of a piping failure.

(2) Horizontal runs of cargo piping installed in pipe tunnels may penetrate gravity type tanks below the weatherdeck: *Provided*, That each penetration is fitted with a stop valve operable from the weatherdeck. If the tunnel is directly accessible from the weatherdeck without penetrating the cargo tank, the stop valve shall be located on the tunnel side. If the tunnel is not accessible from the weatherdeck, the valve shall be located on the tank side of the penetration.

(3) The tunnel shall comply with all tank requirements for construction, location, ventilation, and electrical hazard. There shall be cargo compatibility in the event of a piping failure.

(4) The tunnel shall have no other openings except to the weatherdeck or a cargo pumproom.

§ 151.20-5 Cargo system valving requirements.

For the purpose of adequately controlling the cargo, both under normal operating and casualty conditions, every cargo piping system shall be provided with one of the following sets of control valves and meet the requirements listed below. Cargo tanks, whether gravity or pressure vessel type, for cargoes having a saturated vapor pressure of 10 pounds per square inch gage or less at 115° F. (105° F. if the tank is insulated) shall be provided with a valving system designated as Gravity-1. Cargo tanks, whether gravity or pressure vessel type, for cargoes which are carried below ambient temperature and whose vapor pressure is maintained at 10 pounds per square inch gage or below shall be provided with a valving system designated as Gravity-2. Cargo tanks for cargoes which have vapor pressures above 10 p.s.i.g. at 115° F. (105° F. if tank is insulated) shall be provided with a valving system designated as Pressure-1. Cargo

tanks for cargoes which have vapor pressures above 10 pounds per square inch gage at 115° F. (105° F. if tank is insulated) and which require greater protection due to their hazardous characteristics shall be provided with a valving system designated as Pressure-2. The requirements of paragraphs (a) through (d) of this section for stop valves or excess flow valves to be fitted at tank penetrations are not applicable to nozzles at which pressure vacuum or safety relief valves are fitted.

(a) Gravity-1 (G-1):

(1) One manually operated stop valve shall be installed on each tank filling and discharge line, located near the tank penetration.

(2) One stop valve or blind flange shall be installed at each cargo hose connection. When a cargo hose connection is in use, it shall be provided with a stop valve; which may be part of the vessel's equipment or may be part of the shore facility and attached to the barge end of the loading hose. When a cargo hose connection is not in use, it may be secured with a blind flange.

(3) If individual deepwell pumps are used to discharge the contents of each cargo tank, and the pumps are provided with a remote shutdown device, a stop valve at the tank is not required on the tank discharge line.

(b) Gravity-2 (G-2):

(1) One manually operated stop valve shall be installed on each tank penetration, located as close as possible to the tank.

(2) One remote operated, quick closing shut-off valve shall be installed at each cargo hose connection.

(3) A remote shutdown device shall be installed for all cargo handling machinery.

(c) Pressure-1 (P-1):

(1) One manually operated stop valve and one excess flow valve shall be installed on each tank penetration, located as close as possible to the tank.

(2) One manually operated stop valve shall be installed at each cargo hose connection, when in use.

(d) Pressure-2 (P-2):

(1) One manually operated stop valve and one excess flow valve shall be installed at each tank penetration, located as close as possible to the tank.

(2) One remote operated quick closing shutoff valve shall be installed at each cargo hose connection when in use.

(3) No tank penetration shall be less than 1 inch diameter.

(e) Cargo tank penetrations which are connections for gaging or measuring devices need not be equipped with excess flow or remote operated quick closing valves provided that the opening is constructed so that the outward flow of tank contents shall not exceed that passed by a No. 54 drill size (0.055-inch diameter).

(f) The control system for any required quick closing shutoff valves shall be such that the valves may be operated from at least two remote locations on the vessel; if means of fire protection is required by Table 151.05, the control sys-

tem shall also be provided with fusible elements designed to melt between 208° F. and 220° F., which will cause the quick closing shutoff valves to close in case of fire. Quick closing shutoff valves shall be of the fail-closed (closed on loss of power) type and be capable of local manual operation. Quick closing shutoff valves shall operate from full open to full closed under all service conditions in not more than 10 seconds, without causing excessive pressure surges.

(g) Excess flow valves, where required, shall be closed automatically at the rated closing flow of vapor or liquid as tested and specified by the manufacturer. The piping, including fittings, valves, and appurtenances protected by an excess flow valve, shall have a greater capacity than the rated closing flow of the excess flow valve. Excess flow valves may be designed with a bypass not to exceed 0.040-inch diameter opening to allow equalization of pressure, after an operating shutdown.

(h) Suitable means shall be provided to relieve the pressure and remove liquid contents from cargo lines and hoses to the cargo tank or other safe location prior to effecting disconnections.

§ 151.20-10 Cargo system instrumentation.

(a) Each tank operated at other than ambient temperature shall be provided with at least one remote reading temperature sensor located in the liquid phase of the cargo. The temperature gage shall be located at the cargo handling control station or another approved location.

(b) Where required, each tank equipped with safety relief valves shall be fitted with a pressure gage which shall be located at the cargo handling control station or at another approved location.

§ 151.20-15 Cargo hose if carried on the barge.

(a) Liquid and vapor line hose used for cargo transfer shall be of suitable material resistant to the action of the cargo. Hose shall be suitable for the temperatures to which it may be subjected and shall be acceptable to the Commandant.

(b) Hose subject to tank pressure, or the discharge pressure of pumps or vapor compressors, shall be designed for a bursting pressure of not less than 5 times the maximum safety relief valve setting of the tank, pump, or compressor, whichever determines the maximum pressure to which the hose may be subjected in service.

(c) Each new type of cargo hose, complete with end fittings, shall be prototype tested to a pressure not less than five times its specified maximum working pressure. The hose temperature during this prototype test shall duplicate the intended extreme service temperature. Thereafter, each new length of cargo hose produced shall be hydrostatically tested at ambient temperature to a pressure not less than twice its maximum working pressure nor more than two-fifths its bursting pressure. The hose shall be marked with its maximum work-

ing pressure, and if used in other than ambient temperature service, its maximum or minimum temperature.

§ 151.20-20 Cargo transfer methods.

(a) Cargo transfer may be accomplished by means of gravity, pumping, vapor or gas pressurization, or fluid displacement unless otherwise provided in Subpart 151.50 of this part.

(b) Vapor or gas pressurization may be used only in transferring cargo from pressure vessel type cargo tanks. The pressurizing vapor or gas lines shall be provided with safety relief device in the lines set to open at a pressure no greater than 90 percent of the set pressure of the cargo tank safety relief valve. The pressurizing line shall be fitted with a stop valve at the tank, and a check valve to prevent the accidental release of cargo through the pressure line.

(c) Fluid displacement is permitted with either gravity or pressure vessel type cargo tanks. The displacing fluid shall enter the tank under low relative pressure. The fluid entry line shall be fitted with a safety relief valve set to lift at a pressure no higher than 80 percent of the cargo tank safety relief valve setting.

(d) When cargo vapors are flammable, combustible or toxic, cargo filling lines entering the top of the tank shall lead to a point at or near the bottom. Spray filling lines, discharging near the top of the tank, may be fitted in lieu of, or in addition to, the above cargo filling lines.

Subpart 151.25—Environmental Control

§ 151.25-1 Cargo tank.

When carrying certain commodities regulated by this subchapter, one of the following types of cargo protection may be required, within the main cargo tank, and in some cases, in the space between the primary and secondary barriers.

(a) *Inerted*. All vapor spaces within the cargo tank are filled and maintained with a gas or vapor which will not support combustion and which will not react with the cargo.

(b) *Padded*. All vapor spaces within the cargo tanks are filled and maintained with a liquid, gas (other than air), or vapor which will not react with the cargo.

(c) *Ventilated (forced)*. Vapor space above the liquid surface in the tank is continuously swept with air by means of blowers or other mechanical devices requiring power.

(d) *Ventilated (natural)*. Vapor space above the liquid surface in the tank is continuously swept with atmospheric air without the use of blowers or other mechanical devices requiring power (e.g., "chimney-effect" ventilation).

§ 151.25-2 Cargo handling space.

Pump rooms, compressor rooms, refrigeration rooms, heating rooms, instrument rooms or other closed spaces regularly entered by operating personnel, in which work is performed on the cargo or in which the cargo movement is locally controlled, may be required to be fitted

with one of the following types of ventilation:

(a) *Forced ventilation.* The forced ventilation system shall be designed to insure sufficient air movement through these spaces to avoid the accumulation of toxic or flammable vapors and to insure sufficient oxygen to support life, and, in any event, the ventilation system shall have a minimum capacity sufficient to permit a change of air every 3 minutes.

(b) *Natural ventilation.* The natural ventilation system shall be designed to insure sufficient air movement to avoid the accumulation of toxic or flammable vapors and to insure sufficient oxygen to support life.

Subpart 151.30—Portable Fire Extinguishers

§ 151.30-1 Type.

When required by Table 151.05, approved portable fire extinguishers shall be installed in accordance with Subpart 34.50 of this chapter. The fire extinguishing media shall be dry chemical or other suitable agent for all locations.

Subpart 151.40—Temperature of Pressure Control Installations

§ 151.40-1 Definitions.

This section defines the various methods by which the cargo may be heated or cooled.

(a) *Boiloff.* Cargo pressure and temperatures are maintained by permitting the cargo to boil naturally and the cargo vapor thus generated removed from the tank by venting.

(b) *External cargo cooling.*—(1) *Cargo vapor compression.* A refrigeration system in which the cargo vapors generated within the tank are withdrawn, compressed, and the lower energy vapor or its condensate returned to the tank.

(2) *External heat exchange.* A refrigeration system in which the cargo vapor or liquid is cooled outside the cargo tanks by being passed through a heat exchanger. Refrigeration is not accomplished by direct compression of the cargo.

(c) *Internal heat exchange.* A refrigeration system in which a cooling fluid is passed through heat transfer coils immersed in the cargo tank liquid or vapor phases.

(d) *Tank refrigeration.* A refrigeration system in which the cooling fluid is passed around the cargo tank exterior in order to remove heat from the tank or its surroundings.

(e) *No refrigeration.* A system that allows the liquefied gas to warm up and increase in pressure. The insulation and tank design pressure shall be adequate to provide for a suitable margin for the operating time and temperatures involved.

(f) *Tank heating.* (1) A system in which the cargo is heated by means of steam or other heat transfer fluid running through coils within or around the tank. The cargo itself does not leave the tank.

(2) A recirculating system in which the cargo leaves the tank, is pumped through a heater and then returned to the tank.

§ 151.40-2 Materials.

Materials used in the construction of temperature or pressure control systems shall be suitable for the intended application and meet the requirements of Subchapter F and the Special Requirements section of this subchapter.

§ 151.40-5 Construction.

Construction of machinery or equipment, such as heat exchangers, condensers, piping, etc., associated with temperature or pressure control systems shall meet the requirements of Subchapter F of this chapter. The electrical portions of these installations shall meet the requirements of Subchapter J of this chapter.

§ 151.40-10 Operational requirements.

Control systems, required by Table 151.05 shall be provided with an audible or visual high cargo temperature or high cargo pressure alarm which is discernible at the towboat. The alarm shall operate when either the pressure or the temperature exceeds the operating limits of the system. The alarm may monitor either pressure or temperature, but must be independent of the control system.

§ 151.40-11 Refrigeration systems.

(a) *Boiloff systems:* The venting of cargo boiloff to atmosphere shall not be used as a primary means of temperature or pressure control unless specifically authorized by the Commandant.

(b) *Vapor compression, tank refrigeration, and secondary refrigeration systems:* The required cooling capacity of refrigeration systems shall be sufficient to maintain the cargo at design operating conditions with ambient temperature of 115° F. still air and 90° F. still water. The number and arrangement of compressors shall be such that the required cooling capacity of the system is maintained with one compressor inoperative. Portions of the system other than the compressors need not have standby capacity.

Subpart 151.45—Operations

§ 151.45-1 General.

(a) Barges certificated as tank barges (Subchapter D of this chapter) or cargo barges (Subchapter I of this chapter) for the carriage of cargoes regulated by this subchapter shall meet all applicable requirements for operations in the appropriate subchapter; in addition, requirements prescribed in this subpart shall apply to either type of certification.

§ 151.45-2 Special operating requirements.

(a) The requirements of this section shall apply to all barges carrying in bulk any cargoes regulated by this subchapter; however, the provisions of this section are not applicable to such barges when empty and gas-free.

(b) When it is necessary to operate box or square-end barges as lead barges of tows, the person in charge of the towing vessel shall control the speed to insure protection against diving and swamping of such barges, having due regard to their design and freeboard, and to the operating conditions.

(c) No cargo tank hatch, ullage hole, or tank cleaning openings shall be opened or remain open except under the supervision of the person in charge, except when the tank is gas free.

(d) Barges, when tendered to the carrier for transportation, shall have all bilges and void spaces (except those used for ballasting) substantially free of water. Periodic inspections and necessary pumping shall be carried out to insure maintenance of such water-free condition in order to minimize the free surface effects, both in longitudinal and transverse directions. Except when otherwise considered necessary for inspection or pumping, all hatch covers and other hull closure devices for void spaces and hull compartments other than cargo spaces shall be closed and secured at all time.

(e) Cargo signs and cards:

(1) Warning signs shall be displayed on the vessel, port and starboard, facing outboard without obstruction, at all times except when the vessel is gas free. The warning sign shall be rectangular and a minimum of 3 feet wide and 2 feet high. It shall be of sufficient size to accommodate the required alerting information, which shall be shown in black block style letters and numerals (characters) at least 3 inches high on a white background. The minimum spacing between adjacent words and lines of characters shall be 2 inches. The minimum spacing between adjacent characters shall be one-half inch. All characters shall have a minimum stroke width of one-half inch and shall be a minimum of 2 inches wide, except for the letters "M" and "W", which shall be a minimum of 3 inches wide, and except for the letter "I" and the Numeral "1", which may be 1/2-inch wide. The signs shall have a 2-inch minimum white border clear of characters. The signs shall be maintained legible. The alerting information shall include the following:

WARNING

DANGEROUS CARGO

(This sign may be covered or removed when Subchapter O commodities are not being carried.)

NO VISITORS

NO SMOKING

(This sign may be removed or covered when the commodity is not flammable or combustible.)

NO OPEN LIGHTS

(This sign may be removed or covered when the commodity is not flammable or combustible.)

(2) (i) Names and locations of all cargoes will be displayed in a readily discernible manner on all barges carrying one or more commodities regulated by

this subchapter. This may be an individual sign at or on each tank or by a single sign similar to the following example:

Tank No.	Cargo
IP -----	/xxxx/
IS -----	/xxxx/
2P -----	/xxxx/
2S -----	/xxxx/

These signs may be printed, handwritten, permanent or changeable, but be visible and readable at all times. These signs should be as readable, as those specified in subparagraph (1) of this paragraph. Cargoes regulated by other subchapters will be included whenever carried simultaneously with commodities regulated by this subchapter.

(ii) When the dangerous cargo barge is carrying only a single product, the Warning Sign required by subparagraph (1) of this paragraph can be considered as meeting the requirements for the cargo location sign. The name of the commodity shall be added to the Warning Sign.

(3) A cargo information card for each cargo regulated by this subchapter, shall be carried on the bridge or in the pilot house of the towing vessel, readily available for use by the person in charge of the watch. This information card shall also be carried aboard the barge, mounted near the Warning Sign required by subparagraph (1) of this paragraph, in such position as to be easily read by a man standing on the deck of the barge. The minimum card size shall be 7" x 9 1/2". The card shall have legible printing on one side only. The card shall be laminated in clear plastic or otherwise made weatherproof. The following data shall be listed:

(i) Cargo identification and characteristics: Identification of the cargo, as listed in Table 151.01-10(b), its appearance and odor. A statement of the hazards involved and instructions for the safe handling of the cargo and, as applicable, the need for special cargo environments.

(ii) Emergency procedures: Precautions to be observed in the event of spills, leaks, or equipment or machinery breakdown and/or uncontrolled release of the cargo into the waterway or atmosphere. Precautions to be observed in the event of exposure of personnel to toxic cargoes.

(iii) Firefighting procedures: Precautions to be observed in the event of a fire occurring on or adjacent to the barge, and enumeration of firefighting media suitable for use in case of a cargo fire.

(f) Surveillance: During the time the cargo tanks contain any amount of liquid or gaseous dangerous cargoes requiring Type I or Type II barge hulls, the barge shall be under surveillance, as set forth in this paragraph:

(1) A strict watch of each unmanned barge in tow shall be maintained from the towing vessel while under way.

(2) A towing vessel engaged in transporting such unmanned barges shall not leave them unattended. When a barge

is moored, but not gas free, it shall be under the care of a watchman who may be a member of the complement of the towing vessel, or a terminal employee, or other person. This person shall be responsible for the security of the barge and for keeping unauthorized persons off the barge. Such person shall be provided with, read, and have in his possession for ready reference the information cards required by paragraph (e) of this section.

(g) All cargo hatches shall be closed, dogged down, or otherwise tightly secured.

§ 151.45-3 Manning.

Except as provided for in this section, barges need not be manned unless in the judgment of the Officer in Charge, Marine Inspection, such manning is necessary for the protection of life and property and for safe operation of the vessel. Vessels requiring manning for safe operation shall be subject to additional requirements as determined by the Commandant. Towing vessels, while towing barges which are not required to be manned, shall be provided with and have on board the information card required by § 151.45-2(e)(3). This card shall be in the possession of the master or person in charge.

§ 151.45-4 Cargo handling.

(a) Men on duty: A sufficient number of persons shall be on duty to perform cargo transfer operations.

(1) When the product to be transferred has flammable or combustible characteristics as defined in this part, the shipper and the owners, charterer, agent, masters, or persons in charge of such barges shall insure that a person holding a valid license as master, mate, pilot, or engineer, or a certificated tankerman is on duty to perform transfer operations. This licensed person or certificated tankerman shall be considered as the person in charge of the unmanned tank barge. In addition, the Officer in Charge, Marine Inspection, shall be furnished satisfactory, documentary evidence that this person is trained in, and capable of performing competently, the necessary operation which relates to the transfer of the specific cargo.

(2) When the product to be transferred does not meet the definition of flammability or combustibility as defined in these regulations, the shipper and the owners, charterer, agent, masters, or persons in charge of such barges shall insure that a person especially qualified in the handling of the specific cargo to be transferred shall be on duty to perform or supervise cargo transfer operations. This person shall be considered to be in charge of such operations. The Officer in Charge, Marine Inspection, shall be furnished satisfactory documentary evidence that this person is trained in, and capable of performing competently, the necessary operation which relates to the transfer of such cargo.

(b) Closing of sea and ballast valves: All sea and ballast valves are to be properly aligned and lashed, or sealed in

their correct position prior to beginning cargo transfer operations. Under no circumstances shall such valves be secured by locks.

(c) Connecting for cargo transfer:

(1) Movement of the vessel shall be considered when making the cargo connections to insure safe cargo transfer. Suitable material shall be used in joints and in couplings when making connections to insure that they are tight. Under no circumstances shall less than three bolts be used in a bolted flanged coupling.

(2) When cargo connections are supported by the vessel's tackle, the person in charge of the transfer operations shall inspect the vessel to insure that sufficient tackles are used.

(3) Pans or buckets shall be placed under cargo hose connections.

(4) Cargo transfer operations for any cargo requiring a PV or safety relief venting device in Table 151.05 shall be performed with cargo hatch covers closed.

(d) Inspection prior to transfer of cargo: Prior to the transfer of cargo, the person in charge of the transfer operation shall inspect the barge and other cargo equipment to assure himself that the following conditions exist:

(1) The Certificate of Inspection is endorsed for the products to be loaded. Loading restrictions, if any, should be noted.

(2) Warning signs are displayed as required.

(3) Cargo information cards for the product are aboard.

(4) No repair work in way of cargo space is being carried out.

(5) Cargo connections and hatch covers conform with the provisions of paragraph (c) of this section and cargo valves are properly set.

(6) All connections for cargo transfer have been made to the vessel's fixed pipeline system.

(7) In transferring flammable or combustible cargoes, there are no fires or open flames present on the deck, or in any compartment which is located on, facing, open or adjacent to the part of the deck on which cargo connections have been made.

(8) The shore terminal or other tank vessel concerned has reported itself in readiness for transfer of cargo.

(9) All sea valves are properly set and those connected to the cargo piping are closed.

(10) When transferring flammable or combustible cargoes that a determination was made as to whether or not boiler and/or galley fires can be maintained with reasonable safety.

(11) Cargoes which when mixed with each other react in a hazardous manner must be separated from each other by a cofferdam, empty tank or mutually compatible cargo. Nor shall such cargoes be stowed in tanks having common pipelines or vent systems. See §§ 151.13-5 and 151.13-10.

(e) Duties of the person in charge during transfer operations: The person in charge of the transfer operations shall control the operations as follows:

(1) Supervise the operation of the cargo system valves.

(2) Start transfer of cargo slowly.

(3) Observe cargo connections and hose for leakage.

(4) Observe operating pressure on cargo systems.

(5) Comply with loading limitations placed on the vessel by the Certificate of Inspection, if any, for the purpose of not overloading individual tanks or the vessel.

(6) Observe the loading rate for the purpose of avoiding overflow of the tanks.

(f) Cargo transfer operations shall not be started or, if started, shall be discontinued under the following conditions.

(1) During severe electrical storms.

(2) If a fire occurs on the barge, the wharf or in the immediate vicinity.

(3) If potentially dangerous leakage occurs.

(g) No vessel shall come alongside or remain alongside a barge in way of its cargo tanks while it is transferring cargo unless the conditions then prevailing are mutually acceptable to the persons in charge of cargo handling.

(h) Auxiliary steam, air, fuel, or electric current: When discharging cargo from one or more barges, the towing vessel may furnish steam, air, fuel, or electric current for pumps on barges or dock, but in no case shall the cargo pass through or over the towing vessel.

(i) Termination of transfer operations: When transfer operations are completed, the valves on cargo connections on the vessel shall be closed. The cargo connections shall be drained of cargo.

(j) Transfer of other cargo or stores on a barge.

(1) Packaged goods, freight, and ship's stores shall not be loaded or discharged during the loading of flammable cargoes except by permission of the person in charge of the transfer operation. Explosives shall not be loaded or carried on any barge containing products regulated by this subchapter.

(2) Where package and general cargo is carried directly over bulk cargo tanks, it shall be properly dunnaged to prevent chafing of metal parts and securely lashed or stowed.

(k) Transportation of other cargo or stores on barges: Barges may be permitted to transport deck cargoes directly over bulk cargo spaces when the nature of such deck cargoes and the methods of loading and unloading same do not create an undue hazard. Such barges shall have their decks properly dunnaged to prevent chafing between the steel parts of the vessel and the deck cargo.

(l) Deck construction must be adequate to support the intended load. Provisions for carrying deck cargo shall be endorsed on the Certificate of Inspection by the Officer in Charge, Marine Inspection.

(m) Emergencies: In case of emergencies, nothing in the regulations in this subchapter shall be construed as preventing the person in charge of trans-

fer operations from pursuing the most effective action in his judgment for rectifying the conditions causing the emergency.

§ 151.45-5 Open hopper barges.

(a) All open hopper barges not constructed or modified in conformance with the provisions of Subpart 151.10 of this part when carrying in bulk any cargoes regulated by this subchapter shall meet the provisions of this section. However, the provisions of this section are not applicable to such barges when empty (not necessarily cleaned or gas-freed).

(1) Except as otherwise provided in this section, no such open hopper type barge shall be placed as lead barge in any tow. These barges shall be placed in protected positions within the tow so that the danger from diving or swamping will be minimized. Where, due to operating conditions, compliance with this subparagraph is impossible, the provisions of subparagraph (3) of this paragraph apply. The person in charge of the towing vessel shall be responsible for compliance with this subparagraph.

(2) No such open hopper type barge shall be moved from a loading facility unless all void spaces and bilges are substantially free of water. Periodic inspections and necessary pumping shall be carried out to insure the maintenance of such water-free conditions, in order to minimize the free surface effect in both the longitudinal and transverse directions. Except when considered necessary for inspection or pumping, all hatch covers and other hull closure devices for void spaces and hull compartments shall be closed and secured at all times. In the case of unmanned barges, the person in charge of the towing vessel shall be deemed to be in charge of the barge, and all requirements to be carried out on the barge shall be carried out by or under the direction of this person.

(3) When an open hopper type barge is in an exposed position, such that protection from swamping provided by adjoining barges cannot be obtained from the location within the tow, it shall be the responsibility of the person in charge of the towing vessel to control speed so as to insure protection against diving and swamping of the barge, having regard to its design and freeboard, and other operating conditions.

(b) To show that special operating requirements apply to a specific open hopper type barge, additional placards or signs shall be displayed in at least four different locations on the barge when the cargoes subject to this part are carried in any form in the cargo tanks. The placards or signs shall be posted on the barge approximately amidships on each side and near the centerline fore and aft facing outboard. Racks, or other suitable means for mounting such placards or signs, shall be so arranged as to provide clear visibility and shall be protected from becoming readily damaged or obscured. The placards or signs shall be at least equal in dimensions to the DOT standard tank car "Dangerous" placard (10 3/4 inches square or larger)

and shall display a circle (10 inches in diameter or larger) with alternating quadrants of white and red, and so mounted that the red quadrants are centered on the vertical axis. The shipper and/or owner of the barge shall be responsible for the installation of the required placards or signs, including maintenance of them while such barge is in temporary storage with cargo aboard. The person in charge of the towing vessel shall be responsible for the continued maintenance of the placards or signs while such barge is in transit.

§ 151.45-6 Maximum amount of cargo.

(a) Tanks carrying liquids or liquefied gases at ambient temperatures regulated by this subchapter shall be limited in the amount of cargo loaded to that which will avoid the tank being liquid full at 105° F. if insulated, or 115° F. if uninsulated. If specific filling densities are designated in Subpart 151.50 of this part, they shall take precedence over that noted above.

(b) Refrigerated and semirefrigerated tanks shall be filled so that there is an outage of at least 2 percent of the volume of the tank at the temperature corresponding to the vapor pressure of the cargo at the safety relief valve setting. A reduction in the required outage may be permitted by the Commandant when warranted by special design considerations. Normally, then, the maximum volume to which a tank may be loaded is:

$$V_L = \frac{0.98d_r V}{d_L}$$

where:

V_L = Maximum volume to which tank may be loaded.

V = Volume of tank.

d_r = Density of cargo at the temperature required for a cargo vapor pressure equal to the relief valve setting.

d_L = Density of cargo at the loading temperature and pressure.

§ 151.45-7 Shipping papers.

Each barge carrying dangerous cargo shall have on board a bill of lading, manifest, or shipping document giving the name of shipper, location of the loading point, and the kind, grade, and approximate quantity by compartment of each cargo in the barge. Such manifest or bills of lading may be made out by the shipper, master of the towing vessel, owner, or agent of the owner. However, in the case of unmanned barges the master of the towing vessel shall either have a copy of the shipping papers for each barge in his tow or he shall make an entry in the towing vessel's log book giving the name of the shipper, location where the barge was loaded, and the kind, grade, and quantity of cargo by compartment in the barge. The barge shall not be delayed in order to secure the exact quantities of cargo.

§ 151.45-8 Illness, alcohol, drugs.

A person who is under the influence of liquor or other stimulants, or is so ill as to render him unfit to perform service shall not be permitted to perform any duties on the barge.

§ 151.45-9 Signals.

While fast to a dock, a vessel during transfer of bulk cargo shall display a red flag by day or a red light by night, which signal shall be so placed that it will be visible on all sides. When at anchor, a vessel during transfer of bulk cargo shall display a red flag by day, placed so that it will be visible on all sides. This flag may be metallic.

Subpart 151.50—Special Requirements for Certain Cargoes

§ 151.50-1 General.

Special requirements found in this subpart pertain to specific cargoes and to similar groups of cargoes. These requirements are in addition to and take precedence over any other requirements found in these regulations.

§ 151.50-5 Cargoes having toxic properties.

(a) This section contains requirements for the transportation of cargoes defined as Class "B" or "C" poisons in §§ 146.25-10 and 146.25-15 of this chapter.

(b) Independent tanks shall be designed and tested for a head of at least 8 feet above the top of the tank using the specific gravity of the product to be carried. In addition, tank design calculations shall demonstrate that the tank can withstand, without rupture, a single loading to the highest level to which the product may rise, if that exceeds 8 feet. In general, plate less than five-sixteenths inch in thickness shall not be used in the fabrication of independent tanks unless otherwise approved.

(c) (1) Cargo tanks transporting liquids having a Reid vapor pressure exceeding 14 pounds per square inch absolute or vented at a gage pressure exceeding 4 pounds per square inch, or where air or water pressure is used to discharge the cargo, shall be fabricated as arc-welded unfired pressure vessels.

(2) Unfired pressure vessel cargo tanks shall be designed for a pressure not less than the vapor pressure, in pounds per square inch gage, of the lading at 115° F., or the maximum air or water pressure used to discharge the cargo, whichever is greater, but in no case shall the design pressure of such tanks be less than 30 pounds per square inch gage.

(d) Piping:

(1) The pumps and piping used for cargo transfer shall be independent of all other piping.

(2) Where multiple cargoes are carried, and the cargo piping conveying cargoes covered under this section are led through cargo tanks containing other products, the piping shall be encased in a tunnel.

(3) Where cargo lines handling other products, or bilge and ballast piping are led through tanks containing cargoes covered by this section, the piping shall be encased in a tunnel.

(e) Gravity type cargo tanks shall be fitted with an approved pressure-vacuum relief valve of not less than 2½-inch size, which shall be set at a pressure of not less than 3 pounds per square inch

gage, but not in excess of the design pressure of the tank.

(f) The discharge fittings from each safety relief or pressure vacuum relief valve shall be directed in such a manner as to not impinge on another tank, piping or any other equipment which would increase the fire hazard should burning products be discharged from the safety or pressure vacuum relief valve as a result of a fire or other casualty. In addition, the discharges shall be directed away from areas where it is likely that persons might be working and as remote as practicable from ventilation inlets and ignition sources. A common discharge header may be employed if desired. The area near the discharge fittings shall be clearly marked as a hazardous area.

(g) A means shall be provided for either the reclamation or safe venting of vapors during the loading and unloading operations. For this purpose the safety relief or pressure vacuum relief valve shall be provided with a valved bypass to a vapor return line shore connection which shall be used whenever vapor return shore facilities are available. In the event vapors must be vented to the atmosphere, a vent riser shall extend at least 12 feet above the highest level accessible to personnel. The vent riser may be collapsible for ease of stowage when not in use. Vapor return lines or vent risers for tanks carrying the same class product may be connected to a common header system if desired. Tanks carrying cargoes covered by this section shall be vented independent of tanks carrying other products.

(h) The pump room ventilation outlet duct exhausts shall terminate at a distance of at least 6 feet above the enclosed space or pump room and at least 6 feet from any entrance to the interior part of the vessel. The discharge end of the exhaust ducts shall be located so as to preclude the possibility of recirculating contaminated air through the pump room, or other spaces where personnel may be present.

§ 151.50-6 Motor fuel antiknock compounds.

When transporting motor fuel antiknock compounds containing tetraethyl lead and tetramethyl lead the requirements listed in this section shall be observed.

(a) Tanks used for these cargoes shall not be used for the transportation of any other cargo except those commodities to be used in the manufacture of tetraethyl lead and tetramethyl lead.

(b) Pump rooms shall be equipped with forced ventilation with complete air change every 2 minutes. Air analysis shall be run for lead content to determine if the atmosphere is satisfactory prior to personnel entering the pump room.

(c) Entry into cargo tanks used for the transportation of these cargoes is not permitted.

(d) No internal tank inspection is required. If it is desired to internally inspect tanks used for these cargoes, the Commandant must be notified in advance before such inspection is made.

(e) The provisions of § 151.50-5 shall also be met as a requirement for shipping antiknock compounds containing tetraethyl lead and tetramethyl lead.

§ 151.50-10 Alkylene oxides.

(a) For the purpose of this part, alkylene oxides are considered to be ethylene oxide and propylene oxide.

(b) Alkylene oxides transported under the provisions of this part shall be acetylene free.

(c) (1) No other product may be transported in tanks certified for an alkylene oxide except that the Commandant may approve subsequent transportation of other products and return to alkylene oxide service if tanks, piping and auxiliary equipment are adequately cleaned to the satisfaction of the Marine Inspector.

(2) Unless authorized by the Commandant, no other kind of cargo except methane, ethane, propane, butane and pentane shall be on board a tank vessel certificated for the carriage of an alkylene oxide at the same time an alkylene oxide in either the liquid or vapor state is present in any cargo tank. Alkylene oxide tanks shall not be installed in tanks intended for any other cargo.

(d) All valves, flanges, fittings, and accessory equipment shall be of a type suitable for use with the alkylene oxides and shall be made of steel or stainless steel, or other materials acceptable to the Commandant. Impurities of copper, magnesium and other acetylide-forming metals shall be kept to a minimum. The chemical composition of all material used shall be submitted to the Commandant for approval prior to fabrication. Disks or disk faces, seats and other wearing parts of valves shall be made of stainless steel containing not less than 11 percent chromium. Mercury, silver, aluminum, magnesium, copper, and their alloys shall not be used for any valves, gages, thermometers, or any similar devices. Gaskets shall be constructed of spirally wound stainless steel with "Teflon" or other suitable material. All packing and gaskets shall be constructed of materials which do not react spontaneously with or lower the autoignition temperature of the alkylene oxides.

(e) The pressure rating of valves, fittings, and accessories shall be not less than the maximum pressure for which the cargo tank is designed or the shut-off head of the cargo pump, whichever is greater, but in no case less than 150 pounds per square inch. Welded fittings manufactured in accordance with A.N.S.I. Standards shall be used wherever possible, and the number of pipe joints shall be held to a minimum. Threaded joints in the cargo liquid and vapor lines are prohibited.

(f) The thermometer shall terminate in the liquid space and shall be attached to the shell by welding with the end of the fitting being provided with a gastight screwed plug or bolted cover.

(g) Automatic float continuous reading tape gage, and similar types, shall be fitted with a shutoff valve located as close to the tank as practicable, which shall be designed to close automatically in the event of fracture of the external

gaging piping. An auxiliary gaging device shall always be used in conjunction with an automatic gaging device.

(h) Filling and discharge piping shall extend to within 4 inches of the bottom of the tank or sump pit if one is provided.

(i) Venting:

(1) The discharge fittings from each safety relief or pressure vacuum relief valve shall be directed in such a manner as to not impinge on another tank, piping or any other equipment which would increase the fire hazard should burning products be discharged from the safety or pressure vacuum relief valve as a result of a fire or other casualty. In addition, the discharges shall be directed away from areas where it is likely that persons might be working and as remote as practicable from ventilation inlets and ignition sources. A common discharge header may be employed if desired. The area near the discharge fittings shall be clearly marked as a hazardous area.

(2) A means shall be provided for either the reclamation or safe venting of vapors during the loading and unloading operations. For this purpose, the safety relief or pressure vacuum relief valve shall be provided with a valved bypass to a vapor return line shore connection which shall be used whenever vapor return shore facilities are available. In the event vapors must be vented to the atmosphere, a vent riser shall be connected to the vapor return line and extend at least 12 feet above the highest level accessible to personnel. The vent riser may be collapsible for ease of stowage when not in use. The vent riser shall not be connected to a safety relief or pressure vacuum valve. Vapor return lines or vent risers for tanks carrying the same class product may be connected to a common header system if desired. Tanks carrying alkylene oxides shall be vented independent of tanks carrying other products.

(3) The outlet of each vent riser shall be fitted with acceptable corrosion-resistant flame screen of suitable material or a flame arrester suitable for use with alkylene oxide.

(j) Ventilation:

(1) All enclosed spaces within the hull shall be vented or ventilated in accordance with the provisions of this subchapter except as otherwise provided for in this subpart.

(2) The enclosed spaces in which the cargo tanks are located shall be inerted by injection of a suitable inert gas or shall be well ventilated.

(3) The enclosed spaces in which the cargo tanks are located, if an inerting system is not installed, shall be fitted with forced ventilation of such capacity to provide a complete change of air every three minutes and arranged in such a manner that any vapors lost into the space will be removed. The ventilation system shall be in operation at all times cargo is being loaded or discharged. No electrical equipment shall be fitted within the spaces or within ten feet of the ventilation exhaust from these spaces.

(4) All ventilation machinery shall be of nonsparking construction and shall not provide a source of vapor ignition

(5) Each vent shall be fitted with a flame screen of corrosion resistant wire which is suitable for use with the alkylene oxide.

(k) (1) Flexible metal hose fabricated of stainless steel or other acceptable material, resistant to the action of the alkylene oxide, shall be fitted to the liquid and vapor lines during cargo transfer.

(2) The hose shall be marked with the maximum pressure guaranteed by the manufacturer, and with his certification with the words "Certified for ----- Oxide."

(3) Cargo hose intended for alkylene oxide service shall not be used for any other products except those which are compatible with the alkylene oxide.

(l) Vessel shall be electrically bonded to the shore piping prior to connecting the cargo hose. This electrical bonding shall be maintained until after the cargo hose has been disconnected and any spillage has been removed.

(m) Cargo shall be discharged by pumping or by displacement with nitrogen or other acceptable inert gas. In no case shall air be allowed to enter the system. During loading and unloading operations, the vapor shall not be discharged to the atmosphere. Provisions shall be made to return all displaced vapor to the loading facility. The loading rate and the pressure applied to the tank to discharge the cargo shall be so limited to prevent opening the safety relief valves.

(n) During cargo transfer, a water hose with pressure to the nozzle, when atmospheric temperatures permit, shall be connected to a water supply for immediate use during filling and discharge operations and any spillage of alkylene oxide shall be immediately washed away. This requirement can be met by facilities provided from shore.

(o) Prior to disconnecting shore lines, the pressure in the liquid and vapor lines shall be relieved through suitable valves installed at the loading header. The liquid and vapor discharged from these lines shall not be discharged to atmosphere.

(p) A hydrostatic test of $1\frac{1}{2}$ times the design pressure shall be made on the cargo tanks at least once in each 4 years at the time the internal examination is made and at such other times as considered necessary by the Officer in Charge, Marine Inspection.

(q) The safety relief valves shall be tested by liquid, gas, or vapor pressure at least once every 2 years to determine the accuracy of adjustment and, if necessary, shall be reset. Alkylene oxides shall not be used as the testing medium.

(r) The special requirements for ethylene oxide contained in § 151.50-12 and for propylene oxide contained in § 151.50-13 shall also be observed.

§ 151.50-12 Ethylene oxide.

(a) (1) Ethylene oxide shall be carried in fixed, independent, pressure vessel type cargo tanks, designed, constructed, arranged and, if necessary, equipped with machinery to maintain the cargo temperature below 90° F. except as otherwise provided for in subparagraph (3) of this paragraph.

(2) Ethylene oxide shall be loaded at a temperature below 70° F.

(3) When ethylene oxide is to be transported at or near atmospheric pressure, the Commandant may permit the use of alternate methods of storage which are consistent with the minimum requirements of this subpart.

(b) (1) All cargo tanks shall be constructed of a carbon steel or stainless steel acceptable to the Commandant. Impurities of copper, magnesium and other acetylide-forming metals shall be kept to a minimum. The chemical composition of all steel used shall be submitted to the Commandant for approval prior to fabrication. Aluminum, copper and other acetylide-forming metals, such as silver, mercury, magnesium, and their alloys shall not be used as materials of construction for tanks or equipment used in handling ethylene oxide.

(2) Cargo tanks shall meet the requirements of Class I pressure vessels.

(3) Cargo tanks shall be designed for the maximum pressure of vapor or gas used in discharging the cargo but in no case shall the design pressure of such tanks be less than 75 pounds per square inch gage. The tank shell and heads shall not be less than $\frac{3}{16}$ -inch thick.

(c) (1) Cargo tanks shall be located below deck in holds or enclosed spaces with the domes or trunks extended above the weather deck and terminating in the open. Provisions shall be made to maintain the watertightness of the deck by means of watertight seals around such domes or trunks. The holds or enclosed spaces, in which the ethylene oxide tanks are located, shall not be used for any other purpose. However, in open hopper type barges of a suitable design approved for such service, the weatherdeck may not be required to be watertight.

(2) All cargo tanks shall be installed with the manhole openings and all tank connections located above the weather deck in the open.

(3) Tanks shall be electrically bonded to the hull.

(4) No welding of any kind shall be done on cargo tanks or supporting structure unless authorized by the Commandant.

(d) All cargo tanks, piping, valves, fittings, and similar equipment which may contain ethylene oxide in either the liquid or vapor phase, including the vent risers, shall be insulated. Flanges need not be covered, but if covered, a small opening shall be left at the bottom of the flange cover to detect leaks. Insulation shall be of an approved incombustible material suitable for use with ethylene oxide, which does not significantly lower the autoignition temperature and which does not react spontaneously with ethylene oxide. The insulation shall be of such thickness as to provide a thermal conductance of not more than 0.075 B.t.u. per square foot per degree Fahrenheit differential in temperature per hour.

(e) (1) When cooling systems are installed to maintain the temperature of the liquid below 90° F., at least two complete cooling plants, automatically regulated by temperature variations within the tanks shall be provided; each to be complete with the necessary auxiliaries

for proper operation. The control system shall also be capable of being manually operated. An alarm shall be provided to indicate malfunctioning of the temperature controls. The capacity of each cooling system shall be sufficient to maintain the temperature of the liquid cargo at or below the design temperature of the system.

(2) An alternate arrangement may consist of three cooling plants, any two of which shall be sufficient to maintain the temperature of the liquid cargo at or below the design temperature of the system.

(3) Cooling systems requiring compression of ethylene oxide are prohibited.

(f) In addition to the shutoff valve required, all tank connections larger than one-half inch inside pipe size, except safety relief valves and liquid level gaging devices, shall be fitted with either internal back pressure check valves or internal excess flow valves in conjunction with a quick closing stop valve operable from at least two remote locations. The quick closing stop valve shall be of the "fail safe" type acceptable to the Commandant and shall be equipped with a fusible plug designed to melt between 208° F. and 220° F., which will cause the quick closing valve to close automatically in case of fire. The quick closing valve shall be located as close to the tank as possible.

(g) Piping systems intended for ethylene oxide service shall not be used for any other product and shall be completely separate from all other systems. The piping system shall be designed so that no cross connections may be made either through accident or design.

(h) Each safety relief valve shall be set to start to discharge at not less than 75 pounds per square inch gage, nor more than the design pressure of the tank.

(i) The filling density shall not exceed 83 percent.

(j) (1) The cargo shall be shipped under a suitable protective inerting gas system, such as nitrogen. When nitrogen gas is used, the gas inerting system shall be so designed that the vapor space above the liquid cargo will be filled and maintained with a gas mixture of not less than 45 percent nitrogen. Other gases proposed for inerting use may be given consideration by the Commandant. Original charging only of protective inerting gas at the loading facility is not considered adequate. A sufficient amount of spare inerting gas as approved by the Commandant shall be provided on the vessel in order to maintain the proper concentration of the gas in the event of normal leakage or other losses.

(2) Any inerting gas selected should be at least 98 percent pure and free of reactive materials, such as ammonia, hydrogen sulfide, sulfur compounds, and acetylene.

(k) Prior to loading, a sample from the cargo tank will be taken to insure that the pad gas will meet the requirements of paragraph (j) of this section and that the oxygen content of the vapor space will be not more than 2 percent maximum. If necessary, a sample will

be taken after loading to insure the vapor space meets this requirement.

(l) The cargo piping shall be inspected and tested at least once in each 2 calendar years.

(m) In those cases where the cargo transfer hose used is not part of the barge's equipment, the person in charge of the transfer operation shall determine that the provisions of §151.50-10(k) have been met before using this hose. A certificate of test, supplied by the transfer facility, will be considered as adequate for this determination.

(n) The provisions of §151.50-10 shall be complied with as a requirement for shipping ethylene oxide.

§ 151.50-13 Propylene oxide.

(a) (1) Pressure vessel cargo tanks shall meet the requirements of Class II pressure vessels.

(2) Cargo tanks shall be designed for the maximum pressure expected to be encountered during loading, storing and discharging the cargo but in no case shall the design pressure of pressure vessel tanks be less than thirty (30) pounds per square inch gage. The tank shell and heads shall not be less than 3/16-inch thick.

(b) When propylene oxide is carried on board a vessel, piping systems in propylene oxide service shall not be used for any other product and shall be completely separate from all other systems. The piping system shall be designed so that no cross connection may be made through inadvertence.

(c) Each safety relief valve shall be set to start to discharge at not less than 30 pounds per square inch gage, nor more than the design pressure of the tank.

(d) Filling density shall not exceed 80 percent.

(e) (1) The cargo shall be shipped under a suitable protective padding, such as nitrogen gas. Other gases proposed for use as padding may be given consideration by the Commandant. Original charging only of protective gas padding at the loading facility is not considered adequate. A sufficient amount of spare padding gas as approved by the Commandant shall be provided on the vessel in order to maintain the proper concentration of the gas in the event of normal leakage or other losses.

(2) Any padding gas selected should be at least 98 percent pure and free of reactive materials.

(f) Prior to loading, a sample from the cargo tank will be taken to insure that the pad gas will meet the requirements of paragraph (e) of this section and that the oxygen content of the vapor space will be not more than 2 percent maximum. If necessary, a sample will be taken after loading to insure the vapor space meets this requirement.

(g) The cargo piping shall be subjected to a hydrostatic test of 1½ times the maximum pressure to which they may be subjected in service.

(h) The Commandant may permit the transportation of propylene oxide in other than pressure vessel type tanks if it is shown to his satisfaction that a de-

gree of safety is obtained consistent with the minimum requirements of this subpart.

(i) The provisions of §151.50-10 shall be complied with as a requirement for shipping propylene oxide.

§ 151.50-20 Inorganic acids.

(a) (1) Gravity type cargo tanks shall be designed and tested to meet the rules of the American Bureau of Shipping for a head of water at least 8 feet above the tank top or the highest level the lading may rise, whichever is the greater. The plate thickness of any part of the tank shall not be less than three-eighths inch.

(2) Gravity tank vents.

(i) The outlet end of the gravity tank vent shall terminate above the weather-deck, clear of all obstructions and away from any source of ignition.

(ii) The gravity tank vent shall terminate in a gooseneck bend and shall be fitted with a single flame screen or two fitted flame screens as described in §151.03-25. No shutoff valve or frangible disk shall be fitted in the vent lines.

(b) (1) Pressure vessel type cargo tanks shall be independent of the vessel's structure and shall be designed for the maximum pressure to which they may be subjected when compressed air is used to discharge the cargo, but in no case shall the design pressure be less than that indicated as follows:

Hydrochloric Acid—50 pounds per square inch gage.

Phosphoric Acid—30 pounds per square inch gage.

Sulfuric Acid—50 pounds per square inch gage.

(2) Pressure vessel type cargo tanks shall be of welded construction meeting the requirements for Class II or Class III given in Part 54 of this chapter.

(3) When compressed air is used to discharge the cargo, the tank shall be fitted with a vent led to the atmosphere in which a rupture disk shall be installed. The rupture disk shall be designed to burst at a pressure not exceeding the design pressure of the tank. An auxiliary vent to relieve the pressure or vacuum in the tank during the cargo transfer operation may be led from the vent line between the tank and the rupture disk. A shutoff valve may be fitted in the auxiliary vent.

(c) Openings in tanks are prohibited below deck, except for access openings used for inspection and maintenance of tanks, or unless otherwise specifically approved by the Commandant. Openings shall be fitted with bolted cover plates and acid-resistant gaskets.

(d) Where special arrangements are approved by the Commandant to permit a pump suction to be led from the bottom of the tank, the filling and discharge lines shall be fitted with shutoff valves located above the weatherdeck or operable therefrom.

(e) The outage shall not be less than 1 percent.

(f) All enclosed compartments containing cargo tanks and all machinery spaces containing cargo pumps shall be

fitted with effective means of ventilation.

(g) A separator shall be fitted in compressed air lines to the tank when air pressure is used to discharge the cargo.

(h) Only installed electric or portable battery lights shall be used during the cargo transfer operations. Smoking is prohibited and the person in charge of cargo transfer shall post No Smoking signs during cargo transfer operations.

(i) Tanks approved for the transportation of acid cargoes subject to this section shall not be used for the transportation of any other commodity, except upon authorization by the Commandant (MHM).

(j) Each cargo tank shall be subjected to an internal examination at least once in every 4 years. If cargo tank lining is required and the lining of the cargo tank has deteriorated in service or is not in place, the Marine Inspector may require the tank to be tested by such nondestructive means as he may consider necessary to determine its condition.

(k) The special requirements for sulfuric acid contained in § 151.50-21, for hydrochloric acid contained in § 151.50-22 and for phosphoric acid contained in § 151.50-23 shall also be observed.

§ 151.50-21 Sulfuric acid.

(a) How sulfuric acid may be carried:

(1) Sulfuric acid of concentration of 77.5 percent (1.7019 specific gravity) (59.8° Baume) or greater concentrations with or without an inhibitor, provided the corrosive effect on steel measured at 100° F. is not greater than that of 66° Baume commercial sulfuric acid, may be transported in unlined gravity type cargo tanks or unlined pressure vessel type cargo tanks.

(2) Sulfuric acid of concentration of 65.25 percent (1.559 specific gravity) (52° Baume) or greater concentrations, provided the corrosive effect on steel measured at 100° F. is not greater than that of 52° Baume commercial sulfuric acid, may be transported in unlined pressure vessel type cargo tanks independent of the vessel's structure.

(3) Sulfuric acid of concentration not to exceed 65.25 percent (1.559 specific gravity) (52° Baume) may be transported in gravity type cargo tanks or pressure-vessel type cargo tanks which are lined with lead or other equally suitable acid-resistant material acceptable to the Commandant.

(4) Sulfuric acid of concentration not to exceed 51 percent (1.408 specific gravity) (42° Baume) and spent sulfuric acid resulting from the use of sulfuric acid in industrial processes may be transported in gravity type cargo tanks which are lined with rubber or other equally suitable acid-resistant material acceptable to the Commandant. See § 151.15-3(f)(2).

(5) Spent or sludge sulfuric acid resulting from the use of sulfuric acid in industrial processes may be transported in unlined gravity type cargo tanks or unlined pressure vessel type cargo tanks, provided the corrosive effect on steel is not greater than that of commercial sulfuric acid as prescribed in subparagraph (1) of this paragraph.

(b) Heating coils will be the only acceptable means of liquefying frozen or congealed sulfuric acid.

(c) During cargo transfer, a water hose shall be connected to a water supply ready for immediate use and any leakage or spillage of acid shall be immediately washed down. This requirement can be met by facilities provided from shore.

(d) The requirements of § 151.50-20 are also applicable to the shipment of sulfuric acid.

§ 151.50-22 Hydrochloric acid.

(a) Hydrochloric acid shall be carried in gravity or pressure type cargo tanks which are independent of the vessel's structure provided such tanks are lined with rubber or other equally suitable material acceptable to the Commandant. See § 151.15-3(f)(2).

(b) Notwithstanding the provisions of § 151.50-20(b)(3), compressed air may be used to discharge hydrochloric acid from gravity type cargo tanks only if the tanks are of cylindrical shape with dished heads, provided the air pressure does not exceed the design pressure of the tank but in no case shall it exceed 10 pounds per square inch gage. Such tanks shall be fitted with pressure relief devices and need not be vented to the atmosphere as required by § 151.50-20(b)(3).

(c) During cargo transfer, a water hose shall be connected to a water supply and be ready for immediate use. Any leakage or spillage of acid shall be immediately washed down. This requirement can be met by facilities provided from shore.

(d) Spent hydrochloric acid or hydrochloric acid adulterated by other chemicals, inhibitors, oils, solvents, water, etc., shall not be transported in bulk except upon authorization by the Commandant (MHM).

(e) The requirements of § 151.50-20 are also applicable to the shipment of hydrochloric acid.

§ 151.50-23 Phosphoric acid.

(a) The term "phosphoric acid" as used in this subpart shall include, in addition to phosphoric acid, aqueous solutions of phosphoric acid, and super phosphoric acid.

(b) Phosphoric acid may be carried in either gravity or pressure type cargo tanks. The tanks shall be rubber-lined, or lined or clad with other suitable material acceptable to the Commandant, or shall be fabricated of a phosphoric acid resistant stainless steel. See § 151.15-3(f)(2).

(c) The vessel's shell plating shall not be used as any part of the boundaries of gravity type cargo tanks.

(d) Cargo piping, including valves, fittings, and flanges where exposed to the acid, shall be rubber-lined, or lined, coated or clad with other corrosion-resistant material, or shall be fabricated of a phosphoric acid resistant stainless steel. Vent piping, including flanges and fittings, shall be similarly protected at least to the height of the frangible disk if such is installed.

(e) Phosphoric acid adulterated by other chemicals, inhibitors, oils, solvents,

etc., shall not be transported in bulk cargo tanks except upon authorization by the Commandant (MHM).

(f) The requirements of § 151.50-20 are also applicable to the shipment of phosphoric acid.

§ 151.50-24 Hydrofluoric acid. [Reserved]

§ 151.50-30 Compressed gases.

(a) All tank inlet and outlet connections, except safety relief valves, liquid level gaging devices, and pressure gages shall be marked to designate whether they terminate in the vapor or liquid space. Labels, when used, shall be of corrosion-resistant materials and may be attached to valves.

(b) Venting:

(1) Except as provided in subparagraph (2) of this paragraph, each safety relief valve installed on a cargo tank shall be connected to a branch vent of a venting system which shall be constructed so that the discharge of gas will be directed vertically upward to a point at least 10 feet above the weatherdeck or the top of any tank or house located above the weatherdeck.

(2) Safety valves on cargo tanks in barges may be connected to individual or common risers which shall extend to a reasonable height above the deck. Where the escape of vapors from the venting system may interfere with towing operations, the installation shall be acceptable to the Commandant, and the arrangement shall be such as to minimize the hazard of escaping vapors. Arrangements specially provided for venting cargo tanks forming part of the hull on unmanned barges will be given special consideration by the Commandant.

(3) The capacity of branch vents or vent headers shall depend upon the number of cargo tanks connected to such branch or header as provided in Table 151.50-30(b)(3).

TABLE 151.50-30(b)(3)—CAPACITY OF BRANCH VENTS OR VENT HEADERS

Number of cargo tanks:	Percent of total value discharge
1 or 2.....	100
3.....	90
4.....	80
5.....	70
6 or more.....	60

(4) Return bends and restrictive pipe fittings are prohibited. Vents and headers shall be so installed as to minimize stresses on safety relief valves and their mounting nozzles.

(5) When vent discharge risers are installed, they shall be so located as to protect against physical damage and be fitted with loose raincaps.

(6) When vent discharge risers are installed and their installation in accordance with the provisions of this paragraph results in restrictions in the operation of the barge due to navigation clearances, the vents may be designed so as to be collapsible when passing under such low clearance obstacles.

(c) Repairs involving welding or burning:

(1) Repairs involving welding or burning shall not be undertaken on the cargo tanks or piping while cargo in either the liquid or vapor state is present therein.

(2) Repairs involving welding or burning on parts of the barge other than cargo tanks or piping may be undertaken provided positive pressure is maintained in the tanks or the tanks have been vented or washed internally.

(d) Respiratory equipment:

(1) At least one approved self-contained breathing apparatus shall be available in a readily accessible location off the barge at all times during the cargo transfer operations. This equipment shall not be considered to be part of the barge equipment, and the barge shall not be required to carry this equipment en route.

(2) The approved self-contained breathing apparatus, masks, and all respiratory protective devices shall be of types suitable for starting and operating at the temperatures encountered, and shall be maintained in good operating condition.

(3) Personnel involved in the cargo transfer operations shall be adequately trained in the use of the respiratory equipment.

(e) Filling densities and container design pressure. For compressed gases transported at or near ambient temperatures, the maximum filling densities and minimum design pressure of container as indicated in Table 151.50-30(e) shall apply. Deviations from the tabulated values shall be submitted to the Commandant for approval. Where cargo is to be carried at temperatures below ambient, the tank shall be designed in accordance with § 151.15-3(b)(3) and the maximum amount of cargo shall be in accordance with § 151.45-6(b).

TABLE 151.50-30(e)—FILLING DENSITIES AND CONTAINER DESIGN PRESSURES

Kind of gas	Maximum permitted filling density (percent by weight, see § 151.03-21)		Minimum design pressure of tank (pounds per square inch gage)	
	Uninsulated tanks	Insulated tanks	Uninsulated tanks	Insulated tanks
Ammonia, anhydrous	57	58	250	215
Chlorine	125	125	300	300
Dichlorodifluoromethane	123	125	147	127
Dimethylamine	61	62	46	36
Hydrogen chloride	62	68	1070	955
Methyl chloride	85	87	131	112
Monochlorodifluoromethane	110	113	243	211
Vinyl chloride	86	87	81	67

(f) The shell and head thickness of liquefied compressed cargo tanks shall not be less than five-sixteenths inch.

(g) The special requirements for chlorine, contained in § 151.50-31, anhydrous ammonia, contained in § 151.50-32, anhydrous hydrogen chloride, contained in § 151.50-33, and vinyl chloride, contained in § 151.50-34, are also applicable.

§ 151.50-31 Chlorine.

(a) Chlorine barges: Subparts 98.03 and 98.20 of Part 98 of this chapter have been revoked. However, chlorine barges that were certified in accordance with the requirements of Subpart 98.20 of Part 98 of this chapter and having hulls modified, if necessary, to comply with §§ 98.03-5(c) and 98.03-25(c) of this chapter, shall be considered as complying with this part.

(b) Design and construction of cargo tanks:

(1) The cargo tanks shall meet the requirements of Class I pressure vessels.

(2) Tanks shall be designed for a pressure of not less than 300 pounds per square inch gage. For the maximum allowable working pressure of tanks in service, see paragraph (q) of this section.

(3) Each tank shall be provided with one or more 24-inch inside diameter manhole, fitted with a cover located above the maximum liquid level and as close as possible to the top of the tank. There shall be no other openings in the tank.

(c) Tanks may be installed "on deck" or "under deck" with the tank protruding above deck. If a portion of the tank extends above the weatherdeck, provision shall be made to maintain the weathertightness on the deck. All tanks shall be installed with the manhole opening located above the weatherdeck. Hopper type barges operating on protected inland waters may have tanks located in the hopper space.

(d) All valves, flanges, fittings and accessory equipment shall be of a type suitable for use with chlorine and shall be made of metal, corrosion-resistant to chlorine in either the gas or liquid phase. Cast or malleable iron shall not be used. Valves, flanges, and flanged joints shall be 300 pounds A.N.S.I. standard minimum with tongue and groove or raised face. Joints shall be fitted with sheet lead or other suitable gasket material. Welded fittings shall be used wherever possible and the number of pipe joints held to a minimum. Threaded joints in cargo lines and vapor lines shall not be used in sizes above 1 inch internal diameter. Welded "hammerlock" unions or other unions approved by the Commandant may be used at terminal points of fixed barge piping.

(e) Each tank shall be provided with liquid and vapor connections fitted with manually operated shutoff valves and with safety relief valves. All valves shall be bolted to the cover or covers specified in paragraph (b)(3) of this section and shall be protected against mechanical damage by a suitable protective metal housing. A drain connection shall be provided from the protective housing.

(f) All liquid and vapor connections, except safety relief valves, shall be fitted with automatic excess flow valves, which shall be located on the inside of the tank. Bypass openings are not permitted in excess flow valves.

(g) Chlorine barge cargo piping shall not be fitted with the nonreturn valves specified by § 151.20-20(b).

(h) Liquid level gaging devices of any type are prohibited on chlorine tanks.

(i) A pressure gage shall be attached to the vapor shutoff valve or vapor line so as to indicate the pressure in the tank at all times during loading and unloading.

(j) Piping including connections between tank valves and fixed barge piping, shall be of a thickness of not less than Schedule 80.

(k) In multiple tank installations the tanks shall not be interconnected by piping or manifolds which may contain liquid chlorine. Manifolding of vapor lines of individual tanks into a common header for connection to shore is permitted. More than one cargo tank may be filled or discharged at a time, provided each tank is filled from or discharged to shore tanks through separate lines.

(l) Connections between fixed barge piping and shore piping shall be fabricated from one of the following:

(1) Schedule 80 seamless pipe, having flexible metallic joints.

(2) Corrosion-resistant metallic pipe (equivalent to Schedule 80) not subject to deterioration by chlorine, having flexible metallic joints.

(3) Flexible metallic hose acceptable to the Commandant. If subparagraphs (1) or (2) of this paragraph are used, the flexible metallic joints shall meet the requirements for cargo hose. See § 151.04-5(h).

(m) Safety relief valves shall discharge into the protective housing surrounding the valves. Suitable provisions shall be made to vent the housing. The arrangement shall be such as to minimize the hazard of escaping vapors.

(n) Cargo transfer operations:

(1) The amount of chlorine loaded into each cargo tank shall be determined by weight. Draft marks shall not be used as a means of weighing. Any chlorine vapors vented during the filling operation shall be disregarded when calculating the maximum amount of chlorine to be loaded into the cargo tanks.

(2) Prior to the start of filling operations, care shall be exercised to insure that the cargo tanks are empty, dry, and free from foreign matter.

(3) After the filling operation is completed, the vapor in each cargo tank shall be analyzed to determine the percentage of gaseous chlorine in the vapor space. If it should contain less than 80 percent chlorine by volume, vapors shall be withdrawn through the vent or vapor line until the vapor in the cargo tanks contains at least 80 percent chlorine by volume.

(4) After filling connections are removed, upon completion of the loading of a cargo tank, all connections at the tank shall be tested for leakage of chlorine by the aqua ammonia method.

(5) The chlorine in the cargo tanks shall be discharged by the pressure differential method. If the vapor pressure of the chlorine is not sufficient to force the liquid out of the tank, compressed air, or other nonreactive gas, may be used to secure the desired rate of discharge, provided the air or gas is oil-free and thoroughly dried by passing it over

activated aluminum oxide, silica gel, or other acceptable drying agent, and provided the supply pressure is limited to 75 percent of maximum allowable pressure of chlorine tanks.

(6) After completion of cargo transfer, any liquid chlorine in the cargo piping shall be removed and cargo transfer piping shall be disconnected at the cargo tanks. After disconnecting the cargo piping, both ends of the line shall be closed and all inlet and outlet valves on the tank shall be plugged or fitted with blind flanges.

(o) During cargo transfer, every person on the barge shall carry on his person a respiratory protective device which will protect the wearer against chlorine vapors and will provide respiratory protection for emergency escape from a contaminated area resulting from cargo leakage. This respiratory protective equipment shall be of such size and weight that the person wearing it will not be restricted in movement or in the wearing of a lifesaving device.

(p) Each cargo tank shall be subjected to biennial hydrostatic test of $1\frac{1}{2}$ times the maximum allowable pressure as determined by the safety relief valve setting.

(q) When periodic inspection indicates that a cargo tank has deteriorated in service, the maximum allowable pressure shall be recalculated, using the minimum thickness found by actual measurement. The recalculated maximum allowable pressure shall be not less than 275 pounds per square inch gage. If the recalculated maximum allowable pressure is less than 275 pounds per square inch gage, the cargo tanks shall be withdrawn from service.

(r) The following substances shall not be carried as stores on board barges transporting chlorine in bulk: hydrogen, methane, liquefied petroleum gases, coal gas, acetylene, ammonia, turpentine, compounds containing metallic powders, finely divided metals or finely divided organic materials.

(s) The requirements of § 151.50-30 for compressed gases are also applicable to the shipment of chlorine.

§ 151.50-32 Anhydrous ammonia.

(a) The anhydrous ammonia tanks may be installed in the bulk liquid cargo tanks provided the liquid surrounding the enclosed anhydrous ammonia tanks complies with the following chemical and physical properties:

(1) Boiling point above 125° F. at atmospheric pressure.

(2) Inert to ammonia at 100° F. at atmospheric pressure.

(3) Noncorrosive in the liquid and vapor phase to the ammonia tanks and piping.

(b) Copper, copper alloys, and copper bearing alloys shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with anhydrous ammonia liquid or vapor.

(c) Valves, flanges and pipe fittings shall be of the tongue and groove or raised-face type, fitted with suitable gasket material. Welded fittings shall

be used wherever possible and the number of pipe joints shall be held to a minimum. Threaded joints are not permitted for pipe diameters exceeding 2 inches. Braze joints are prohibited.

(d) All enclosed spaces containing cargo tanks fitted with bottom outlet connections shall be provided with mechanical ventilation of sufficient capacity to assure a change of air every 3 minutes.

(e) Each cargo tank shall be electrically grounded to the hull.

(f) When transferring cargo, a hose shall be connected to a water supply so that if leakage of anhydrous ammonia occurs the vapor may be dispersed by the use of water fog. This requirement can be met by facilities provided from shore.

(g) During cargo transfer operations, every person on the vessel shall carry on his person or have close at hand at all times a canister mask approved for ammonia or each person shall carry on his person a respiratory protective device which will protect the wearer against ammonia vapors and will provide respiratory protection for emergency escape from a contaminated area resulting from cargo leakage. This respiratory protective equipment shall be of such size and weight that the person wearing it will not be restricted in movement or in the wearing of a lifesaving device.

(h) To the extent he deems it necessary, the Officer in Charge, Marine Inspection, may require that sufficient insulation shall be removed from insulated tanks at least once in each 8 calendar years to permit spot external examination of the tanks and insulation in accordance with § 151.04-5(c).

(i) The requirements of § 151.50-30 for compressed gases are also applicable to the shipment of anhydrous ammonia.

§ 151.50-33 Anhydrous hydrogen chloride. [Reserved]

§ 151.50-34 Vinyl chloride.

(a) Copper, aluminum, magnesium, mercury, silver, and their alloys shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with vinyl chloride liquid or vapor.

(b) Valves, flanges, and pipe fittings shall be of the tongue and groove or raised-face type, fitted with suitable gasket material. Welded fittings shall be used wherever possible and the number of pipe joints shall be held to a minimum. Threaded joints are not permitted for pipe diameters exceeding 2 inches. Braze joints are prohibited.

(c) Each cargo tank shall be electrically grounded to the hull.

(d) The vessel shall be electrically bonded to the shore piping prior to connecting the cargo hose. This electrical bonding shall be maintained until after the cargo hose has been disconnected and any spillage has been removed.

(e) To the extent he deems it necessary, the Officer in Charge, Marine Inspection, may require that sufficient insulation shall be removed from insulated tanks at least once in each 8

calendar years to permit spot external examination of the tanks and insulation in accordance with § 151.04-5(c).

(f) The requirements of § 151.50-30 for compressed gases are also applicable to the shipment of vinyl chloride.

§ 151.50-40 Additional requirements for carbon bisulfide and ethyl ether.

(a) The provisions of this section are applicable if specifically referenced in the Special Requirements column of Table 151.05.

(b) Cargo tanks shall be electrically bonded to the hull of the vessel. A vessel shall be electrically bonded to the shore piping prior to connecting the cargo hose. This electrical bonding shall be maintained until after the cargo hose has been disconnected and any spillage has been removed.

(c) Pumps may be used for discharging cargo: *Provided*, That they are the vertical submerged type designed to avoid liquid pressure against the shaft gland and are suitable for use with the cargo.

(d) Provisions shall be made to maintain an inert gas padding in the cargo tank during loading, unloading and during transit.

(e) Provisions shall be made to prevent any leakage being washed into the waterways at the loading and unloading points.

(f) The special requirements of § 151.50-41 for carbon bisulfide and § 151.50-42 for ethyl ether shall also be observed.

§ 151.50-41 Carbon bisulfide.

(a) All openings shall be in the top of the tank.

(b) Loading lines shall terminate near the bottom of the tank.

(c) A standard ullage opening shall be provided for secondary and emergency sounding.

(d) If a cargo discharge pump is used, it shall be inserted through a cylindrical well extending from the tank top to a point near the tank bottom. A blanket of water shall be formed in this well before attempting pump removal.

(e) Water or inert gas displacement may be used for discharging cargo provided the cargo system is designed for the expected pressure and temperature. This method for discharging may be used with pressure type tanks only.

(f) Adequate natural ventilation shall be provided for the voids around the cargo tanks while the vessel is under way. During loading and unloading, forced ventilation shall be used. The forced ventilation shall be of sufficient capacity to provide a complete change of air within each void space every 5 minutes. The ventilating fan shall be of nonsparking construction.

(g) Because of its low ignition temperature and the close clearances required to arrest its flame propagation, carbon bisulfide requires safeguards beyond those required for any electrical hazard groups.

(h) The requirements of § 151.50-40 are also applicable to the shipment of carbon bisulfide.

§ 151.50-42 Ethyl ether.

(a) (1) Gravity tanks shall be designed and tested to meet the rules of the American Bureau of Shipping for a head of water at least 8 feet above the tank top or the highest level the lading may rise, whichever is greater. All openings shall be in the top of the tank.

(2) Pressure vessel type tanks shall be designed for the maximum pressure to which they may be subjected when pressure is used to discharge the cargo, but in no case shall the design pressure be less than 50 pounds per square inch gage. All openings shall be in the top of the tank.

(b) Adequate natural ventilation shall be provided for the voids around the cargo tanks while the vessel is underway. If a power ventilation system is installed, all blowers shall be of nonsparking construction. Power driven ventilation equipment shall not be located in the void spaces surrounding the cargo tanks.

(c) Pressure relief valve settings shall not be less than 3 pounds per square inch gage for gravity tanks. For pressure vessels, the relief valve setting shall not exceed the design pressure of the tank.

(d) Inert gas displacement may be used for discharging cargo from pressure vessel tanks provided the cargo system is designed for the expected pressure and the discharge pressure does not exceed 50 pounds per square inch gage or the design pressure of the tank, whichever is less.

(e) No electrical equipment except for approved lighting fixtures shall be installed in enclosed spaces adjacent to the cargo tanks. Lighting fixtures must be approved for use in Class 1, Group C, hazardous locations. The installation of electrical equipment on the weather deck shall comply with the requirements of § 111.70-10(c) (4) of this chapter.

(f) Copper, silver, mercury and magnesium or other acetylide forming metals and their alloys shall not be used as materials of construction for tanks, pipelines, valves, fittings and other items of equipment that may come in contact with the cargo vapor or liquid.

(g) Precautions shall be taken to prevent the contamination of ethyl ether by strong oxidizing agents.

(h) The requirements of § 151.50-40 are also applicable to the shipment of ethyl ether.

§ 151.50-50 Elemental phosphorus in water.

(a) Tanks shall be designed and tested for a head equivalent to the design lading of phosphorus and its water blanket extended to 8 feet above the tank top. In addition, tank design calculations shall demonstrate that the tank can withstand, without rupture, a single loading to the highest level to which the water blanket may rise, if that exceeds 8 feet. Tanks shall not be less than $\frac{5}{16}$ -inch thick.

(b) When a water displacement method of discharge is used, pressure vessel type cargo tanks, designed and tested in accordance with Subchapter F of this chapter shall be employed. Such tanks shall be designed for the maximum pres-

sure to which they may be subjected when water pressure is used to discharge the cargo.

(c) Each cargo tank shall be fitted with an approved pressure vacuum relief valve set to discharge at a pressure not exceeding 2 pounds per square inch. When transferring cargo, the vent discharge shall lead overboard above the waterline. When pressure vessel type tanks are used, each tank shall be fitted with a relief valve of suitable size.

(d) Sufficient outage shall be provided to prevent the tank from being liquid full at any time, but in no case shall the outage be less than 1 percent. When pressure vessel type tanks are used, outage need not be provided.

(e) The use of compressed air to discharge cargo is prohibited.

(f) Cargo shall be loaded at a temperature not exceeding 140° F., and then cooled until the water above the cargo has a temperature not exceeding 105° F. prior to the movement of the vessel. Upon presentation of satisfactory proof that procedures followed will provide adequate safety in transportation and handling, the Commandant may authorize movement of the vessel following cooling of the water above the cargo to a temperature exceeding 105° F.

(g) Coils in which steam or hot water is circulated to heat the cargo so that it may be pumped shall be located outside the cargo tanks.

(h) A fixed ballast piping system (including a power driven pump of ample capacity), or other means acceptable to the Commandant shall be installed so that any void space surrounding the tanks may be flooded.

(i) All openings shall be in the top of the tank and shall be fitted with bolted cover plates and gaskets resistant to the attack of phosphorus pentoxide.

(j) All enclosed compartments containing cargo tanks shall be provided with effective means of ventilation.

(k) Cargo lines shall be traced with steam piping and secured thereto by lagging to prevent solidification of cargo during transfer operations.

(l) During cargo transfer, a water hose shall be connected to a water supply ready for immediate use, and any spillage of phosphorus shall be immediately washed down. This requirement can be met by facilities provided from shore.

(m) At least two fresh air masks or self-contained breathing apparatus shall be stowed on board the vessel at all times for use of personnel entering the tanks or adjacent spaces.

(n) Authorization from the Commandant (MHM) shall be obtained to transport lading other than phosphorus in the cargo tanks or to have on board any other cargo when phosphorus is laden in the tanks.

(o) Mechanical ventilation of sufficient capacity to insure a change of air within the cargo tanks every 3 minutes shall be provided during the inspection and maintenance of the cargo tanks.

(p) Cargo tanks shall be electrically bonded to the hull of the barge. A vessel shall be electrically bonded to the shore piping prior to connecting the cargo

hose. This electrical bonding shall be maintained until after the cargo hose has been disconnected.

§ 151.50-55 Liquid sulfur.

(a) Ventilation (cargo tank):

(1) Cargo tank ventilation shall be provided to maintain the concentration of H₂S below one-half of its lower explosive limit throughout the cargo tank vapor space for all conditions of carriage; i.e., below 1.85 percent by volume.

(2) Where mechanical ventilation systems are used for maintaining low gas concentrations in cargo tanks, an alarm system shall be provided to give warning if the system fails.

(3) Connections shall be provided to enable sampling of the atmosphere over the cargo in each cargo tank for analysis.

(4) The ventilation system shall be designed and arranged to preclude the depositing of sulfur within the system.

(b) Void spaces:

(1) Openings to void spaces adjacent to cargo tanks shall be designed and fitted to prevent the entry of water, sulfur or cargo vapors.

(2) Connections shall be provided to enable sampling and analyzing vapors in void spaces.

(c) Temperature controls shall be provided in accordance with § 151.20-10 and applicable sections of Subpart 151.40 of this part. Heat transfer media shall be steam, and alternate media will require specific approval of the Commandant.

§ 151.50-60 Ethyleneimine.

(a) (1) Ethyleneimine transported under the provisions of this part shall be not less than 99.9 percent pure.

(2) Unless otherwise authorized by the Commandant, no other cargo may be transported in tanks certified for ethyleneimine.

(b) Cargo tanks:

(1) All cargo tanks shall be constructed of carbon steel or stainless steel. Aluminum or silver or their alloys or silver solder shall not be used as materials of construction for tanks and equipment used in handling ethyleneimine.

(2) Cargo tanks shall meet the requirements of Class I pressure vessels.

(3) Cargo tanks shall be designed for the maximum pressure of vapor or gas used in discharging the cargo, but in no case shall the design pressure of such tanks be less than the one hundred (100) pounds per square inch gage. The tank shell and heads shall not be less than $\frac{5}{16}$ -inch thick.

(c) (1) Cargo tanks shall be located above or below deck in holds or enclosed spaces with the domes or trunks extended above the weatherdeck and terminating in the open. Provisions shall be made to maintain the watertightness of the deck by means of watertight seals around the domes or trunks. The holds or enclosed spaces in which the ethyleneimine tanks are located shall not be used for any other purpose. The watertightness of the weatherdeck may not be required to be fully maintained on open hopper type barges of a suitable design approved for such service.

(2) All cargo tanks shall be installed with the manhole openings and all tank connections located above the weather-deck in the open.

(3) Tanks shall be suitably mounted on steel supports anchored in place and suitably electrically bonded to the hull.

(4) No welding of any kind shall be done on cargo tanks or supporting structure unless authorized by the Commandant.

(d) Piping systems intended for ethyleneimine service shall not be used for any other product and shall be completely separate from all other systems. The piping system shall be designed so that no cross connections may be made either through accident or design.

(e) All valves, flanges and accessory equipment shall be of a type suitable for use with ethyleneimine and shall be made of steel, stainless steel, or other materials acceptable to the Commandant. Impurities of copper and silver shall be kept to a minimum. Such metals and their alloys shall not be used for valves, gages, or thermometers. All packing and gaskets shall be constructed of materials suitable for use with ethyleneimine.

(f) The pressure rating of valves, fittings and accessories shall be not less than the maximum pressure for which the cargo tank is designed or the shut-off head of the cargo pump, whichever is greater, but in no case less than 150 pounds per square inch, U.S.A.S.I. Standard B-16. Welded fittings shall be used wherever possible, and the number of pipe joints shall be held to a minimum. Threaded joints in the cargo liquid and vapor lines are prohibited.

(g) Filling and discharge piping shall extend to within four inches of the bottom of the tank or sump pit, if one is provided.

(h) Each cargo tank shall be equipped with either a temperature or pressure alarm system. Such system shall have either an audible or visual signal as part of the system.

(i) Automatic float continuous reading tape gage and similar types shall be fitted with a shutoff valve located as close to the tank as practicable and be designed to close automatically in the event of fracture of the external gage piping. An auxiliary gaging device shall always be used in conjunction with an automatic gaging device.

(j) Cargo shall be discharged by pumping or by displacement with nitrogen or other acceptable inert gas. In no case shall air be allowed to enter the system. During cargo transfer operations, the cargo vapor shall not be discharged to the atmosphere. The loading rate and the pressure applied to the tank to discharge the cargo shall be so limited to prevent opening the safety relief valves.

(k) Venting:

(1) Each safety relief valve shall be set to start to discharge at not less than 100 pounds per square inch gage, nor more than the design pressure of the tank.

(2) The discharge fittings from each safety relief or pressure vacuum relief

valve shall be directed in such a manner as to not impinge on another tank, piping or any other equipment which would increase the fire hazard should burning products be discharged from the safety or pressure vacuum relief valve as a result of a fire or other casualty. In addition, the discharge shall be directed away from areas where it is likely that persons might be working and as remote as practicable from ventilation inlets and ignition sources. A common discharge header may be employed if desired. The area near the discharge fittings shall be clearly marked as a hazardous area.

(3) A means shall be provided for either the reclamation or safe venting of vapors during the loading and unloading operations. For this purpose the safety relief or pressure vacuum relief valve shall be provided with a valved bypass to a vapor return line shore connection which shall be used whenever vapor return shore facilities are available. In the event vapors must be vented to the atmosphere, a vent riser shall be connected to the vapor return line and extend at least 12 feet above the highest level accessible to personnel. The vent riser may be collapsible for ease of stowage when not in use. The vent riser shall not be connected to a safety relief or pressure vacuum valve. Vapor return lines or vent risers for tanks carrying the same class product may be connected to a common header system. Tanks carrying ethyleneimine shall be vented independent of tanks carrying other products.

(4) The outlet of each vent riser shall be fitted with acceptable corrosion-resistant flame screen of suitable material or a flame arrester suitable for use with ethyleneimine.

(l) Ventilation:

(1) All enclosed spaces within the hull shall be vented or ventilated in accordance with the provisions of this subchapter except as otherwise provided for in this subpart.

(2) All ventilation machinery shall be of nonsparking construction and shall not provide a source of vapor ignition.

(3) Each vent shall be fitted with a flame screen of corrosion resistant wire which is suitable for use with ethyleneimine.

(m) Flexible metal hose fabricated of stainless steel or other acceptable material, resistant to the action of ethyleneimine, shall be fitted to the liquid and vapor lines during filling and discharging of the tanks.

(n) The cargo piping shall be inspected and tested at least once in each 2 calendar years.

(o) If cooling systems are used, compression of ethyleneimine is prohibited.

(p) Each cargo tank shall be electrically bonded to the hull. A vessel shall be electrically bonded to the shore piping prior to connecting the cargo hose. This electrical bonding shall be maintained until after the cargo hose has been disconnected and any spillage has been removed.

(q) When ethyleneimine is to be transported at or near atmospheric pres-

sure, the Commandant may permit the use of alternate methods of stowage if it is shown to his satisfaction that a degree of safety is obtained consistent with the minimum requirements of this subpart.

§ 151.50-65 Hydrogen fluoride. [Reserved]

Subpart 151.55—Special Requirements for Materials of Construction

§ 151.55-1 General.

(a) This section provides special requirements for the materials of construction of equipment that may come into contact with various cargoes. Table 151.05 contains specific requirements for various cargoes.

(b) Copper, copper alloys, zinc, and aluminum shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor.

(c) Copper, copper alloys, zinc, galvanized steel, and mercury shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor.

(d) Aluminum, magnesium, zinc, and lithium shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor.

(e) Copper and copper bearing alloys shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor.

(f) Aluminum or copper or alloys of either shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo vapor or liquid.

(g) Aluminum, stainless steel, or steel covered with a suitable protective lining or coating shall be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor.

(h) Alkaline or acidic materials, such as caustic soda or sulfuric acid, should not be allowed to contaminate this cargo.

(i) For concentrations of 98 percent or greater, aluminum or stainless steel shall be used as materials of construction. For concentrations of less than 98 percent, 304L or 316 stainless steel shall be used as materials of construction.

Effective date. The regulations in this document shall become effective on June 1, 1970.

Dated: February 13, 1970.

W. J. SMITH,
Admiral, U.S. Coast Guard,
Commandant.

[F.R. Doc. 70-1991; Filed, Feb. 24, 1970;
8:45 a.m.]